

Section 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product name: HUMBROL ENAMEL RANGE

Synonyms: PAINT RELATED MATERIAL

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.3. Details of the supplier of the safety data sheet**

Company name: Rustins Ltd

Waterloo Road

Cricklewood

London

NW2 7TX

United Kingdom

Tel: +44 (0)208 450 4666

Fax: +44 (0)208 452 2008

Email: rustins@rustins.co.uk

1.4. Emergency telephone number**Section 2: Hazards identification****2.1. Classification of the substance or mixture**

Classification under CHIP: -: R10; -: R66; -: R67

Classification under CLP: Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH208

Most important adverse effects: Flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

2.2. Label elements**Label elements under CLP:**

Hazard statements: EUH208: Contains zirconium drier 18%, methyl ethyl ketoxime. May produce an allergic reaction.

H226: Flammable liquid and vapour.

H336: May cause drowsiness or dizziness.

Signal words: Warning

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark



SAFETY DATA SHEET

HUMBROL ENAMEL RANGE

Page: 2

Precautionary statements: P271: Use only outdoors or in a well-ventilated area.
P280: Wear eye protection.
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing.
Rinse skin with water.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312: Call a POISON CENTER or doctor if you feel unwell.
P370+378: In case of fire: Use carbon dioxide for extinction.

Label elements under CHIP:

Risk phrases: R10: Flammable.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.

Precautionary phrases: Contains methyl ethyl ketoxime. May produce an allergic reaction.

2.3. Other hazards

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

XYLENE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
215-535-7	1330-20-7	-: R10; Xn: R20/21; Xi: R38	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	1-10%

Non-hazardous ingredients:

CALCIUM CARBOXYLATE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
271-376-3	68551-41-7	-	-	<1%

COBALT 6

EINECS	CAS	CHIP Classification	CLP Classification	Percent
-	-	Sens.: R42/43; -: R53	Eye Irrit. 2: H319; Skin Sens. 1: H317; Repr. 2: H361f; Aquatic Chronic 3: H412	<1%

METHYL ETHYL KETOXIME

EINECS	CAS	CHIP Classification	CLP Classification	Percent
-	-	Xi: R36; Sens.: R43	Acute Tox. 4: H312; Carc. 2: H351; Eye Dam. 1: H318; Skin Sens. 1: H317	<1%

Section 4: First aid measures

[cont...]

SAFETY DATA SHEET

HUMBROL ENAMEL RANGE

Page: 3

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious, check for breathing and apply artificial respiration if necessary. Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be vomiting and diarrhoea.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide (CO₂). Dry chemical powder. Alcohol resistant foam. Do not use water.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear protective clothing to prevent contact with skin and eyes. Wear self-contained breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Eliminate all sources of ignition. Mark out the contaminated area with signs and prevent access to unauthorised personnel. If outside do not approach from downwind. Mechanically ventilate the spillage area whilst avoiding the formation of explosive concentrations - see section 9 of SDS. If outside keep bystanders upwind and away from danger point. Evacuate the area immediately.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Alert the neighbourhood to the presence of fumes or gas.

[cont...]

SAFETY DATA SHEET

HUMBROL ENAMEL RANGE

Page: 4

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Wash the spillage site with large amounts of water. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks. Transfer to a suitable container. Wash the ground with an appropriate self-emulsifying solvent.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Earth any equipment used in handling. Use non-sparking tools. Avoid direct contact with the substance. Smoking is forbidden.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. The floor of the storage room must be impermeable to prevent the escape of liquids. Keep container tightly closed. Keep away from direct sunlight. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging. Glass. Coated steel.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

XYLENE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	220 mg/m ³	441 mg/m ³	-	-

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure all engineering measures mentioned in section 7 of SDS are in place. Ensure there is sufficient ventilation of the area. Ensure there is exhaust ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be used in handling. Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Nitrile gloves. PVC gloves.

Eye protection: Safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing, PVC.

[cont...]

SAFETY DATA SHEET

HUMBROL ENAMEL RANGE

Page: 5

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Various

Odour: Paraffinic.

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Not miscible

Viscosity: Viscous

Flash point°C: 38

Relative density: 0.93 - 1.02 @ 20C

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Avoid heat, flames and sparks. Direct sunlight.

10.5. Incompatible materials

Materials to avoid: Oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

Toxicity values: No data available.

[cont...]

SAFETY DATA SHEET

HUMBROL ENAMEL RANGE

Page: 6

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be vomiting and diarrhoea.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

Mobility: Insoluble in water. Partially absorbed into soil. Volatile.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT

including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: 3

[cont...]

SAFETY DATA SHEET

HUMBROL ENAMEL RANGE

Page: 7

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: Yes

14.6. Special precautions for user

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: Safety Data Sheet complies with UK regulatory references in accordance with CHIP 3.1.

Section 16: Other information

Other information

Phrases used in s.2 and 3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H226: Flammable liquid and vapour.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H361f: Suspected of damaging fertility.

R10: Flammable.

R20/21: Harmful by inhalation and in contact with skin.

R36: Irritating to eyes.

R38: Irritating to skin.

R42/43: May cause sensitisation by inhalation and skin contact.

R43: May cause sensitisation by skin contact.

R53: May cause long-term adverse effects in the aquatic environment.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.