



**Safety Data Sheet
EPT1-2016 HIGH SOLID EPOXY
PRIMER**

**Revision Date:
11 June, 2026**

Section 1. Identification

Product identifier

Product Identity

Other means of identification

EPT1-2016 HIGH SOLID EPOXY PRIMER
NON CHROMATE - HIGH SOLID EPOXY
PRIMER

Relevant identified uses of the substance or mixture and uses advised against

See Technical Data Sheet.

Details of the supplier of the safety data sheet

Company Name

3Chem LLC
1700 West Sheridan
Oklahoma City, OK. 73106

Emergency

24 hour Emergency Telephone No.

24 Hour Chemical Emergency Response: (Spill,
Leak, Fire, Exposure or Accident) Call INFOTRAC -
Day or Night 1-800-535-5053
Outside the USA, Call Collect 1-352-323-3500
1-866-324-3666

Customer Service:

Section 2. Hazard(s) identification

Classification of the substance or mixture under OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7)

Flammable Liquid, category 2;H225

Highly Flammable liquid and vapor.

Skin corrosion/irritation category 2;H315

Causes skin irritation.

Serious eye damage / eye irritation,
category 2A;H319

Causes serious eye irritation.

Skin sensitizer category 1;H317

May cause an allergic skin reaction.

Aquatic toxicity (acute), category 3;H402

Harmful to aquatic life.

Aquatic toxicity (chronic), category
3;H412

Harmful to aquatic life with long lasting effects.

Label elements



Danger

H225 Highly flammable liquid and vapor.

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H412 Harmful to aquatic life with long lasting effects.

[Prevention]

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking.
- P233 Keep container tightly closed.
- P235 Keep cool.
- P240 Ground and bond container and receiving equipment.
- P241 Use explosion-proof electrical, ventilating, light, equipment.
- P242 Use non-sparking tools.
- P243 Take action to prevent static discharges.
- P260 Do not breathe dust, fume, mist, vapors or spray.
- P261 Avoid breathing dust, fume, gas, mist, vapors, spray.
- P262 Do not get in eyes, on skin, or on clothing.
- P264 Wash thoroughly after handling.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves, eye protection, and face protection.

[Response]

- P301+310 IF SWALLOWED: Immediately call a POISON CENTER, doctor or physician.
- P302+352 IF ON SKIN: Wash with plenty of soap and water.
- P303+361+353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P331 Do NOT induce vomiting.
- P333+313 If skin irritation or a rash occurs: Get medical advice or attention.
- P337+313 If eye irritation persists: Get medical advice or attention.
- P362+364 Take off contaminated clothing and wash it before reuse.
- P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

[Storage]

- P403+235 Store in a well ventilated place. Keep cool.

[Disposal]

- P501 Dispose of contents or container in accordance with local and national regulations.

Other hazards

This product contains no PBT/vPvB/vPvM chemicals.

This product contains no endocrine disrupting chemicals.

Does NOT contain component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS) per the US EPA PFASMASTER combined list of PFAS chemicals.

Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the OSHA’s Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7).

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
EPOXY RESIN CAS Number: 25036-25-3 Synonyms: Bisphenol A diglycidyl ether - bisphenol A copolymer	10 - 30	Serious eye damage / eye irritation, category 2;H319	No data available

		Skin corrosion/irritation category 2;H315 Skin sensitizer category 1;H317	
Magnesium silicate talc CAS Number: 14807-96-6 Synonyms: TALC (Mg ₃ H ₂ (SiO ₃) ₄), Talc containing asbestiform fibers	10 - 30	Not Classified	No data available
Iron hydroxide oxide yellow CAS Number: 51274-00-1 Synonyms: CI 77492 Pigment Yellow 42, Yellow Iron Oxide	3 - 7	Not Classified	No data available
Xylene CAS Number: 1330-20-7 Synonyms: 1,2-xylene; 1,3-xylene; 1,4-xylene; Benzene, dimethyl-, Dimethylbenzene, Methyl toluene, Solvent B-2, Xylene, mixture of isomers	3 - 7	Flammable Liquid, category 3;H226 Acute toxicity(inhalation), category 4;H332 Acute toxicity(dermal), category 4;H312 Skin corrosion/irritation category 2;H315	No data available
Chlorite (mg al silicate) CAS Number: 1318-59-8 Synonyms: No available information	3 - 7	Serious eye damage / eye irritation, category 2;H319	No data available
N-Butyl Acetate CAS Number: 123-86-4 Synonyms: Acetic acid, butyl ester, Butyl acetate, n-Butyl axetat	3 - 7	Flammable Liquid, category 3;H226 Specific target organ toxicity, Single exposure category 3;H336	No data available
Tert-Butyl Acetate CAS Number: 540-88-5 Synonyms: Butyl acetate	3 - 7	Flammable Liquid, category 2;H225	No data available
Butanone CAS Number: 78-93-3 Synonyms: Methyl ethyl ketone	3 - 7	Flammable Liquid, category 2;H225 Serious eye damage / eye irritation, category 2;H319 Specific target organ toxicity, Single exposure category 3;H336	No data available
Dolomite CAS Number: 16389-88-1 Synonyms: Calcidol, Virpazar, Sindofom K, Gurhofite	1 - 5	Not Classified	No data available
2-Methoxy-1-Methylethyl Acetate CAS Number: 108-65-6 Synonyms: Propylene glycol monomethyl ether acetate, 1-Methoxy-2-propyl acetate	1 - 5	Flammable Liquid, category 3;H226	No data available
Titanium dioxide CAS Number: 13463-67-7 Synonyms: C47051, C475001	1 - 5	Not Classified	No data available
Diglycidyl ether of bisphenol A CAS Number: 25068-38-6 Synonyms: Epoxy Resin	0.5 - 1.5	Serious eye damage / eye irritation, category 2;H319: C ≥ 5 % Skin corrosion/irritation category 2;H315: C ≥ 5 % Skin sensitizer category 1;H317 Aquatic toxicity (chronic), category 2;H411	No data available
Crystalline Silica - Quartz CAS Number: 14808-60-7 Synonyms: Quartz	0.1 - 1	Not Classified	No data available

The actual concentration or concentration range is withheld as a trade secret.

*PBT/vPvB - PBT, vPvM or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes

Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

Skin

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Ingestion

If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Overview

No chronic toxicity or long term toxicity information available. Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Eyes

Causes serious eye irritation.

Skin

May cause an allergic skin reaction. Causes skin irritation.

Section 5. Fire-fighting measures**Extinguishing media**

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.

Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: No hazardous decomposition data available.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking.

Keep container tightly closed.

Keep cool.

Ground and bond container and receiving equipment.

Use explosion-proof electrical, ventilating, light, equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Do not breathe dust, fume, mist, vapors or spray.

Avoid breathing dust, fume, gas, mist, vapors, spray.

Do not get in eyes, on skin, or on clothing.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

ERG Guide No. 128

Section 6. Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Put on appropriate personal protective equipment (see section 8).

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8. Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

See section 2 for further details. - [Prevention]

Conditions for safe storage, including any incompatibilities

Incompatible materials: No available information

See section 2 for further details. - [Storage]

Specific end use(s)

No available information

Section 8. Exposure controls / personal protection

Control parameters

Exposure Limits

CAS No.	Ingredient	Source	Value
78-93-3	Butanone	OSHA	200 ppm, 590 mg/m ³
		ACGIH	TWA: 75 ppm STEL: 150 ppm
		NIOSH	TWA 200 ppm (590 mg/m ³) STEL: 300 ppm (885 mg/m ³)
108-65-6	2-Methoxy-1-Methylethyl Acetate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
123-86-4	N-Butyl Acetate	OSHA	150 ppm, 710 mg/m ³
		ACGIH	TWA: 50 ppm STEL: 150 ppm
		NIOSH	TWA 150 ppm (710 mg/m ³) STEL: 200 ppm (950 mg/m ³)
540-88-5	Tert-Butyl Acetate	OSHA	200 ppm, 950 mg/m ³
		ACGIH	TWA: 50 ppm STEL: 150 ppm
		NIOSH	TWA 200 ppm (950 mg/m ³)
1318-59-8	Chlorite (mg al silicate)	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
1330-20-7	Xylene	OSHA	100 ppm, 435 mg/m ³
		ACGIH	TWA: 20 ppm
		NIOSH	No Established Limit
13463-67-7	Titanium dioxide	OSHA	15 mg/m ³ (total dust), 5 mg/m ³ (respirable fraction)
		ACGIH	Nanoscale 0.2 mg/m ³ (R) Respirable fraction - finescale 2.5 mg/m ³ ®
		NIOSH	See Appendix A: NIOSH Potential Occupational Carcinogens
14807-96-6	Magnesium silicate talc	OSHA	20 mppcf (less than 1% crystalline silica):
		ACGIH	TWA: 2 mg/m ³ (E,R) asbestos and crystalline silica < 1%, Respirable
		NIOSH	TWA 2 mg/m ³ (resp)
14808-60-7	Crystalline Silica - Quartz	OSHA	250/(%SiO ₂ +5) mppcf, 10 (%SiO ₂ +2) mg/m ³
		ACGIH	TWA: 0.025 mg/m ³ (R) Respirable fraction
		NIOSH	0.05 mg/m ³ TWA (respirable)
16389-88-1	Dolomite	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
25036-25-3	EPOXY RESIN	OSHA	No Established Limit
		ACGIH	No Established Limit

		NIOSH	No Established Limit
25068-38-6	Diglycidyl ether of bisphenol A	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
51274-00-1	Iron hydroxide oxide yellow	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes Protective safety glasses recommended

Skin Avoid skin contact. Protective gloves recommended.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

Information on basic physical and chemical properties

Physical State	Liquid
Color	Green
Odor	Mild
Odor threshold	No available information
Melting point / freezing point	No available information
Initial boiling point and boiling range	210 °F - 281 °F
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1.1% Upper Explosive Limit: 7.6%
Flash Point	13.89 °C / 57 °F
Auto-ignition temperature	No available information
Decomposition temperature	No available information
pH	No available information
Viscosity (cSt)	No available information
Solubility in Water	No available information
Partition coefficient n-octanol/water (Log Kow)	No available information
Vapor pressure (Pa)	No available information
Relative Density	1.339
Vapor Density	Heavier than air
Evaporation rate (Ether = 1)	No available information
VOC Content	2.878 lbs/gal - 344.8 g/L
Oxidising properties	No available information
Explosive properties	No available information
Other information	No other relevant information.

Section 10. Stability and reactivity

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Possibility of hazardous reactions

No available information

Conditions to avoid

Avoid high temperatures and contact with incompatible material

Incompatible materials

No available information

Hazardous decomposition products

No hazardous decomposition data available.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
EPOXY RESIN - (25036-25-3)	No data available.	No data available.	No data available.	No data available.	No data available.
Magnesium silicate talc - (14807-96-6)	> 5,000.00, Rat - Category: NA	No data available.	No data available.	No data available.	No data available.
Iron hydroxide oxide yellow - (51274-00-1)	> 10,000, Rat - Category: NA	No data available.	No data available.	No data available.	No data available.
Xylene - (1330-20-7)	4,299.00, Rat - Category: 5	1,548.00, Rabbit - Category: 4	No data available.	No data available.	5,000.00, Rat - Category: 4
Chlorite (mg al silicate) - (1318-59-8)	No data available.	No data available.	No data available.	No data available.	No data available.
N-Butyl Acetate - (123-86-4)	10,760.00, Rat - Category: NA	17,600.00, Rabbit - Category: NA	No data available.	No data available.	No data available.

Tert-Butyl Acetate - (540-88-5)	4,100.00, Rat - Category: 5	> 2,000.00, Rabbit - Category: NA	No data available.	No data available.	No data available.
Butanone - (78-93-3)	No data available.	6,480.00, Rabbit - Category: NA	32.00, Mouse - Category: NA	No data available.	No data available.
Dolomite - (16389-88-1)	5,000.00, Rat - Category: 5	No data available.	No data available.	No data available.	No data available.
2-Methoxy-1-Methylethyl Acetate - (108-65-6)	5,155.00, Rat - Category: NA	> 2,000.00, Rabbit - Category: NA	No data available.	No data available.	No data available.
Titanium dioxide - (13463-67-7)	> 25,000.00, Rat - Category: NA	No data available.	No data available.	6.82, Rat - Category: NA	No data available.
Diglycidyl ether of bisphenol A - (25068-38-6)	> 5,000.00, Rat - Category: NA	20,000.00, Rabbit - Category: NA	No data available.	No data available.	No data available.
Crystalline Silica - Quartz - (14808-60-7)	No data available.	100,000.00 - Category: NA	No data available.	No data available.	No data available.

Carcinogen Data

CAS No.	Ingredient	Source	Value
78-93-3	Butanone	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit
108-65-6	2-Methoxy-1-Methylethyl Acetate	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit
123-86-4	N-Butyl Acetate	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit
540-88-5	Tert-Butyl Acetate	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit
1318-59-8	Chlorite (mg al silicate)	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit
1330-20-7	Xylene	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 3
		ACGIH	A4
13463-67-7	Titanium dioxide	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 2b
		ACGIH	A3
14807-96-6	Magnesium silicate talc	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 2a
		ACGIH	A4
14808-60-7	Crystalline Silica - Quartz	OSHA	Regulated Carcinogen: No;
		NTP	Known: Yes; Suspected: No;
		IARC	No
		ACGIH	A2
16389-88-1	Dolomite	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit
25036-25-3	EPOXY RESIN	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit

25068-38-6	Diglycidyl ether of bisphenol A	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit
51274-00-1	Iron hydroxide oxide yellow	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit
Classification		Category	Hazard Description
Acute toxicity (oral)		---	Not Applicable
Acute toxicity (dermal)		---	Not Applicable
Acute toxicity (inhalation)		---	Not Applicable
Skin corrosion/irritation		2	Causes skin irritation.
Serious eye damage/irritation		2A	Causes serious eye irritation.
Respiratory sensitization		---	Not Applicable
Skin sensitization		1	May cause an allergic skin reaction.
Germ cell mutagenicity		---	Not Applicable
Carcinogenicity		---	Not Applicable
Reproductive toxicity		---	Not Applicable
STOT-single exposure		---	Not Applicable
STOT-repeated exposure		---	Not Applicable
Aspiration hazard		---	Not Applicable

Possible routes of entry:

Inhalation, ingestion, skin contact, and skin absorption.

Symptoms and effects, both acute and delayed:

No chronic toxicity or long term toxicity information available. Treat symptomatically.

Eyes Causes serious eye irritation.

Skin May cause an allergic skin reaction. Causes skin irritation.

Section 12. Ecological information

Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
EPOXY RESIN - (25036-25-3)	No data available.	No data available.	No data available.
Magnesium silicate talc - (14807-96-6)	110,000.00, Fishes species	36,812.36, Daphnid species	7,202.70, Green algae
Iron hydroxide oxide yellow - (51274-00-1)	1,000.00, Leuciscus idus	No data available.	No data available.
Xylene - (1330-20-7)	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00, Chlorococcales
Chlorite (mg al silicate) - (1318-59-8)	No data available.	No data available.	No data available.
N-Butyl Acetate - (123-86-4)	18.00, Pimephales promelas	44.00, Daphnia sp	246.00, Pseudokirchnerella subcapitata

Tert-Butyl Acetate - (540-88-5)	327.00, Pimephales promelas	No data available.	1,300.00, Chlorococcales
Butanone - (78-93-3)	2,993.00, Pimephales promelas	308.00, Daphnia magna	2,029.00, Pseudokirchnerella subcapitata
Dolomite - (16389-88-1)	No data available.	No data available.	No data available.
2-Methoxy-1-Methylethyl Acetate - (108-65-6)	161.00, Pimephales promelas	501.00, Daphnia magna	> 1,000, Pseudokirchnerella subcapitata
Titanium dioxide - (13463-67-7)	294.00, Oryzias latipes	501.00, Daphnia magna	101.00, Pseudokirchnerella subcapitata
Diglycidyl ether of bisphenol A - (25068-38-6)	3.10, Pimephales promelas	1.40, Daphnia magna	No data available.
Crystalline Silica - Quartz - (14808-60-7)	No data available.	No data available.	No data available.

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

No available information

Mobility in soil

No available information

Results of PBT and vPvB assessment

This product contains no PBT/vPvB/vPvM chemicals.

Other adverse effects

No available information

Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.

Section 14. Transport information



	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
UN number	UN1263	UN1263	UN1263
UN proper shipping name	UN1263, Paint, 3, II	Paint	Paint
Transport hazard class(es)	Class: 3 Sub Class: Not Applicable	Class: 3 Sub Class: Not Applicable	Class: 3 Sub Class: Not Applicable
Packing group	II	II	II
Environmental hazards			

IMDG Marine Pollutant: No;

Special precautions for user

No available information

Section 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Classification of the substance or mixture under OSHA’s Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7)

Toxic Substance Control Act (TSCA)

CAS Number	Ingredient	Toxic Substance Control Act (TSCA)	Comments	Status
0000526-73-8	1,2,3-Trimethylbenzene	Yes		ACTIVE
0000095-63-6	1,2,4-trimethyl benzene	Yes		ACTIVE
0000108-67-8	1,3,5-trimethylbenzene	Yes		ACTIVE
0000077-99-6	1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-	Yes		ACTIVE
0000108-65-6	2-Methoxy-1-Methylethyl Acetate	Yes	PMN	ACTIVE
0070657-70-4	2-Methoxy-1-propanol acetate	No		
0007760-50-1	Basic magnesium carbonate	Yes		ACTIVE
0000103-65-1	Benzene, propyl-	Yes		ACTIVE
0025551-13-7	Benzene, trimethyl-	Yes		ACTIVE
0000078-93-3	Butanone	Yes		ACTIVE
0068187-76-8	Castor oil, sulfated, sodium salt	Yes	UVCB T	ACTIVE
0001318-59-8	Chlorite (mg al silicate)	No		
0014808-60-7	Crystalline Silica - Quartz	Yes		ACTIVE
0000098-82-8	Cumene	Yes		ACTIVE
0025068-38-6	Diglycidyl ether of bisphenol A	Yes	XU	ACTIVE
0016389-88-1	Dolomite	Yes		ACTIVE
0025036-25-3	EPOXY RESIN	Yes	XU	ACTIVE
0000100-41-4	Ethylbenzene	Yes		ACTIVE
0051274-00-1	Iron hydroxide oxide yellow	Yes		ACTIVE
0001317-65-3	Limestone	Yes	UVCB	ACTIVE
0014807-96-6	Magnesium silicate talc	Yes		ACTIVE
0000123-86-4	N-Butyl Acetate	Yes		ACTIVE
0064742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	Yes	UVCB	ACTIVE
0007664-38-2	Phosphoric acid	Yes		ACTIVE
Proprietary	Proprietary additive	No		
0064742-95-6	Solvent naphtha (petroleum), light aromatic	Yes	UVCB	ACTIVE
0008052-41-3	Stoddard solvent	Yes	UVCB	ACTIVE
0000540-88-5	Tert-Butyl Acetate	Yes		ACTIVE
0013463-67-7	Titanium dioxide	Yes		ACTIVE
0000108-88-3	Toluene	Yes		ACTIVE
0001330-20-7	Xylene	Yes		ACTIVE
0001314-13-2	Zinc oxide	Yes		ACTIVE

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

- Ethylbenzene
- Xylene

Proposition 65 - Carcinogens (>0.0%):

- Cumene
- Ethylbenzene

Proposition 65 - Developmental Toxins (>0.0%):

- Toluene

Proposition 65 - Female Repro Toxins (>0.0%):

Toluene

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 Label Warning:

WARNING: This product can expose you to chemicals including [Cumene, Ethylbenzene], which are known to the State of California to cause cancer, and [Toluene], which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

NFPA	Health Hazards	Flammability	Instability	Special Hazards
	2	4	0	--
HMIS	Health Hazards	Flammability	Physical Hazards	Personal Protection
	2	4	0	

Section 16. Other information

Revision Date 11 June, 2026

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness and dizziness.

H411 Toxic to aquatic life with long lasting effects.

Disclaimer: The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

End of Document