

# SAFETY DATA SHEET

## REN-WELD 5169 RESIN US

### Section 1. Identification

**GHS product identifier** : REN-WELD 5169 RESIN US  
**Product code** : 00066883  
**Other means of identification** : Not available.  
**Product type** : Liquid.  
**Material uses** : Component of a Polyurethane System  
**Supplier's details** : Huntsman Advanced Materials Americas LLC  
P.O. Box 4980  
The Woodlands, TX 77387  
  
Non-Emergency phone: (800) 257-5547  
  
**e-mail address of person responsible for this SDS** : MSDS@huntsman.com  
  
**Emergency telephone number (24h/7day)** : Chemtrec: (800) 424-9300 or (703) 527-3887

### Section 2. Hazards identification

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).  
  
**Classification of the substance or mixture** : ACUTE TOXICITY: INHALATION - Category 4  
SKIN CORROSION/IRRITATION - Category 2  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2B  
RESPIRATORY SENSITIZATION - Category 1  
SKIN SENSITIZATION - Category 1  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3  
  
Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 22%  
Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 22%

#### GHS label elements

##### Hazard pictograms



##### Signal word

: Danger

##### Hazard statements

: Harmful if inhaled.  
Causes skin and eye irritation.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause an allergic skin reaction.  
May cause respiratory irritation.

## Section 2. Hazards identification

**Precautionary statements** : Wear protective gloves. Wear eye or face protection. In case of inadequate ventilation wear respiratory protection. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. If experiencing respiratory symptoms: Call a POISON CENTER or physician. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Other hazards which do not result in classification** : Not available.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture

Ingredient name	%	CAS number
Diphenylmethane 4,4'-diisocyanate	30 - 60	101-68-8
Methylenediphenyldiisocyanate (mixed isomers)	13 - 30	26447-40-5
Diphenylmethane diisocyanate, homopolymer	7 - 13	39310-05-9

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**Occupational exposure limits, if available, are listed in Section 8.**

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
- Inhalation** : Move exposed person to fresh air. Get medical attention immediately. Treatment is symptomatic for primary irritation or bronchospasm. If breathing is laboured, oxygen should be administered by qualified personnel.
- Skin contact** : After contact with skin, wash immediately with plenty of warm soapy water: Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. An MDI study has demonstrated that a polyglycol-based skin cleanser (such as D-Tam™, PEG-400) or corn oil may be more effective than soap and water. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Provided the patient is conscious, wash out mouth with water. Get medical attention if symptoms appear.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes eye irritation.

## Section 4. First aid measures

- Inhalation** : Harmful if inhaled. May cause respiratory irritation. This product is a respiratory irritant and potential respiratory sensitizer: repeated inhalation of vapour or aerosol at levels above the occupational exposure limit could cause respiratory sensitisation. Symptoms may include irritation to the eyes, nose, throat and lungs, possibly combined with dryness of the throat, tightness of chest and difficulty in breathing. The onset of the respiratory symptoms may be delayed for several hours after exposure. A hyper-reactive response to even minimal concentrations of MDI may develop in sensitised persons. LC50 (rat) : ca. 490 mg/m<sup>3</sup> (4 hours) : using experimentally produced respirable aerosol having aerodynamic diameter <5microns.
- Skin contact** : Causes skin irritation. May cause sensitization by skin contact. Animal studies have shown that respiratory sensitisation can be induced by skin contact with known respiratory sensitizers including diisocyanates. These results emphasize the need for protective clothing including gloves to be worn at all times when handling these chemicals or in maintenance work.
- Ingestion** : Low oral toxicity, but ingestion may cause irritation of the gastrointestinal tract.

### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
wheezing and breathing difficulties  
asthma
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Symptomatic treatment and supportive therapy as indicated. Following severe exposure the patient should be kept under medical review for at least 48 hours.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

- Flash point** : Closed cup: >93.33°C (>200°F) [Estimated]
- Extinguishing media**
- Suitable extinguishing media** : Foam, CO2 or dry powder.
- Unsuitable extinguishing media** : Water may be used if no other available and then in copious quantities. Reaction between water and hot isocyanate may be vigorous. Prevent washings from entering water courses, keep fire exposed containers cool by spraying with water.

## Section 5. Fire-fighting measures

- Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Hazardous thermal decomposition products** : Combustion products may include: carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons and HCN.
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. PVC boots, gloves, safety helmet and protective clothing should be worn.
- Remark** : Due to reaction with water producing CO<sub>2</sub>-gas, a hazardous build-up of pressure could result if contaminated containers are re-sealed. Containers may burst if overheated.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Methods and materials for containment and cleaning up** : If the product is in its solid form: Spilled MDI flakes should be picked up carefully. The area should be vacuum cleaned to remove remaining dust particles completely. If the product is in its liquid form: Absorb spillages onto sand, earth or any suitable adsorbent material. Leave to react for at least 30 minutes. Shovel into open-top drums for further decontamination. Wash the spillage area with water. Test atmosphere for MDI vapour. Neutralise small spillages with decontaminant. Remove and dispose of residues. The compositions of liquid decontaminants are given in Section 16. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** :

## Section 7. Handling and storage

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous.

### Advice on general occupational hygiene

- : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### Conditions for safe storage, including any incompatibilities

- : Store in accordance with local regulations. Keep container tightly closed in a cool, well-ventilated place. Keep away from moisture. Due to reaction with water producing CO<sub>2</sub>-gas, a hazardous build-up of pressure could result if contaminated containers are re-sealed. Do not reseal contaminated containers. Uncontaminated containers, free of moisture, may be resealed only after placing under a nitrogen blanket. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Unsuitable containers: Do not store in containers made of copper, copper alloys or galvanized surfaces.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
Diphenylmethane 4,4'-diisocyanate	<b>ACGIH TLV (United States, 6/2013).</b> TWA: 0.005 ppm 8 hours. <b>OSHA PEL (United States, 2/2013).</b> CEIL: 0.02 ppm CEIL: 0.2 mg/m <sup>3</sup>

### Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Diisocyanates can only be smelled if the occupational exposure limit has been exceeded considerably.

Medical supervision of all employees who handle or come in contact with respiratory sensitizers is recommended. Personnel with a history of asthma-type conditions, bronchitis or skin sensitisation conditions should not work with MDI based products. The Occupational Exposure Limits listed do not apply to previously sensitised individuals. Sensitised individuals should be removed from any further exposure.

### Environmental exposure controls

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

## Section 8. Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Hand protection** : Use chemical resistant gloves classified under Standard EN374: protective gloves against chemicals and microorganisms. Examples of glove materials that might provide suitable protection include :Butyl rubber, Chlorinated polyethylene, Polyethylene, Ethyl vinyl alcohol copolymers laminated ("EVAL"), Polychloroprene (Neoprene\*), Nitrile/butadiene rubber ("nitrile" or "NBR"), Polyvinyl chloride ("PVC" or "vinyl"), Fluoroelastomer (Viton\*).
- When prolonged or frequently repeated contact may occur, a glove with protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN374) is recommended.
- Contaminated gloves should be decontaminated and disposed of.  
Notice: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all requisite workplace factors such as, but not limited to : other chemicals that may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), as well as instructions/ specifications provided by the glove supplier. Protective gloves should be worn when handling freshly made polyurethane products to avoid contact with trace residual materials which may be hazardous in contact with skin.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Overall (preferably heavy cotton) or Tyvek-Pro Tech 'C' , Tyvek-Pro 'F' disposable coverall.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Thermal hazards** : Not available.

## Section 9. Physical and chemical properties

### Appearance

- Physical state** : Liquid. [Liquid.]
- Color** : Not available.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point/Freezing point** : Not available.
- Boiling/condensation point** : Not available.
- Flash point** : Closed cup: >93.33°C (>200°F) [Estimated]

## Section 9. Physical and chemical properties

<b>Evaporation rate</b>	: Not available.
<b>Flammability (solid, gas)</b>	: Not available.
<b>Lower and upper explosive (flammable) limits</b>	: Not available.
<b>Vapor pressure</b>	: Not available.
<b>Vapor density</b>	: Not available.
<b>Relative density</b>	: Not available.
<b>Solubility in water</b>	: Reacts with water
<b>Partition coefficient: n-octanol/water</b>	: Not available.
<b>Auto-ignition temperature</b>	: >600°C
<b>Decomposition temperature</b>	: Not available.
<b>Viscosity</b>	: Not available.

## Section 10. Stability and reactivity

<b>Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>Chemical stability</b>	: Stable at room temperature.
<b>Possibility of hazardous reactions</b>	: Reaction with water (moisture) produces CO <sub>2</sub> -gas. Exothermic reaction with materials containing active hydrogen groups. The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of the reaction partners is good or is supported by stirring or by the presence of solvents. MDI is insoluble with, and heavier than water and sinks to the bottom but reacts slowly at the interface. A solid water-insoluble layer of polyurea is formed at the interface by liberating carbon dioxide gas.
<b>Conditions to avoid</b>	: Avoid high temperatures.
<b>Incompatible materials</b>	: Water, alcohols, amines, bases, and acids.
<b>Hazardous decomposition products</b>	: Combustion products may include: carbon oxides (CO, CO <sub>2</sub> ) nitrogen oxides (NO, NO <sub>2</sub> etc.) hydrocarbons and HCN

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Test	Endpoint	Species	Result
Diphenylmethane 4,4'-diisocyanate	OECD 403 Acute Inhalation Toxicity	LC50 Inhalation Dusts and mists	Rat - Male, Female	0.49 mg/l
	OECD 402 Acute Dermal Toxicity	LD50 Dermal	Rabbit - Male, Female	>9400 mg/kg
	OECD 401 Acute Oral Toxicity	LD50 Oral	Rat - Male	>10000 mg/kg
Methylenediphenyldiisocyanate (mixed isomers)	OECD 403 Acute Inhalation Toxicity	LC50 Inhalation Dusts and mists	Rat - Male, Female	>2.24 mg/l
	OECD 403 Acute	LC50 Inhalation Dusts	Rat - Male,	0.49 mg/l

3/25/2014.

Not available.

7/18

## Section 11. Toxicological information

Diphenylmethane diisocyanate, homopolymer	Inhalation Toxicity OECD 402 Acute Dermal Toxicity No official guidelines	and mists LD50 Dermal  LD50 Oral	Female Rabbit - Male, Female Rat - Male, Female	>9400 mg/kg  >2000 mg/kg
	OECD 403 Acute Inhalation Toxicity OECD 402 Acute Dermal Toxicity OECD 425 Acute Oral Toxicity: Up-and-Down Procedure	LC50 Inhalation Dusts and mists LD50 Dermal  LD50 Oral	Rat - Male, Female Rabbit - Male, Female Rat - Female	0.49 mg/l  >9400 mg/kg  >5000 mg/kg

### Conclusion/Summary :

Diphenylmethane 4,4'-diisocyanate      Irritating to respiratory system.

### Irritation/Corrosion

Product/ingredient name	Test	Species	Result
Diphenylmethane 4,4'-diisocyanate	OECD 404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Irritant
	OECD 405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Non-irritant.
Diphenylmethane diisocyanate, homopolymer	OECD 405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Non-irritant.
	-	Rabbit	Skin - Irritant

### Conclusion/Summary

#### Skin

: Diphenylmethane 4,4'-diisocyanate      Irritating to skin.  
Methylenediphenyldiisocyanate (mixed isomers)      No additional information.  
Diphenylmethane diisocyanate, homopolymer      Irritating to skin.

#### Eyes

: Diphenylmethane 4,4'-diisocyanate      Based on the human occupational exposure data, this substance is considered as irritating to eyes.  
Methylenediphenyldiisocyanate (mixed isomers)      No additional information.  
Diphenylmethane diisocyanate, homopolymer      Based on the human occupational exposure data, this substance is considered as irritating to eyes.

#### Respiratory

: Diphenylmethane 4,4'-diisocyanate      No additional information.  
Methylenediphenyldiisocyanate (mixed isomers)      No additional information.  
Diphenylmethane diisocyanate, homopolymer      No additional information.

### Sensitization

## Section 11. Toxicological information

Product/ingredient name	Test	Route of exposure	Species	Result
Diphenylmethane 4,4'-diisocyanate	OECD 429 Skin Sensitization: Local Lymph Node Assay	skin	Mouse	Sensitizing
	OECD 406 Skin Sensitization	skin	Guinea pig	Not sensitizing
	No official guidelines	Respiratory	Guinea pig	Sensitizing
Methylenediphenyldiisocyanate (mixed isomers)	OECD 406 Skin Sensitization	skin	Guinea pig	Not sensitizing
	No official guidelines	Respiratory	Guinea pig	Sensitizing
	OECD 429 Skin Sensitization: Local Lymph Node Assay	skin	Mouse	Sensitizing
Diphenylmethane diisocyanate, homopolymer	OECD 406 Skin Sensitization	skin	Guinea pig	Sensitizing
	No official guidelines	Respiratory	Guinea pig	Sensitizing

### Mutagenicity

Product/ingredient name	Test	Result
Diphenylmethane 4,4'-diisocyanate	Experiment: In vitro Subject: Bacteria Metabolic activation: +/-	Negative
	Experiment: In vivo Subject: Mammalian-Animal	Negative
Methylenediphenyldiisocyanate (mixed isomers)	Experiment: In vitro Subject: Bacteria Metabolic activation: +/-	Negative
	Experiment: In vivo Subject: Mammalian-Animal	Negative
Diphenylmethane diisocyanate, homopolymer	Experiment: In vitro Subject: Bacteria Metabolic activation: +/-	Negative
	Experiment: In vivo Subject: Mammalian-Animal	Negative

### Conclusion/Summary :

Diphenylmethane 4,4'-diisocyanate No mutagenic effect.

### Carcinogenicity

Product/ingredient name	Test	Species	Dose	Exposure	Result/Result type
Diphenylmethane 4,4'-diisocyanate	OECD 453 Combined Chronic Toxicity/ Carcinogenicity Studies	Rat - Male, Female	1 mg/m <sup>3</sup>	2 years; 5 days per week	Positive - Inhalation - NOAEL
Methylenediphenyldiisocyanate (mixed isomers)	OECD 453	Rat - Male,	1 mg/m <sup>3</sup>	2 years; 5	Negative -

3/25/2014.

Not available.

9/18



## Section 11. Toxicological information

Diphenylmethane diisocyanate, homopolymer	Combined Chronic Toxicity/ Carcinogenicity Studies OECD 453 Combined Chronic Toxicity/ Carcinogenicity Studies	Female  Rat - Male, Female	1 mg/m <sup>3</sup>	days per week  2 years; 5 days per week	Inhalation - NOAEL  Negative - Inhalation - NOAEL
---	--	----------------------------------	---------------------	---	---

### Carcinogenic class

Product/ingredient name	IARC	OSHA
Diphenylmethane 4,4'-diisocyanate	3	-

### Reproductive toxicity

Product/ingredient name	Test	Species	Maternal toxicity	Fertility	Developmental effects
Methylenediphenyldiisocyanate (mixed isomers)	OECD 414 Prenatal Developmental Toxicity Study	Rat - Male, Female	Negative	Negative	Negative

### Conclusion/Summary :

Diphenylmethane 4,4'-diisocyanate No known significant effects or critical hazards.

### Teratogenicity

Product/ingredient name	Test	Species	Result/Result type
Diphenylmethane 4,4'-diisocyanate	OECD 414 Prenatal Developmental Toxicity Study	Rat - Female	Negative - Inhalation
Methylenediphenyldiisocyanate (mixed isomers)	OECD 414 Prenatal Developmental Toxicity Study	Rat - Female	Negative - Inhalation
Diphenylmethane diisocyanate, homopolymer	OECD 414 Prenatal Developmental Toxicity Study	Rat - Female	Negative - Inhalation

### Conclusion/Summary :

Diphenylmethane 4,4'-diisocyanate No known significant effects or critical hazards.

### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Diphenylmethane 4,4'-diisocyanate	Category 3	Not applicable.	Respiratory tract irritation
Methylenediphenyldiisocyanate (mixed isomers)	Category 3	Not applicable.	Respiratory tract irritation
Diphenylmethane diisocyanate, homopolymer	Category 3	Not applicable.	Respiratory tract irritation

## Section 11. Toxicological information

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

- Eye contact** : Causes eye irritation.
- Inhalation** : Harmful if inhaled. May cause respiratory irritation. This product is a respiratory irritant and potential respiratory sensitizer: repeated inhalation of vapour or aerosol at levels above the occupational exposure limit could cause respiratory sensitisation. Symptoms may include irritation to the eyes, nose, throat and lungs, possibly combined with dryness of the throat, tightness of chest and difficulty in breathing. The onset of the respiratory symptoms may be delayed for several hours after exposure. A hyper-reactive response to even minimal concentrations of MDI may develop in sensitised persons. LC50 (rat) : ca. 490 mg/m<sup>3</sup> (4 hours) : using experimentally produced respirable aerosol having aerodynamic diameter <5microns.
- Skin contact** : Causes skin irritation. May cause sensitization by skin contact. Animal studies have shown that respiratory sensitisation can be induced by skin contact with known respiratory sensitizers including diisocyanates. These results emphasize the need for protective clothing including gloves to be worn at all times when handling these chemicals or in maintenance work.
- Ingestion** : Low oral toxicity, but ingestion may cause irritation of the gastrointestinal tract.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
wheezing and breathing difficulties  
asthma
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

## Section 11. Toxicological information

### Potential chronic health effects

Product/ingredient name	Test	Endpoint	Species	Result
Methylenediphenyldiisocyanate (mixed isomers)	OECD 453 Combined Chronic Toxicity/ Carcinogenicity Studies	Chronic NOEC Inhalation Dusts and mists	Rat - Male, Female	0.2 mg/m <sup>3</sup>
Diphenylmethane diisocyanate, homopolymer	OECD 453 Combined Chronic Toxicity/ Carcinogenicity Studies	Chronic NOEC Inhalation Dusts and mists	Rat - Male, Female	0.2 mg/m <sup>3</sup>

- General** : May cause damage to organs through prolonged or repeated exposure if inhaled. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : Rats have been exposed for two years to a respirable aerosol of polymeric MDI which resulted in chronic pulmonary irritation at high concentrations. Only at the top level (6 mg/m<sup>3</sup>), there was a significant incidence of a benign tumour of the lung (adenoma) and one malignant tumour (adenocarcinoma). There were no lung tumours at 1 mg/m<sup>3</sup> and no effects at 0.2 mg/m<sup>3</sup>. Overall, the tumour incidence, both benign and malignant, and the number of animals with the tumours were not different from controls. The increased incidence of lung tumours is associated with prolonged respiratory irritation and the concurrent accumulation of yellow material in the lung, which occurred throughout the study. In the absence of prolonged exposure to high concentrations leading to chronic irritation and lung damage, it is highly unlikely that tumour formation will occur.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No birth defects were seen in two independent animal (rat) studies. Fetotoxicity was observed at doses that were extremely toxic (including lethal) to the mother. Fetotoxicity was not observed at doses that were not maternally toxic. The doses used in these studies were maximal, respirable concentrations, which are well in excess of defined occupational exposure limits.
- Fertility effects** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Inhalation (vapors)	46.5 mg/l
Inhalation (dusts and mists)	1.986 mg/l

**Other information** : Not available.

## Section 12. Ecological information

### Toxicity

## Section 12. Ecological information

Product/ingredient name	Test	Endpoint	Exposure	Species	Result
Diphenylmethane 4,4'-diisocyanate	OECD 202 <i>Daphnia</i> sp. Acute Immobilisation Test	Acute EC50	24 hours Static	Daphnia	>1000 mg/l
	OECD 203 Fish, Acute Toxicity Test	Acute LC50	96 hours Static	Fish	>1000 mg/l
	OECD 211 <i>Daphnia Magna</i> Reproduction Test	Chronic NOEC	21 days Semi-static	Daphnia	>=10 mg/l
	OECD 201 Alga, Growth Inhibition Test	Chronic NOECr	72 hours Static	Algae	1640 mg/l
Methylenediphenyldiisocyanate (mixed isomers)	OECD 201 Alga, Growth Inhibition Test	Acute EC50	72 hours Static	Algae	>1640 mg/l
	OECD 209 Activated Sludge, Respiration Inhibition Test	Acute EC50	3 hours Static	Bacteria	>100 mg/l
	OECD 202 <i>Daphnia</i> sp. Acute Immobilisation Test	Acute EC50	24 hours Static	Daphnia	>1000 mg/l
	OECD 203 Fish, Acute Toxicity Test	Acute LC50	96 hours Static	Fish	>1000 mg/l
Diphenylmethane diisocyanate, homopolymer	OECD 211 <i>Daphnia Magna</i> Reproduction Test	Chronic NOEC	21 days Semi-static	Daphnia	>10 mg/l
	OECD 201 Alga, Growth Inhibition Test	Chronic NOECr	72 hours Static	Algae	1640 mg/l
	OECD 201 Alga, Growth Inhibition Test	Acute EC50	72 hours Static	Algae	>1640 mg/l
	OECD 209 Activated Sludge, Respiration Inhibition Test	Acute EC50	3 hours Static	Bacteria	>100 mg/l
Diphenylmethane diisocyanate, homopolymer	OECD 202 <i>Daphnia</i> sp. Acute Immobilisation Test	Acute EC50	24 hours Static	Daphnia	>1000 mg/l
	OECD 203 Fish, Acute Toxicity Test	Acute LC50	96 hours Static	Fish	>1000 mg/l
	OECD 211 <i>Daphnia Magna</i> Reproduction Test	Chronic NOEC	21 days Semi-static	Daphnia	>=10 mg/l
	OECD 201 Alga, Growth Inhibition Test	Chronic NOECr	72 hours Static	Algae	1640 mg/l

### Persistence and degradability

Product/ingredient name	Test	Period	Result
Diphenylmethane 4,4'-diisocyanate	OECD 302C Inherent Biodegradability: Modified MITI Test (II)	28 days	0 %
Methylenediphenyldiisocyanate (mixed isomers)	OECD 302C Inherent Biodegradability: Modified MITI Test (II)	28 days	0 %
Diphenylmethane diisocyanate, homopolymer	OECD 302C Inherent Biodegradability: Modified MITI Test (II)	28 days	0 %

## Section 12. Ecological information

**Conclusion/Summary** : Diphenylmethane 4,4'-diisocyanate Not biodegradable

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Diphenylmethane 4,4'-diisocyanate	Fresh water 0.83 days	-	Not readily
Methylenediphenyldiisocyanate (mixed isomers)	-	-	Not readily
Diphenylmethane diisocyanate, homopolymer	-	-	Not readily

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Diphenylmethane 4,4'-diisocyanate	4.51	200	low
Methylenediphenyldiisocyanate (mixed isomers)	4.51	439	low
Diphenylmethane diisocyanate, homopolymer	8.56	200	low

### Mobility in soil

**Mobility** : By considering the production and use of the substance, it is unlikely that significant environmental exposure in the air or water will arise. Immiscible with water, but will react with water to produce inert and non-biodegradable solids. Conversion to soluble products, including diamino- diphenylmethane (MDA), is very low under the optimal laboratory conditions of good dispersion and low concentration. In air, the predominant degradation process is predicted to be a relatively rapid OH radical attack, by calculation and by analogy with related diisocyanates.

**Other adverse effects** : No known significant effects or critical hazards.

### Other ecological information

**BOD5** : Not determined.

**COD** : Not determined.

**TOC** : Not determined.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**Disposal should be in accordance with applicable regional, national and local laws and regulations.**

## Section 14. Transport information

### Proper shipping name

**DOT** : OTHER REGULATED SUBSTANCES, LIQUID, N.O.S. (Methylene Diphenyl Diisocyanate)  
**TDG** : Not regulated.  
**IMDG** : Not regulated.  
**IATA** : Not regulated.

Regulatory information	UN number	Classes	PG*	Label	Additional information
<b>DOT Classification</b>	NA3082	9	III		<b>Reportable quantity 5000 lbs. (2270 kg)</b> Single containers less than 5,000 lbs. are not regulated.
<b>TDG Classification</b>	Not regulated.	-	-		-
<b>IMDG Classification</b>	Not regulated.	-	-		-
<b>IATA Classification</b>	Not regulated.	-	-		-

PG\* : Packing group

## Section 15. Regulatory information

### Safety, health and environmental regulations specific for the product

#### United States Regulations

**TSCA 8(b) inventory** : All components are listed or exempted.

**TSCA 5(a)2 final significant new use rule (SNUR)** : No ingredients listed.

**TSCA 5(e) substance consent order** : No ingredients listed.

**TSCA 12(b) export notification** : No ingredients listed.

**SARA 311/312** : Immediate (acute) health hazard

	<u>Product name</u>	<u>Concentration %</u>
<b>Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)</b>	: Diphenylmethane 4,4'-diisocyanate	49.545

## Section 15. Regulatory information

**Clean Air Act - Ozone Depleting Substances (ODS)** : This product does not contain nor is it manufactured with ozone depleting substances.

	<u>Product name</u>	<u>Concentration %</u>
<b>SARA 313 Form R - Reporting requirements</b>	: Diphenylmethane 4,4'-diisocyanate	49.545

	<u>Ingredient name</u>	<u>%</u>	<u>Section 304 CERCLA Hazardous Substance</u>	<u>CERCLA Reportable Quantity (Lbs)</u>	<u>Product Reportable Quantity (Lbs)</u>
<b>CERCLA Hazardous substances</b>	: Diphenylmethane 4,4'-diisocyanate	49.5446	Listed	5000	10092

### State regulations

**PENNSYLVANIA - RTK** : Diphenylmethane 4,4'-diisocyanate

**California Prop 65** : This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

### Canadian regulations

**CEPA DSL** : At least one component is not listed.

**WHMIS Classes** : WHMIS Class D-2A: Material causing other toxic effects (Very toxic).  
WHMIS Class D-2B: Material causing other toxic effects (Toxic).

**This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.**

### Brazil Regulations

**Classification system used** : Norma ABNT-NBR 14725-2:2012

### International lists

: **Australia inventory (AICS)**: Not determined.  
: **China inventory (IECSC)**: Not determined.  
: **Japan inventory**: Not determined.  
: **Korea inventory**: Not determined.  
: **Malaysia Inventory (EHS Register)**: Not determined.  
: **New Zealand Inventory of Chemicals (NZIoC)**: Not determined.  
: **Philippines inventory (PICCS)**: Not determined.  
: **Taiwan inventory (CSNN)**: Not determined.

## Section 16. Other information


**Hazardous Material Information System (U.S.A.)** :

<b>Health</b>	*	2
<b>Flammability</b>		1
<b>Physical hazards</b>		1
<b>Personal protection</b>		

**The customer is responsible for determining the PPE code for this material.**

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**National Fire Protection Association (U.S.A.)** :



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

**Date of printing** : 3/25/2014.  
**Date of issue** : 3/25/2014.  
**Date of previous issue** : No previous validation.  
**Version** : 1

📌 **Indicates information that has changed from previously issued version.**

Liquid decontaminants (percentages by weight or volume) :

Decontaminant 1 : \*- sodium carbonate : 5 - 10 % \*- liquid detergent : 0.2 - 2 % \*- water : to make up to 100 %

Decontaminant 2 : \*- concentrated ammonia solution : 3 - 8 % \*- liquid detergent : 0.2 - 2 % \*- water : to make up to 100 %

Decontaminant 1 reacts slower with diisocyanates but is more environmentally friendly than decontaminant 2.

Decontaminant 2 contains ammonia. Ammonia presents health hazards. (See supplier safety information.)

Literature reference: PU 193-1 : 'MDI-Based Compositions : Hazards and Safe Handling Procedures.'

PU 181-15 : Recommended melting procedures for MDI-based isocyanates.

ISOPA Guidelines for safe Loading/Unloading, Transportation, Storage of TDI and MDI , Ref.03-96 PSC-0005-GUIDL.

SPI PMDI User Guidelines for the Chemical Protective Clothing Selection.

References of methods used in the Physico-Chemical Properties section are reported in Annex V part A to Commission Directive 92/69/EEC of 31 July 1992 adapting to technical progress for the Seventeenth time Council Directive 67/548/EEC.

[Notice to reader](#)

## Section 16. Other information

*While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.*

**IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.**

**THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.**

*Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.*

**NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.**

# SAFETY DATA SHEET

## REN-WELD 5169 HARDENER

### Section 1. Identification

**GHS product identifier** : REN-WELD 5169 HARDENER  
**Product code** : 00066884  
**Other means of identification** : Not available.  
**Product type** : Liquid.  
**Material uses** : Component of a Polyurethane System  
**Supplier's details** : Huntsman Advanced Materials Americas LLC  
P.O. Box 4980  
The Woodlands, TX 77387  
  
Non-Emergency phone: (800) 257-5547  
  
**e-mail address of person responsible for this SDS** : MSDS@huntsman.com  
  
**Emergency telephone number (24h/7day)** : Chemtrec: (800) 424-9300 or (703) 527-3887

### Section 2. Hazards identification

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Classification of the substance or mixture** : ACUTE TOXICITY: ORAL - Category 4  
SKIN CORROSION/IRRITATION - Category 2  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
CARCINOGENICITY - Category 2  
TOXIC TO REPRODUCTION [Fertility] - Category 1B  
TOXIC TO REPRODUCTION [Unborn child] - Category 1B  
AQUATIC HAZARD (ACUTE) - Category 3  
AQUATIC HAZARD (LONG-TERM) - Category 3

**GHS label elements**

**Hazard pictograms** : 

**Signal word** : Danger

**Hazard statements** : Harmful if swallowed.  
Causes serious eye damage.  
Causes skin irritation.  
May damage fertility or the unborn child.  
Suspected of causing cancer.  
Harmful to aquatic life with long lasting effects.

## Section 2. Hazards identification

**Precautionary statements** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. IF exposed or concerned: Get medical attention. IF SWALLOWED: Call a POISON CENTER or physician if you feel unwell. Rinse mouth. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Other hazards which do not result in classification** : None known.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture

Ingredient name	%	CAS number
POLYPROPYLENE GLYCOL	13 - 30	25322-69-4
Polyether polyol	13 - 30	25791-96-2
Polyoxypropylenediamine	3 - 7	9046-10-0
DIBUTYL PHTHALATE (DBP)	1 - 3	84-74-2
diethyl methylene dianiline	0.1 - 1	19900-65-3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**Occupational exposure limits, if available, are listed in Section 8.**

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

## Section 4. First aid measures

- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Skin contact** : Causes skin irritation.
- Ingestion** : Harmful if swallowed. May cause burns to mouth, throat and stomach.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
stomach pains  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

## Section 4. First aid measures

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

**Flash point** : Closed cup: >93.33°C (>200°F) [Estimated]

### Extinguishing media

**Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing media** : None known.

**Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
metal oxide/oxides

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

## Section 6. Accidental release measures

**Methods and materials for containment and cleaning up** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
DIBUTYL PHTHALATE (DBP)	<b>ACGIH TLV (United States, 6/2013).</b> TWA: 5 mg/m <sup>3</sup> 8 hours. <b>OSHA PEL (United States, 2/2013).</b> TWA: 5 mg/m <sup>3</sup> 8 hours.

**Appropriate engineering controls** : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## Section 8. Exposure controls/personal protection

### Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Thermal hazards** : Not available.

## Section 9. Physical and chemical properties

### Appearance

- Physical state** : Liquid.
- Color** : Red.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point/Freezing point** : Not available.
- Boiling/condensation point** : Not available.
- Flash point** : Closed cup: >93.33°C (>200°F) [Estimated]
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Not available.
- Vapor pressure** : Not available.
- Vapor density** : Not available.
- : 1.12

## Section 9. Physical and chemical properties

### Relative density

- Solubility in water** : Slight
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Not available.

## Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : No specific data.
- Incompatible materials** : No specific data.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Test	Endpoint	Species	Result
POLYPROPYLENE	-	LD50 Oral	Rat	541 to 57000 mg/kg
GLYCOL	-	LD50 Oral	Rat	>2000 mg/kg
Polyether polyol	OECD 402 Acute Dermal Toxicity	LD50 Dermal	Rat - Male, Female	>2000 mg/kg
	OECD 401 Acute Oral Toxicity	LD50 Oral	Rat - Male, Female	933 to 1072 mg/kg
Polyoxypropylenediamine	-	LD50 Dermal	Rabbit	2090 mg/kg
	-	LD50 Oral	Rat	480 mg/kg
DIBUTYL PHTHALATE (DBP)	No official guidelines	LC50 Inhalation Dusts and mists	Rat - Male, Female	>15.68 mg/l
	No official guidelines	LD50 Dermal	Rabbit	>20000 mg/kg
	OECD 401 Acute Oral Toxicity	LD50 Oral	Rat - Male, Female	6279 mg/kg
diethyl methylene dianiline	-	LC50 Inhalation Dusts and mists	Rat - Male, Female	>0.85 mg/l
	OECD 402 Acute Dermal Toxicity	LD50 Dermal	Rat - Male, Female	2080 mg/kg
	OECD 401 Acute Oral Toxicity	LD50 Oral	Rat	444 mg/kg

#### Irritation/Corrosion

## Section 11. Toxicological information

Product/ingredient name	Test	Species	Result
POLYPROPYLENE GLYCOL	-	Rabbit	Skin - Non-irritant.
Polyether polyol	-	Rabbit	Eyes - Non-irritant.
	OECD 405 Acute Eye Irritation/ Corrosion	Rabbit	Eyes - Non-irritant.
	OECD 404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Non-irritant.
DIBUTYL PHTHALATE (DBP)	OECD 405 Acute Eye Irritation/ Corrosion	Rabbit	Eyes - Non-irritant.
	OECD 404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Non-irritant.
diethyl methylene dianiline	EPA OPPTS OPPTS 870.2500 Acute Dermal Irritation	Rabbit	Skin - Non-irritant.
	EPA OPPTS EPA OTS 798.4500	Rabbit	Eyes - Non-irritant.

### Conclusion/Summary

<b>Skin</b>	:	POLYPROPYLENE	Slightly irritating to the skin.
		GLYCOL	
		Polyether polyol	Non-irritating to the skin.
		Polyoxypropylenediamine	No additional information.
		DIBUTYL PHTHALATE (DBP)	Non-irritating to the skin.
		diethyl methylene dianiline	Non-irritating to the skin.
<b>Eyes</b>	:	POLYPROPYLENE	Slightly irritating to the eyes.
		GLYCOL	
		Polyether polyol	Non-irritating to the eyes.
		Polyoxypropylenediamine	No additional information.
		DIBUTYL PHTHALATE (DBP)	Non-irritating to the eyes.
		diethyl methylene dianiline	Non-irritating to the eyes.
<b>Respiratory</b>	:	POLYPROPYLENE	No additional information.
		GLYCOL	
		Polyether polyol	No additional information.
		Polyoxypropylenediamine	No additional information.
		DIBUTYL PHTHALATE (DBP)	No additional information.
		diethyl methylene dianiline	No additional information.

### Sensitization

Product/ingredient name	Test	Route of exposure	Species	Result
POLYPROPYLENE GLYCOL	-	skin	Human	Not sensitizing
Polyether polyol	OECD 406 Skin Sensitization	skin	Guinea pig	Not sensitizing
DIBUTYL PHTHALATE (DBP)	OECD 406 Skin Sensitization	skin	Guinea pig	Not sensitizing
diethyl methylene dianiline	-	skin	Human	Sensitizing

### Mutagenicity

## Section 11. Toxicological information

Product/ingredient name	Test	Result
POLYPROPYLENE GLYCOL	Experiment: In vitro Subject: Bacteria	Negative
Polyether polyol	Metabolic activation: + Experiment: In vitro Subject: Mammalian-Animal	Negative
	Metabolic activation: +/- Experiment: In vitro Subject: Mammalian-Human	Negative
	Metabolic activation: +/- Experiment: In vitro Subject: bacteria/yeast	Negative
DIBUTYL PHTHALATE (DBP)	Metabolic activation: +/- Experiment: In vitro Subject: Bacteria	Negative
	Metabolic activation: +/- Experiment: In vitro Subject: Mammalian-Animal	Negative
	Metabolic activation: +/- Experiment: In vitro Subject: Yeast	Negative
	Metabolic activation: +/- Experiment: In vitro Subject: bacteria/yeast	Negative
	Metabolic activation: +/- Experiment: In vivo Subject: Mammalian-Animal	Negative
diethyl methylene dianiline	Experiment: In vitro Subject: bacteria/yeast	Positive
	Metabolic activation: +/- Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Positive

### Conclusion/Summary :

Aluminium oxide	Not mutagenic in a standard battery of genetic toxicological tests.
DIBUTYL PHTHALATE (DBP)	Not mutagenic in a standard battery of genetic toxicological tests.
diethyl methylene dianiline	The weight of the scientific evidence indicates that this material is genotoxic.

### Carcinogenicity

Product/ingredient name	Test	Species	Dose	Exposure	Result/Result type
diethyl methylene dianiline	OECD 451 Carcinogenicity Studies	Rat - Male, Female	9 to 10 mg/kg	103 weeks; 24 hours per day	Positive - Oral - LOAEL

### Conclusion/Summary :

DIBUTYL PHTHALATE (DBP)	In accordance with column 2 of Annex VII - X of Regulation (EC) No 1907/2006, the test for this property of the substance does not need to be conducted.
-------------------------	--

### Reproductive toxicity

## Section 11. Toxicological information

Product/ingredient name	Test	Species	Maternal toxicity	Fertility	Developmental effects
Polyether polyol	OECD 421 Reproduction/ Developmental Toxicity Screening Test	Rat - Male, Female	Negative	Negative	Negative
DIBUTYL PHTHALATE (DBP)	No official guidelines	Rat - Male, Female	Positive	Positive	Positive

**Conclusion/Summary** : Aluminium oxide No known significant effects or critical hazards.

### Teratogenicity

Product/ingredient name	Test	Species	Result/Result type
DIBUTYL PHTHALATE (DBP)	No official guidelines No official guidelines	Mouse Rat - Male, Female	Positive - Oral Positive - Oral

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Skin contact** : Causes skin irritation.
- Ingestion** : Harmful if swallowed. May cause burns to mouth, throat and stomach.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

## Section 11. Toxicological information

- Skin contact** : Adverse symptoms may include the following:  
 pain or irritation  
 redness  
 blistering may occur  
 reduced fetal weight  
 increase in fetal deaths  
 skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
 stomach pains  
 reduced fetal weight  
 increase in fetal deaths  
 skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

### Potential chronic health effects

Product/ingredient name	Test	Endpoint	Species	Result
POLYPROPYLENE GLYCOL	-	Sub-chronic NOEL Oral	Rat	3 %
	-	Sub-chronic NOAEL Dermal	Rat	1000 mg/kg/d
Polyether polyol	OECD 407 Repeated Dose 28-day Oral Toxicity Study in Rodents	Sub-chronic NOAEL Oral	Rat - Male, Female	>1000 mg/kg/d
DIBUTYL PHTHALATE (DBP)	OECD 408 Repeated Dose 90-Day Oral Toxicity Study in Rodents	Sub-chronic NOAEL Oral	Rat - Male, Female	152 mg/kg/d
	OECD 412 Repeated Dose Inhalation Toxicity: 28-day or 14-day Study	Sub-chronic NOEC Inhalation Dusts and mists	Rat - Male, Female	509 mg/m <sup>3</sup>
diethyl methylene dianiline	OECD 408 Repeated Dose 90-Day Oral Toxicity Study in Rodents	Sub-chronic LOAEL Oral	Rat - Male, Female	7.5 to 8 mg/kg/d
	-	Sub-chronic NOAEL Dermal	Rat - Male, Female	3 mg/kg/d
	-	Sub-chronic LOAEL Oral	Rat - Male, Female	8 mg/kg

- General** : No known significant effects or critical hazards.
- Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

## Section 11. Toxicological information

- Mutagenicity** : No known significant effects or critical hazards.  
**Teratogenicity** : May damage the unborn child.  
**Developmental effects** : No known significant effects or critical hazards.  
**Fertility effects** : May damage fertility.

### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Oral	1340.4 mg/kg
Dermal	45434.8 mg/kg

**Other information** : Not available.

## Section 12. Ecological information

### Toxicity

Product/ingredient name	Test	Endpoint	Exposure	Species	Result	
POLYPROPYLENE GLYCOL	DIN DIN 38412 Part 11	Acute EC50	24 hours	Daphnia	>1000 mg/l	
	-	Acute LC0	48 hours	Fish	4600 mg/l	
	-	Acute LC0	96 hours	Fish	500 mg/l	
	-	Acute LC50	96 hours	Fish	>100 mg/l	
	-	Acute LC50	96 hours	Fish	>500 mg/l	
	Polyether polyol	OECD 202 <i>Daphnia</i> sp. Acute Immobilisation Test	Acute EC50	48 hours	Daphnia	>100 mg/l
		EU EC C.11 Biodegradation: Activated Sludge Respiration Inhibition Test.	Acute IC50	3 hours	Bacteria	>10000 mg/l
		EU EC C.3 Algal Inhibition Test	Acute LC50	96 hours	Algae	>100 mg/l
		EU EC C.1 Acute Toxicity for Fish	Acute LC50	96 hours	Fish	>1000 mg/l
		OECD 211 <i>Daphnia Magna</i> Reproduction Test	Chronic NOEC	21 days	Daphnia	>10 mg/l
-		Acute EC50	48 hours	Daphnia	15 mg/l	
Polyoxypropylenediamine	-	Acute IC50	72 hours	Algae	135 mg/l	
	-	Acute LC50	96 hours	Fish	>100 mg/l	
	-	Acute EC50	10 days	Algae	0.75 mg/l	
DIBUTYL PHTHALATE (DBP)	No official guidelines	Acute EC50	Static	Bacteria	2.2 mg/l	
	EPA OPPTS	Acute EC50	48 hours	Daphnia	2.99 mg/l	
	EPA OPPTS	Acute LC50	96 hours	Daphnia	0.5 mg/l	
	OECD 203 Fish, Acute Toxicity Test	Acute LC50	96 hours	Fish	0.48 mg/l	
	No official guidelines	Chronic NOEC	10 days	Algae	0.39 mg/l	
	-	Chronic NOEC	Static	Bacteria	>10 mg/l	
	DIN DIN 38412 Part	Chronic NOEC	30 minutes	Bacteria	>10 mg/l	

## Section 12. Ecological information

diethyl methylene dianiline	27			Static			
	No official guidelines	Chronic	NOEC	10 days	Daphnia	0.1	mg/l
	No official guidelines	Chronic	NOECr	99 days	Fish	0.1	mg/l
	OECD 202 <i>Daphnia</i> sp. Acute	Acute	EC50	48 hours	Daphnia	0.35	mg/l
	Immobilisation Test			Static			
	OECD 203 Fish, Acute Toxicity Test	Acute	LC50	96 hours	Fish	20.6	mg/l
	OECD 211 <i>Daphnia Magna</i> Reproduction Test	Chronic	NOEC	21 days	Daphnia	0.00525	mg/l
				Semi-static			

### Persistence and degradability

Product/ingredient name	Test	Period	Result
POLYPROPYLENE GLYCOL	OECD 301F Ready Biodegradability - Manometric Respirometry Test	28 days	>70 %
Polyether polyol	OECD 301B Ready Biodegradability - CO <sub>2</sub> Evolution Test	28 days	40 %
	OECD 302A Inherent Biodegradability: Modified SCAS Test	28 days	1.9 %
DIBUTYL PHTHALATE (DBP)	EPA OPPTS	21 days	>97 %
	EU EC C.4-C Biodegradation: Determination of the "Ready" Biodegradability: Carbon Dioxide Evolution Test	28 days	81 %

**Conclusion/Summary** : Aluminium oxide In accordance with column 2 of Annex VII - X of Regulation (EC) No 1907/2006, the test for this property of the substance does not need to be conducted.

DIBUTYL PHTHALATE (DBP) Readily biodegradable

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
POLYPROPYLENE GLYCOL	-	-	Readily
Polyether polyol	-	-	Not readily
DIBUTYL PHTHALATE (DBP)	Fresh water 2.7 days	-	Readily

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Polyether polyol	-1.82 to -0.73	-	low
DIBUTYL PHTHALATE (DBP)	4.46	<1	low

### Mobility in soil

Not available.

**Other adverse effects** : No known significant effects or critical hazards.

### Other ecological information

**BOD5** : Not determined.

**COD** : Not determined.

## Section 12. Ecological information

**TOC** : Not determined.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

## Section 14. Transport information

### Proper shipping name

**DOT** : Not regulated.

**TDG** : Not regulated.

**IMDG** : Not regulated.

**IATA** : Not regulated.

Regulatory information	UN number	Classes	PG*	Label	Additional information
<b>DOT Classification</b>	Not regulated.	-	-		-
<b>TDG Classification</b>	Not regulated.	-	-		-
<b>IMDG Classification</b>	Not regulated.	-	-		-
<b>IATA Classification</b>	Not regulated.	-	-		-

PG\* : Packing group

## Section 15. Regulatory information

### Safety, health and environmental regulations specific for the product

#### United States Regulations

**TSCA 8(b) inventory** : All components are listed or exempted.

**TSCA 5(a)2 final significant new use rule (SNUR)** : No ingredients listed.

**TSCA 5(e) substance consent order** : No ingredients listed.

**TSCA 12(b) export notification** : No ingredients listed.

**SARA 311/312** : Immediate (acute) health hazard  
Delayed (chronic) health hazard

	<u>Product name</u>	<u>Concentration %</u>
<b>Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)</b>	: Dibutyl phthalate	1.02

**Clean Air Act - Ozone Depleting Substances (ODS)** : This product does not contain nor is it manufactured with ozone depleting substances.

	<u>Product name</u>	<u>Concentration %</u>
<b>SARA 313 Form R - Reporting requirements</b>	: Aluminium oxide	3.1314
	DIBUTYL PHTHALATE (DBP)	1.02

	<u>Ingredient name</u>	<u>%</u>	<u>Section 304 CERCLA Hazardous Substance</u>	<u>CERCLA Reportable Quantity (Lbs)</u>	<u>Product Reportable Quantity (Lbs)</u>
<b>CERCLA Hazardous substances</b>	: DIBUTYL PHTHALATE (DBP)	1.02	Listed	10	980

#### State regulations

**PENNSYLVANIA - RTK** : Aluminium oxide, Amorphous silica, Dibutyl phthalate

**California Prop 65** : **WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

<u>Ingredient name</u>	<u>Cancer</u>	<u>Reproductive</u>
DIBUTYL PHTHALATE (DBP)	No.	Yes.

#### Canadian regulations

**CEPA DSL** : At least one component is not listed.

## Section 15. Regulatory information

**WHMIS Classes** : Class D-2A: Material causing other toxic effects (Very toxic).  
Class D-2B: Material causing other toxic effects (Toxic).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

### Brazil Regulations

**Classification system used** : Norma ABNT-NBR 14725-2:2012

### International lists

: **Australia inventory (AICS)**: Not determined.  
**China inventory (IECSC)**: Not determined.  
**Japan inventory**: At least one component is not listed.  
**Korea inventory**: At least one component is not listed.  
**Malaysia Inventory (EHS Register)**: Not determined.  
**New Zealand Inventory of Chemicals (NZIoC)**: At least one component is not listed.  
**Philippines inventory (PICCS)**: At least one component is not listed.  
**Taiwan inventory (CSNN)**: Not determined.

## Section 16. Other information


**Hazardous Material Information System (U.S.A.)** :

Health	*	3
Flammability		1
Physical hazards		0
Personal protection		

The customer is responsible for determining the PPE code for this material.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**National Fire Protection Association (U.S.A.)** :



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

**Date of printing** : 3/25/2014.  
**Date of issue** : 3/25/2014.  
**Date of previous issue** : No previous validation.

## Section 16. Other information

Version : 1

✔ Indicates information that has changed from previously issued version.

### Notice to reader

*While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.*

**IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.**

**THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.**

*Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.*

**NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.**