

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Revision Date 14-Feb-2025 Version 1

1. Identification

Product identifier

Product Name SURFACE PREP 4.50Z AE

Other means of identification

Product Code 24163

UN number or ID number 1950

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Surface active agent

Restrictions on use No information available

Details of the supplier of the safety data sheet

Manufacturer Address May Also Be Distributed by:

ITW Permatex, Inc. ITW Permatex Canada 6875 Parkland Blvd. 101-2360 Bristol Circle

Solon, Ohio 44139 USA Oakville, ON Canada L6H 6M5 Telephone: 1-87-Permatex Telephone: (800) 924-6994

(866) 732-9502

E-mail address mail@permatex.com

Emergency telephone number

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

24-hour emergency phone number No information available

2. Hazard(s) identification

Classification

Aerosols	Category 1
Skin corrosion/irritation	Category 2
Germ cell mutagenicity	Category 1B
Reproductive toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Aspiration hazard	Category 1

Label elements

Contains HEPTANE; ISOBUTANE; ORGANO-COPPER COMPOUND



Danger

Hazard statements

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes skin irritation.

May cause genetic defects.

May damage fertility or the unborn child.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Use personal protective equipment as required.

Wash face, hands and any exposed skin thoroughly after handling.

Avoid breathing dust, fume, gas, mist, vapors and spray.

Use only outdoors or in a well-ventilated area.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Pressurized container: Do not pierce or burn, even after use.

Do not spray on an open flame or other ignition source.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see .? on this label).

Skin

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice and attention.

Take off contaminated clothing and wash before reuse.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Protect from sunlight.

Precautionary Statements - Disposal

Dispose of contents and container to an approved waste disposal plant.

97 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.

34 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.

71 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).

99 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).

32 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Other Information

May be harmful in contact with skin. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
HEPTANE	142-82-5	45-70%	-	-
PROPANE	74-98-6	10-30%	-	-
ISOBUTANE	75-28-5	10-30%	-	-
ETHANOL	64-17-5	1-5%	-	-
ORGANO-COPPER COMPOUND	22221-10-9	0.1-1%	-	-

4. First-aid measures

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Inhalation Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing

has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult,

(trained personnel should) give oxygen. Delayed pulmonary edema may occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and

persists.

Skin contact In case of contact with liquefied gas, thaw frosted parts with lukewarm water. Wash off

immediately with soap and plenty of water for at least 15 minutes. Get medical attention if

irritation develops and persists.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious

person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Get immediate medical attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s)

involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Avoid

contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Inhalation of high vapor

concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting.

Effects of Exposure May cause adverse reproductive effects - such as birth defect, miscarriages, or infertility.

Mutagenic effects.

Indication of any immediate medical attention and special treatment needed

Revision Date 14-Feb-2025

Note to physicians Because of the danger of aspiration, emesis or gastric lavage should not be employed

unless the risk is justified by the presence of additional toxic substances.

5. Fire-fighting measures

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray.

Small FireIn case of fire, use water spray, foam, dry chemical, or CO2.
Large Fire
In case of fire, use water spray, foam, dry chemical, or CO2.

Unsuitable extinguishing media DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

Specific hazards arising from the chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Ruptured cylinders may rocket.

Hazardous combustion products No information available.

Explosion data

Sensitivity to mechanical impact Yes. **Sensitivity to static discharge** Yes.

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions

Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Contents under pressure. Empty containers pose a potential fire

and explosion hazard. Do not cut, puncture or weld containers.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce

vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might

cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapors or mists. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

8. Exposure controls/personal protection

Control parameters Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
HEPTANE	TWA: 400 ppm	TWA: 500 ppm	IDLH: 750 ppm
142-82-5	STEL: 500 ppm	TWA: 2000 mg/m ³	Ceiling: 440 ppm 15 min
		(vacated) TWA: 400 ppm	Ceiling: 1800 mg/m³ 15 min
		(vacated) TWA: 1600 mg/m ³	TWA: 85 ppm
		(vacated) STEL: 500 ppm	TWA: 350 mg/m ³
		(vacated) STEL: 2000 mg/m ³	
PROPANE	: See Appendix F:	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6	Minimal Oxygen Content,	TWA: 1800 mg/m ³	TWA: 1000 ppm
	explosion hazard	(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
	Simple asphyxiant	(vacated) TWA: 1800 mg/m ³	
ISOBUTANE	STEL: 1000 ppm explosion	-	TWA: 800 ppm
75-28-5	hazard		TWA: 1900 mg/m ³
ETHANOL	STEL: 1000 ppm	TWA: 1000 ppm	IDLH: 3300 ppm
64-17-5		TWA: 1900 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1900 mg/m ³
		(vacated) TWA: 1900 mg/m ³	
ORGANO-COPPER COMPOUND	TWA: 1 mg/m³ Cu dust and	-	IDLH: 100 mg/m³ Cu dust and
22221-10-9	mist		mist
			TWA: 1 mg/m ³ Cu dust and
			mist

Chemical name	Alberta	British Columbia	Ontario	Quebec
HEPTANE	TWA: 400 ppm	TWA: 400 ppm	TWA: 400 ppm	TWA: 400 ppm
142-82-5	TWA: 1640 mg/m ³	STEL: 500 ppm	STEL: 500 ppm	STEL: 500 ppm
	STEL: 500 ppm			
	STEL: 2050 mg/m ³			
PROPANE	TWA: 1000 ppm	Simple asphyxiant	TWA:	Simple asphyxiant
74-98-6			Simple asphyxiant (See	
			Appendix F: Minimal	
			Oxygen	
			Content; explosion	
			hazard)	
ISOBUTANE	-	STEL: 1000 ppm	TWA:	TWA: 1000 ppm
75-28-5			STEL: 1000 ppm	
ETHANOL	TWA: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm
64-17-5	TWA: 1880 mg/m ³			

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
HEPTANE	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm STEL: 500 ppm
PROPANE	TWA: Simple asphyxiant (See Appendix F: Minimal Oxygen Content)	TWA:	TWA:	TWA: Simple asphyxiant
ISOBUTANE	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm
ETHANOL	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
HEPTANE	TWA: 400 ppm	TWA: 400 ppm	TWA: 400 ppm	TWA: 400 ppm
	STEL: 500 ppm	STEL: 500 ppm	STEL: 500 ppm	TWA: 1600 mg/m ³
				STEL: 500 ppm
				STEL: 2000 mg/m ³
PROPANE	TWA: 1000 ppm	TWA:	TWA: 1000 ppm	Simple asphyxiant
	STEL: 1250 ppm		STEL: 1250 ppm	
ISOBUTANE	TWA: 1000 ppm	STEL: 1000 ppm	TWA: 1000 ppm	
	STEL: 1250 ppm		STEL: 1250 ppm	
ETHANOL	TWA: 1000 ppm	STEL: 1000 ppm	TWA: 1000 ppm	TWA: 1000 ppm
	STEL: 1250 ppm		STEL: 1250 ppm	TWA: 1900 mg/m ³
				STEL: 1000 ppm
				STEL: 1900 mg/m ³

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Impervious gloves. Wear suitable gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

Antistatic boots.

Respiratory protection Appropriate respiratory protection should be selected and used according to the chemical

nature, hazards and use of this product and safety requirements of the local jurisdiction. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be

required.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not

be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

Wear suitable gloves and eye/face protection.

Thermal hazards No information available.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state Aerosol

Appearance No information available

Color Green

Odor No information available Odor threshold No information available

PropertyValuesRemarks • MethodpHNo data available10% in deionized water

Melting point / freezing point

No data available

No data available

No data available

No data available

Flash point < 0 °C / 32 °F

Evaporation rate <1

Flammability (solid, gas) No data available

Flammability Limit in Air

Upper flammability limit: 9.5%
Lower flammability limit: 1.0%
Vapor pressure 71 psig
Vapor density >1

Relative density 0.66

Water solubility No data available Negligible

Solubility(ies)

Partition coefficient
Autoignition temperature

Decomposition temperature

No Data Available
No data available
No data available

temperature (SADT): 50 °C SADT-Self Accelerating

Decomposition Temperature. Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction.

Remarks: Self-Accelerating decomposition

Gives a flame projection at full valve opening or flashback at any degree of valve opening

Flammable in the presence of the following materials or conditions: open flames, sparks and static

Kinematic viscosity

No Data Available

No data available

No data available

Remarks: Self-Accelerating decomposition

temperature (SADT): 50 °C SADT-Self Accelerating Decomposition Temperature. Lowest temperature at

Estimated

Ether = 1

discharge. None known

Air = 1

None known

None known

Estimated

which the tested package size will undergo a self-accelerating decomposition reaction.

Other information

Explosive properties
Oxidizing properties
No information available

VOC content 9

Density
No information available
No information available

10. Stability and reactivity

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions
None under normal processing.

Hazardous polymerizationNo information available.

Conditions to avoid Heat, flames and sparks. Excessive heat.

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition products Carbon oxides. Phosphorus. Copper compounds.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal. Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be

fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact Specific test data for the substance or mixture is not available. May cause irritation.

Skin contact Repeated exposure may cause skin dryness or cracking. Specific test data for the

substance or mixture is not available. Causes skin irritation. (based on components).

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if

swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness

and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 10,590.00 mg/kg

 ATEmix (dermal)
 3,046.20 mg/kg

 ATEmix (inhalation-gas)
 207,142.90 ppm

 ATEmix (inhalation-vapor)
 99,999.00 mg/l

 ATEmix (inhalation-dust/mist)
 30.40 mg/l

97 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

34 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

71 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

99 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

32 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Component information						
Chemical name	Oral LD50	Dermal LD50	Inhalation LC50			
HEPTANE	PTANE -		> 29.29 mg/L (Rat) 4 h			
142-82-5			-			
PROPANE	-	-	> 800000 ppm (Rat) 15 min			
74-98-6						
ISOBUTANE -		-	> 800000 ppm (Rat) 15 min			
75-28-5						
ETHANOL	= 7060 mg/kg (Rat)	-	= 116.9 mg/L (Rat) 4 h			
64-17-5			= 133.8 mg/L (Rat) 4 h			
ORGANO-COPPER COMPOUND	-	> 2000 mg/kg (Rat)	-			
22221-10-9						

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity Contains a known or suspected mutagen. Classification based on data available for

ingredients. May cause genetic defects.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGÍH	IARC	NTP	OSHA
	7.00111	IARC	1411	USHA
ETHANOL	A3	Group 1	Known	X
64-17-5		·		

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans NTP (National Toxicology Program)

Known - Known Carcinogen

Occupational Safety and Health Administration of the US Department of Labor

X - Present

Reproductive toxicity Contains a known or suspected reproductive toxin. Classification based on data available

for ingredients. May damage fertility or the unborn child.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure No information available.

Aspiration hazard May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
HEPTANE	-	LC50: =375.0mg/L (96h,	-	-
142-82-5		Cichlid fish)		
ETHANOL	-	LC50: 12.0 - 16.0mL/L	-	LC50: 9268 -
64-17-5		(96h, Oncorhynchus		14221mg/L (48h,
		mykiss)		Daphnia magna)
		LC50: >100mg/L (96h,		EC50: =2mg/L (48h,
		Pimephales promelas)		Daphnia magna)
		LC50: 13400 -		
		15100mg/L (96h,		
		Pimephales promelas)		

Persistence and degradability No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient

Revision Date 14-Feb-2025

HEPTANE 142-82-5	4.66
PROPANE 74-98-6	1.09
ISOBUTANE 75-28-5	2.8
ETHANOL 64-17-5	-0.35

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

US EPA Waste Number

Waste designations and classifications should be determined by the end user based on the

application for which the product was used.

14. Transport information

DOT

UN number or ID number 1950

Proper shipping name Aerosols, Limited Quantity (LQ)

Transport hazard class(es) 2.1 Emergency Response Guide 126

Number

TDG

UN number or ID number 1950

UN proper shipping name Aerosols, Limited Quantity (LQ)

Transport hazard class(es) 2.1

MEX

UN number or ID number 1950

UN proper shipping name Aerosols, Limited Quantity (LQ)

Transport hazard class(es) 2.1

<u>IATA</u>

UN number or ID number ID 8000

UN proper shipping name Consumer Commodity

Transport hazard class(es) 9

IMDG

UN number or ID number 1950

UN proper shipping name Aerosols, Limited Quantity (LQ)

Transport hazard class(es) 2.1

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA Complies DSL/NDSL Complies **EINECS/ELINCS** Complies Complies **ENCS** Complies **IECSC** Complies KECI Complies **PICCS AICS** Complies **NZIoC** Complies

Leaend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing Chemicals Inventory

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable	CWA - Toxic Pollutants	CWA - Priority	CWA - Hazardous
	Quantities		Pollutants	Substances
ORGANO-COPPER COMPOUND 22221-10-9	-	X	-	-

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
ETHANOL - 64-17-5	*Developmental (in alcoholic beverages)

Revision Date 14-Feb-2025

*Ethanol is only considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage

U.S. State Right-to-Know Regulations

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPAHealth hazards2Flammability4Instability0Special hazards-HMISHealth hazards3 *Flammability4Physical hazards3Personal protectionX

Chronic Hazard Star Legend *= Chronic Health Hazard

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity ATE: Acute Toxicity Estimate

LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

+ Sensitizers

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR) U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA) Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

U.S. National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications

Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

World Health Organization

Revision Date 14-Feb-2025

Revision Note No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.