

PRODUCTS TECHNIQUES, INC.
Safety Data Sheet

SECTION 1 - PRODUCT & COMPANY INFORMATION

Product Name TT-P-1757A/B TY III GREEN PRIMER Product Code PT-522GREEN
Trade Name NSN 8010-00-145-0312/8010-00-582-5318 CAGE CODE 06341

MANUFACTURER
Products/Techniques, Inc
3271 S. Riverside Ave.
Bloomington, CA 92316

PH 909 877 3951
FX 909 877 6078
E-mail pti@plupaint.com
Web: www.plupaint.com

OPERATING HOURS 8:00 am - 4:30 pm PDT

In an emergency, call
CHEMTREC: 1 800 424 9300

SECTION 2 - HAZARDS IDENTIFICATION

HMS: 230X

GHS Ratings:

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Respiratory sensitizer	1	Respiratory sensitizer
Skin sensitizer	1	Skin sensitizer
Carcinogen	1A	Known Human Carcinogen Based on human evidence

GHS Hazards

H225	Highly flammable liquid and vapour
H303	May be harmful if swallowed
H313	May be harmful in contact with skin
H317	May cause an allergic skin reaction
H331	Toxic if inhaled
H333	May be harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H350	May cause cancer

GHS Precautions

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces - No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/lighting equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P271	Use only outdoors or in a well-ventilated area
P272	Contaminated work clothing should not be allowed out of the workplace

SDS for: PT-522GREEN

Page 1 of 10

Printed: 8/12/2016 at 11:16:07AM

(1) NON-HAZARDOUS MATERIAL

SECTION 4 - FIRST AID MEASURES

INHALATION: If breathing problems occur during use, LEAVE AREA IMMEDIATELY and get fresh air. If breathing problems remain, SEEK IMMEDIATE MEDICAL ATTENTION.
EYE CONTACT: Flush eyes with large amounts of clean water for at least 20 minutes. Seek immediate medical attention.
SKIN CONTACT: Wash affected area thoroughly with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and launder before re-use.
INGESTION: Do not induce vomiting. Get immediate medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: -20°C (-4°F)

LEL: 1.00

UEL: 13.00

All flashpoints: TCC

EXTINGUISHING MEDIA: Alcohol foam, carbon dioxide (CO₂), dry chemical, water spray/water fog extinguishing systems

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors can travel to a source of ignition and flash back. Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flashpoint. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum re-conditioner, or properly disposed of.

SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways.

SECTION 7 - HANDLING & STORAGE

HANDLING: Wear all appropriate Personal Protective Equipment (PPE). Wear appropriate respiratory protection and ensure adequate ventilation at all times as vapors can accumulate over time in enclosed spaces and poorly ventilated areas. Use product in a way that minimizes splashes and/or creation of dust. Wash with soap and water thoroughly after each use.

STORAGE: Keep away from heat, sparks and flame. Keep container closed when not in use. Store in a cool dry area at a temperature between 50 and 95 degrees F. Do not store outside in direct sunlight.

SDS for: PT-522GREEN

Page 3 of 10

Printed: 8/12/2016 at 11:16:07AM

P280
P281
P285
P311
P321
P363
P302+P352
P303+P361+P353

P304+P340

P304+P341

P308+P313
P333+P313
P342+P311
P370+P378
P405
P403+P233
P403+P235
P501

Wear protective gloves/protective clothing/eye protection/face protection
Use personal protective equipment as required
In case of inadequate ventilation wear respiratory protection
Call a POISON CENTER or doctor/physician
Specific treatment (see on this label)
Wash contaminated clothing before reuse
IF ON SKIN: Wash with soap and water
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
If exposed or concerned: Get medical advice/attention
If skin irritation or a rash occurs: Get medical advice/attention
Call a POISON CENTER or doctor/physician
In case of fire: Use for extinction
Store locked up
Store in a well ventilated place. Keep container tightly closed.
Store in a well ventilated place. Keep cool.
Dispose of contents/container to

Signal Word: **Danger**



SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
POTASSIUM HYDROXYOCTAOXODIZINCATEDICHROMATE	11103-86-9	30.07%
ALKYD RESIN - NOT HAZARDOUS	ALKYD RESIN-CAS: PROPRIETARY	18.44%
ACETONE	67-64-1	17.21%
MINERAL SPIRITS	8052-41-3	7.53%
XYLENE	1330-20-7	5.82%
N-BUTYL ACETATE NORMAL	123-86-4	4.67%
BARTEX ADDITIVE	7727-43-7	4.49%
NON-HAZARDOUS INGREDIENTS	NH1	4.08%
METHYL ETHYL KETONE	78-93-3	3.58%
SYNTHETIC AMORPHOUS SILICA	112926-00-8	2.08%
ETHYLBENZENE	100-41-4	0.49%
SILANE	1760-24-3	0.42%
1-METHOXY-2-PROPANOL ACETATE	108-65-6	0.36%
ADDITIVE	96-29-7	0.16%
(P-TERT)BUTYLPHENOL	98-54-4	0.16%
ZIRCONIUM ADDITIVE	22464-99-9	0.13%
WATER	7732-18-5	0.11%
COBALT ADDITIVE	61789-51-3	0.09%
FORMALDEHYDE	50-00-0	0.00%

SDS for: PT-522GREEN

Page 2 of 10

Printed: 8/12/2016 at 11:16:07AM

SECTION 8 - EXPOSURE CONTROL AND PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
POTASSIUM HYDROXYOCTAOXODIZINCATEDICHROMATE 11103-86-9	5 ug/m3 8 hr TWA 1 mg/10m3 CEIL 0.1 mg/m3 CEIL (as CrO3)	0.01 mg/m3 TWA (as Cr, listed under Zinc chromates)	NIOSH: 0.001 mg/m3 10 hr TWA (as Cr)
ALKYD RESIN - NOT HAZARDOUS ALKYD RESIN-CAS: PROPRIETARY	Not Established	Not Established	Not Established
ACETONE 67-64-1	1000 ppm TWA; 2400 mg/m3 TWA	750 ppm STEL 590 mg/m3 TWA	NIOSH: 250 ppm TWA; 590 mg/m3 TWA
MINERAL SPIRITS 8052-41-3	500 ppm TWA; 2900 mg/m3 TWA	100 ppm TWA	NIOSH: 350 mg/m3 TWA 1800 mg/m3 Ceiling (15 min)
XYLENE 1330-20-7	100 ppm TWA; 435 mg/m3 TWA	150 ppm STEL 100 ppm TWA	Not Established
N-BUTYL ACETATE NORMAL 123-86-4	150 ppm TWA; 710 mg/m3 TWA	200 ppm STEL 150 ppm TWA	NIOSH: 150 ppm TWA; 710 mg/m3 TWA 200 ppm STEL; 950 mg/m3 STEL
BARTEX ADDITIVE 7727-43-7	15 mg/m3 TWA (total dust), 5 mg/m3 TWA (respirable fraction)	10 mg/m3 TWA	NIOSH: 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
NON-HAZARDOUS INGREDIENTS NH1	Not Established	Not Established	Not Established
METHYL ETHYL KETONE 78-93-3	200 ppm TWA; 590 mg/m3 TWA	300 ppm STEL 200 ppm TWA	NIOSH: 200 ppm TWA; 590 mg/m3 TWA 300 ppm STEL; 885 mg/m3 STEL
SYNTHETIC AMORPHOUS SILICA 112926-00-8	Not Established	Not Established	Not Established
ETHYLBENZENE 100-41-4	100 ppm TWA; 435 mg/m3 TWA	125 ppm STEL 100 ppm TWA	NIOSH: 100 ppm TWA; 435 mg/m3 TWA 125 ppm STEL; 545 mg/m3 STEL
SILANE 1760-24-3	Not Established	Not Established	Not Established
1-METHOXY-2-PROPANOL ACETATE 108-65-6	TWA 50 PPM	Not Established	Not Established
ADDITIVE 96-29-7	Not Established	Not Established	Not Established
(P-TERT)BUTYLPHENOL 98-54-4	Not Established	Not Established	Not Established
ZIRCONIUM ADDITIVE 22464-99-9	Not Established	Not Established	Not Established

SDS for: PT-522GREEN

Page 4 of 10

Printed: 8/12/2016 at 11:16:07AM

WATER 7732-18-5	No TLV established	No PEL established	Not Established
COBALT ADDITIVE 61789-51-3	Not Established	Not Established	Not Established
FORMALDEHYDE 50-00-0	0 75 ppm TWA	0 3 ppm Ceiling	NIOSH: 0 016 ppm TWA 0 1 ppm Ceiling (15 min)

ENGINEERING CONTROLS Good general ventilation should be sufficient to control airborne levels. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

VENTILATION & RESPIRATORY PROTECTION Always follow all local, state, and federal laws and regulations regarding the use of respirators. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release. Exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. Wear a MSHA/NIOSH approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.

ADMINISTRATIVE CONTROLS: All individual company safety policies should be reviewed to determine compliance with applicable Federal, State and local safety regulations. If a company determines that threshold limit values and air quality contaminant level have not been exceeded, then that company should set its own policies regarding the use of respirators and other Personal Protective Equipment.

SKIN PROTECTION: Where contact is likely, wear chemical resistant gloves, such as neoprene or solvent resistant nitrile. To prevent repeated or prolonged skin contact, wear impervious clothing such as a chemical suit, rubber boots, and/or chemical safety goggles plus a face shield if such should be necessary. If the equipment to be worn is not available or the type of equipment for a specific job is not known, consult a reputable safety equipment supply company. Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).

EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.

OTHER PROTECTIVE EQUIPMENT: Where splashing is possible, full chemically resistant protective clothing (e.g. acid suit) and boots are required.

HYGIENIC PRACTICES: Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all MSDS/label precautions even after container is emptied because they may retain product residues. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid prolonged or repeated contact with skin. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES

Appearance: Pigmented liquid	Odor: Solvent like
Physical State: Liquid	Vapor Density: 2.64
Vapor Pressure: 105.5 mmHg	Boiling Range: 56 to 148 °C, 133 to 298 °F

SDS for: PT-522GREEN	Page 5 of 10
Blood, Eyes, Kidneys, Liver, Lungs, Central Nervous System, Reproductive System	Printed: 8/12/2016 at 11:16:07AM
Skin, Heart, Respiratory System	

Effects of Overexposure			
CARCINOGENICITY:			
CAS Number 11103-86-9	Description POTASSIUM HYDROXYOCTAOXODIZINCATED ICHROMATE	% Weight 30.07	Carcinogen Rating POTASSIUM HYDROXYOCTAOXODIZINCATED CHROMATE: IARC: Human carcinogen IARC: Human carcinogen OSHA: listed ECHA CANDIDATE LIST: Human carcinogen
50-00-0	FORMALDEHYDE	0.000	FORMALDEHYDE: NIOSH: potential occupational carcinogen IARC: Human carcinogen OSHA: listed
61789-51-3	COBALT ADDITIVE	0.086	COBALT ADDITIVE: IARC: Possible human carcinogen OSHA: listed

ACUTE TOXICITY

INHALATION Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

CONDITIONS AGGRAVATED: Unknown

CHRONIC EFFECTS: Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage.

SECTION 12 - ECOLOGICAL INFORMATION

No information available	
Component Ecotoxicity ACETONE	96 Hr LC50 Pimephales promelas: 6210-8120 mg/L [static] 48 Hr EC50 water flea: 0.0039 mg/L; 48 Hr EC50 water flea: 12700 mg/L [Static]; 48 Hr EC50 Daphnia magna: 12600 mg/L
XYLENE	96 Hr LC50 Pimephales promelas: 13.4 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 8.05 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 16.1 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: 26.7 mg/L [static] 48 Hr EC50 water flea: 3.82 mg/L; 48 Hr LC50 Gammarus lacustris: 0.6 mg/L
N-BUTYL ACETATE NORMAL	96 Hr LC50 Leuciscus idus: 62 mg/L [static] 48 Hr EC50 water flea: 44 mg/L 96 Hr EC50 Scenedesmus subspicatus: 320 mg/L; 72 Hr EC50 Scenedesmus subspicatus: 674.7 mg/L
METHYL ETHYL KETONE	96 Hr LC50 Pimephales promelas: 3220 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 1690 mg/L 48 Hr EC50 water flea: 520 mg/L; 48 Hr EC50 Daphnia magna: 5091 mg/L

Wt% Solids 61.19	Weight/Gallon 10.89
VOC(g/l) Less H2O and 385.68	VOC(lbs/gal) Less H2O and 3.21
Exempt Compounds	Exempt Compounds
VOC (g/L) Material 281.03	Specific Gravity 1.31
% VOC (C.A.R.B.) 21.53	

SECTION 10 - REACTIVITY & STABILITY

STABILITY

STABLE

INCOMPATIBILITY (Materials to avoid): strong acids and bases, oxidizers, and selected amines

CONDITIONS TO AVOID: Avoid all possible sources of ignition

No Data

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide (CO) and carbon dioxide (CO2)

Other unknown hazardous products are possible.

No Data

Hazardous polymerization will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Mixture Toxicity Inhalation Toxicity LC50: 800mg/L	
Component Toxicity	
123-86-4	N-BUTYL ACETATE NORMAL Inhalation LC50: 390 ppm (Rat)
100-41-4	ETHYLBENZENE Oral LD50: 3,500 mg/kg (Rat); Inhalation LC50: 17 mg/L (Rat)
108-65-6	1-METHOXY-2-PROPANOL ACETATE Dermal LD50: 5,000 mg/kg (Rabbit); Inhalation LC50: 100 ppm (Rat)
96-29-7	ADDITIVE Oral LD50: 930 mg/kg (Rat); Inhalation LC50: 20 mg/L (Rat)
98-54-4	(P-TERT)BUTYLPHENOL Oral LD50: 2,990 mg/kg (Rat); Dermal LD50: 2,318 mg/kg (Rabbit)
7732-18-5	WATER Oral LD50: 90 mL/kg (Rat)
50-00-0	FORMALDEHYDE Oral LD50: 500 mg/kg (Rat); Inhalation LC50: 1 mg/L (Rat)

INHALATION: Headaches, dizziness, nausea, decreased blood pressure, change in heart rate, and cyanosis may result from overexposure to vapor. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

INGESTION: This material may be harmful or fatal if swallowed.

SKIN CONTACT: May cause sensitization or allergic reaction.

EYE CONTACT: Direct contact with liquid, exposure to vapors or mist may cause stinging, tearing, redness, swelling and eye damage.

Routes of Entry:

Inhalation	Skin Contact	Eye Contact	Ingestion
------------	--------------	-------------	-----------

Exposure to this material may affect the following organs:

SDS for: PT-522GREEN	Page 6 of 10
	Printed: 8/12/2016 at 11:16:07AM

ETHYLBENZENE	96 Hr LC50 Oncorhynchus mykiss: 14.0 mg/L [static]; 96 Hr LC50 Pimephales promelas: 9.09 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 150.0 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 4.2 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 32 mg/L [static]; 96 Hr LC50 Pimephales promelas: 48.5 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 9.6 mg/L [static] 48 Hr EC50 Daphnia magna: 1.8-2.4 mg/L 72 Hr EC50 Selenastrum capricornutum: 4.6 mg/L; 96 Hr EC50 Selenastrum capricornutum: >438 mg/L
1-METHOXY-2-PROPANOL ACETATE	96 Hr LC50 Pimephales promelas: 161 mg/L [static] 48 Hr EC50 Daphnia magna: >500 mg/L
ADDITIVE	96 Hr LC50 Leuciscus idus: 320-1000 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 760 mg/L [static] 48 Hr EC50 Daphnia magna: 750 mg/L 72 Hr EC50 Scenedesmus subspicatus: 83 mg/L
(P-TERT)BUTYLPHENOL	96 Hr LC50 Pimephales promelas: 5.1 mg/L [flow-through] 48 Hr EC50 Daphnia magna: 3.9 mg/L 72 Hr EC50 Scenedesmus subspicatus: 11.2 mg/L
FORMALDEHYDE	96 Hr LC50 Brachydanio rerio: 41 mg/L [static] 96 Hr EC50 water flea: 20 mg/L; 48 Hr EC50 Daphnia magna: 2 mg/L

SECTION 13 - DISPOSAL CONSIDERATIONS

It is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition. Maximize material recovery for reuse or recycling.

It is the responsibility of the user to determine if the material is a RCRA "hazardous waste" at the time of disposal. Transportation, treatment, storage, and disposal of waste material must be conducted in accordance with RCRA regulations (see 40 CFR 260 through 40 CFR 271). State and/or local regulations may be more restrictive. Contact your regional US EPA office for guidance concerning case specific disposal issues.

Non-usable product is regulated by US EPA as hazardous material under the following codes:

SECTION 14 - TRANSPORTATION / SHIPPING INFORMATION

Hazardous Material? Ship according to all applicable local, state, and federal regulations regarding labeling and packaging requirements.

Agency	Proper Shipping Name	UN Number	Packing Group	Hazard Class
DOT	PAINT	UN1263	II	3
IATA	PAINT	UN1263	II	3
IMO	PAINT	UN1263	II	3

SECTION 15 - REGULATORY INFORMATION

Additional regulatory listings, where applicable:

The following chemicals are listed under California Proposition 65:

11103-86-9 POTASSIUM HYDROXYOCTAOXODIZINCATEDICHROMATE 30.07 % Carcinogen

The following chemicals appear on the New Jersey Right-To-Know Chemicals list:

8052-41-3	MINERAL SPIRITS
1330-20-7	XYLENE
123-86-4	N-BUTYL ACETATE NORMAL

The following chemicals appear on the Pennsylvania Right-To-Know list:

8052-41-3 MINERAL SPIRITS 7.53 %
123-86-4 N-BUTYL ACETATE NORMAL 4.67 %
78-93-3 METHYL ETHYL KETONE 3.58 %

SARA HAZARD CATEGORY: The product has been reviewed according to the EPA 'Hazard Categories' promulgated under sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered under applicable definitions to meet the following categories:

11103-86-9 POTASSIUM HYDROXYOCTAOXODIZINCATEDICHROMATE Acute Health Hazard, Chronic Health Hazard
67-64-1 ACETONE Fire Hazard, Acute Health Hazard
8052-41-3 MINERAL SPIRITS Fire Hazard
1330-20-7 XYLENE Fire Hazard, Acute Health Hazard, Chronic Health Hazard
123-86-4 N-BUTYL ACETATE NORMAL Fire Hazard, Acute Health Hazard
78-93-3 METHYL ETHYL KETONE Fire Hazard, Acute Health Hazard, Chronic Health Hazard

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

- None

Country

Regulation

All Components Listed



EU Risk Phrases

R10: Flammable
R20: Harmful by inhalation
R25: Toxic if swallowed
R36: Irritating to eyes
R45: May cause cancer
R48: Danger of serious damage to health by prolonged exposure
R49: May cause cancer by inhalation

Safety Phrases

S16: Keep away from sources of ignition - No smoking
S22: Do not breathe dust
S38: In case of insufficient ventilation wear suitable respiratory equipment
S60: This material and its container must be disposed of as hazardous waste
S1/2: Keep locked up and out of the reach of children
S3/7: Keep container tightly closed in a cool place
S20/21: When using do not eat, drink or smoke
S24/25: Avoid contact with skin and eyes
S29/56: Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point
S36/37/39: Wear suitable protective clothing, gloves and eye/face protection

The chemical substances listed below are not on the TSCA Section 8 Inventory:

- None

SARA Section 313: The product contains the following substances subject to the reporting requirements of section 313 and Title II of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

SECTION 16 - OTHER INFORMATION

The information in this document is believed to be correct as of the date printed.

NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION. THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT OF THE HAZARDS RELATED TO ITS USE.

This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of his use thereof.

(C) Copyright, 2015 Products Techniques, Inc.

Hazardous Material Information System (HMIS)

HEALTH	2	HMIS & NFPA Hazard Rating Legend
FLAMMABILITY	3	* = Chronic Health Hazard
PHYSICAL HAZARD	0	0 = INSIGNIFICANT
PERSONAL PROTECTION	X	1 = SLIGHT
		2 = MODERATE
		3 = HIGH

National Fire Protection Association (NFPA)



Date Prepared: 8/12/2016

Reviewer Revision