Product Name: Finish Sand 4:1 Product identifier: 100738 Revision Date: 12-14-2015 Replaces:



1. Identification

Product Name: Product identifier: Relevant identified uses of the substance or mixture and uses advised against:	Finish Sand 4:1 100738 Primer
Other means of identification Chemical Manufacturer / Importer / Distributor:	ITW Evercoat a division of Illinois Tool Works Inc. 6600 Cornell Road Cincinnati, OH 45242
Emergency telephone number:	513-489-7600 CHEMTREC: 1-800-424-9300 CANUTEC: 1-613-996-6666

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;



GHS Classification:	Reproductive Toxicity Category 1B Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 1 Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 1 Flammable Liquid Category 2 Skin Corrosion/Irritation Category 2 Serious Eye Damage/Eye Irritation Category 2A Germ Cell Mutagenicity Category 2 Carcinogenicity Category 2 Hazardous to the aquatic environment - Acute Category 3 Acute Toxicity - Inhalation Dust / Mist Category 4
GHS Signal Word:	Danger
GHS Hazard Statements:	Highly flammable liquid and vapour. Causes skin irritation.
	Causes serious eye irritation. Harmful if inhaled.

Product Name: Finish Sand 4:1 Product identifier: 100738 Revision Date: 12-14-2015

Replaces:

Replaces:	
	Suspected of causing genetic defects.
	Suspected of causing cancer.
	May damage fertility or the unborn child.
	Causes damage to organs.
	Causes damage to organs through prolonged or repeated exposure.
	Harmful to aquatic life.
GHS Precautionary Statements:	
Safety Precautions:	Obtain special instructions before use.
	Do not handle until all safety precautions have been read and understood.
	Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
	Keep container tightly closed.
	Ground/bond container and receiving equipment.
	Use explosion-proof electrical/ventilating/lighting equipment.
	Use only non-sparking tools.
	Take precautionary measures against static discharge.
	Do not breathe dust/fume/gas/mist/vapours/spray.
	Avoid breathing dust/fume/gas/mist/vapours/spray.
	Wash thoroughly after handling.
	Do not eat, drink or smoke when using this product.
	Use only outdoors or in a well-ventilated area.
	Avoid release to the environment.
	Wear protective gloves/protective clothing/eye protection/face protection.
	Use personal protective equipment as required.
First Aid Measures:	IF ON SKIN: Wash with plenty of soap and water.
	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.
	Rinse skin with water/shower.
	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable
	for breathing.
	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,
	if present and easy to do. Continue rinsing.
	IF exposed: Call a POISON CENTER or doctor/physician.
	IF exposed or concerned: Get medical advice/attention.
	Call a POISON CENTER or doctor/physician if you feel unwell.
	Get medical advice/attention if you feel unwell.
	Specific treatment (see on this label).
	If skin irritation occurs: Get medical advice/attention.
	If eye irritation persists: Get medical advice/attention.
	Take off contaminated clothing and wash before reuse.
	In case of fire: Use for extinction.
Storage:	Keep container tightly closed.
	Store in a well-ventilated place. Keep cool.
	Store locked up.
Disposal:	Dispose of contents/container in accordance with
	local/regional/national/international regulation for hazardous wastes.

Product Name: Finish Sand 4:1 Product identifier: 100738 Revision Date: 12-14-2015 Replaces:

Hazards not otherwise
classified:Reports have associated repeated and prolonged occupational overexposure to
solvents with permanent brain and nervous system damage.

3. Composition/information on ingredients

Chemical Component:	CAS number and other unique identifiers	% (or range) of ingredient
Styrene	100-42-5	10 - 30
Acetone	67-64-1	10 - 30
Titanium dioxide	13463-67-7	5 - 10
Toluene	108-88-3	0.1 - 1

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Eye Contact:	Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention. Flush eyes gently with water for at least 15 minutes, lifting upper & lower eye lids. Seek immediate medical attention.
Skin Contact:	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists. Remove contaminated clothing and continue flushing with water. Wash affected area thoroughly with soap and water. Seek medical advice if symptoms persist Wash clothing before reuse.
Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately If symptoms develop, immediately move individual away from exposure and into fresh air. Get medical attention immediately. Keep the victim warm and quiet. If the victim has stopped breathing open airway, loosen collar and belt, and administer artificial respiration. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice.
Ingestion:	Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this MSDS. Call a physician or poison control center immediately. Do not induce vomiting unless directed to do so by medical personnel. If individual is drowsy or unconscious, do not give anything by mouth; place individual on left side with head down. If possible, do not leave individual unattended. If vomiting Page 3 of 10
	Page 3 OF IU

mmediate medical attention and special treatment needed,:	occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. No additional first aid information available
. Fire-fighting measures	
Suitable extinguishing media:	Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and keep exposed material from being damaged by fire. Regular foam Carbon dioxide Dry chemical
Jnsuitable extinguishing media: Fire and/or Explosion Hazards:	No data available Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a Class B fire. Vapors are heavier than air and may travel to a source of ignition and flash back
Hazardous Combustion Products:	Carbon dioxide, Carbon monoxide, Styrene oxide, oxides of
Special protective equipment and precautions for fire- ighters:	nitrogen, Hydrocarbons Do not enter fire area without proper protection including self- contained toxic breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for cooling. Water may be used to cool closed containers to prevent pressure build-up and possible auto ignition or explosion when exposed to extreme heat. Wear a self contained breathing apparatus (NIOSH approved) with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment.

Product Name: Finish Sand 4:1 Product identifier: 100738 Revision Date: 12-14-2015

Replaces:

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.
Methods and material for containment and cleaning up:	Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Activate available exhaust ventilation equipment in the immediate spill area. All personnel in the area should be protected as in Section 8. Avoid breathing vapors. Use an inert absorbent such as sand or vermiculite. Place in properly labeled closed container.

7. Handling and storage

Precautions for safe handling:	Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. All hazard precautions given in the data sheet must be observed. Do not get in eyes, on skin and clothing Wash hands before eating Use with adequate ventilation Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Do not take internally. Keep container closed when not in use. Keep out of the reach of children.
Conditions for safe storage:	Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Store in a cool dry place For maximum product quality, avoid prolonged storage at temperatures above 75 °F (25 °C). Keep away from heat, sparks, and flame Store in a tightly closed container Avoid contact with incompatible materials.
Materials to Avoid/Chemical Incompatibility::	Peroxides Strong acids Strong oxidizing agents Halogens Reducing agents Strong alkalies

Product Name: Finish Sand 4:1 Product identifier: 100738 Revision Date: 12-14-2015 Replaces:

8. Exposure controls/personal protection

Limits:

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
Styrene	100 ppm	20 ppm	40 ppm STEL; 170 mg/m3 STEL
Acetone	1000 ppm	500 ppm	750 ppm
Titanium dioxide	15 mg/m3	10 mg/m3	No data available
Appropriate engineering controls.:	No exposure limits exist for the constituents of this product. Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort. General or local ventilation or isolation may prove adequate to keep airborne exposures below exposure limits. Explosion proof exhaust ventilation should be used.		
Eye Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses. Splash proof chemical goggles are recommended to protect against the splash of product.		
Skin Protection:	Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. To prevent repeated or prolonged skin contact, wear impervious clothing and boots		
Respiratory Protection:	Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Use a NIOSH approved respirator designed to remove particulate matter and organic solvent vapors. NIOSH approved air purifying respirator with organic vapor cartridge and HEPA filter. Air purifying respirators should not be used in oxygen deficient or IDLH atmospheres		
Other Protective Equipment:	Splash proof chemical goggle the splash of product. Protec be worn to prevent skin con	es are recommended to protec ctive gloves and proper clothin tact. Gloves should be made o To prevent repeated or prolor othing and boots	ıg should f
General Hygiene Conditions:	All hazard precautions given Do not get in eyes, on skin a	in the data sheet must be obs nd clothing Wash hands before on Avoid contact with material	eeating

Product Name: Finish Sand 4:1 Product identifier: 100738 Revision Date: 12-14-2015 Replaces:

breathing dusts or fumes, use only in a well ventilated area. Do not take internally. Keep container closed when not in use. Keep out of the reach of children.

9. Physical and chemical properties

Appearance (physical state):	Liquid
Color:	Grey
Odor:	Aromatic
Odor threshold:	No data available
pH:	No data available
Melting Point/Freezing Point (°C):	No data available
Initial Boiling Point and Boiling Range (°C):	56
Flash Point (°C):	-17
Evaporation Rate:	No data available
Flammability (solid, gas):	No data available
Upper Flammable/Explosive Limit:	12.8
Lower Flammable/Explosive Limit:	2.5
Vapor Pressure:	5 MMHG@20C/68F 180 MMHG@20C/68F
Vapor Density:	Heavier than air. Vapors that evolve from this product
	will tend to settle and accumulate near the floor.
Relative Density:	1.38
Solubility(ies):	Insoluble
Partition coefficient: n-octanol/water:	1.36
Auto-ignition Temperature (°C):	465 ° C
Decomposition Temperature::	No data available
Viscosity:	No data available
VOC (as packaged-less exempts and water)	2.89 or 346
VHAP Content by weight – as packaged	22

10. Stability and reactivity

Reactivity: Chemical stability: Conditions to avoid:	No data available Stable under normal conditions. Sparks, open flame, other ignition sources, and elevated temperatures. Contamination.
Incompatible materials:	Peroxides Strong acids Strong oxidizing agents Halogens Reducing agents Strong alkalies
Hazardous decomposition products:	Carbon dioxide Carbon monoxide Styrene oxide oxides of nitrogen Hydrocarbons

Product Name: Finish Sand 4:1 Product identifier: 100738

Revision Date: 12-14-2015 Replaces:

11. Toxicological information

Likely routes of exposure (inhalation, ingestion, skin and eye contact):	Ingestion, Skin contact, Eye contact, Absorption
Immediate (Acute) Health Effects	by Route of Exposure:
Inhalation Irritation:	Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Excessive inhalation of vapors may cause nasal and respiratory irritation, acute nervous system depression, fatigue, weakness, nausea, headache and dizziness. Airborne overexposure well above the PEL may result additionally in eye irritation,
	headache, chemical bronchitis, asthma-like findings or pulmonary edema.
Inhalation Toxicity:	Harmful! Can cause systemic damage (see "Target Organs)
Skin Contact:	Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Skin Absorption:	No absorption hazard in normal industrial use. Causes skin irritation. Contact may cause irritation and possible dermatitis or sensitization. Symptoms may include redness, burning, drying and cracking of skin, and skin burns
Eye Contact:	Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue. Contact with liquid or vapor may result in irritation, redness, tearing, and blurred vision.
Ingestion Irritation:	Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea. Causes gastrointestinal tract irritation, nausea, vomiting, diarrhea and possible ulcerations to mucous membranes. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.
Ingestion Toxicity:	Harmful if swallowed. May cause systemic poisoning.
Long-Term (Chronic) Health Effec	<u>ts:</u>
Carcinogenicity:	Suspected of causing cancer. The International Agency for Research on Cancer (IARC) has classified styrene as a group 2B carcinogen (possibly carcinogenic to humans).
Reproductive and	May damage fertility or the unborn child.
Developmental Toxicity:	
Mutagenicity:	Suspected of causing genetic defects.
Inhalation:	Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Harmful! Can cause systemic damage upon prolonged and/or repeated exposure (see "Target Organs)
Skin Contact:	Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Skin Absorption:	Upon prolonged or repeated exposure, no hazard in normal industrial use.

Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
No data available			

Has the chemical been classified as a Carcinogen by NTP, IARC or OSHA.

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
Styrene	Ν	Y	Y
Titanium dioxide	Ν	Y	Ν

12. Ecological information	
Ecotoxicity (aquatic and terrestrial, where available):	Toxic to aquatic life. Styrene is toxic to aquatic organisms and should not be released to sewage, draining systems or any body of water exceeding concentrations of approved limits under applicable regulations and permits.
Persistence and degradability:	No data available
Mobility in soil:	No data available
Other adverse effects (such as hazardous to the ozone layer):	No data available

Données sur l'écotoxicité

F

Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
No data available			

13. Disposal considerations

Description of waste residues: Safe Handling of Waste:	Spent or discarded material is a hazardous waste. Disposal must be in accordance with applicable Federal, State/Provincial and Local regulations.
Waste treatment methods	Dispose of by incineration following Federal, State, Local, or
(including packaging):	Provincial regulations.
Waste Disposal Code(s):	D001

14. Transport information

UN number:	UN1263
UN proper shipping name:	
Transport hazard class(es):	3
Packing group:	П

The shipper is responsible for following all applicable regulations. The transportation classification provided is based on ITW Evercoat original packaging, which is suitable for domestic ground transport only.

15. Regulatory information

Statut TSCA:

The intentional ingredients of this product are listed.

Regulated Components:

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
Styrene	100-42-5	Ν	Ν	Y	N
Acetone	67-64-1	Ν	N	Y	N
Titanium dioxide	13463-67-7	Ν	N	Y	Y

16. Other information, including date of preparation or last revision.

Revision Date:	12-14-2015
Revision Number:	8

Disclaimer: NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances