

PRODUCTS TECHNIQUES, INC.
Safety Data Sheet

SECTION 1 - PRODUCT & COMPANY INFORMATION

Product Name: TT-E-527D FLAT WHITE LOW VOC Product Code: PT-383837875
MANUFACTURER: PH: 909.877.3951
Products/Techniques, Inc. FX: 909.877.6078
3271 S. Riverside Ave. E-mail: pt@ptpaint.com
Bloomington, CA 92316 Web: www.ptpaint.com

OPERATING HOURS: 8:00 am - 4:30 pm PDT

In an emergency, call:
CHEMTREC: 1 800 424 9300

SECTION 2 - HAZARDS IDENTIFICATION

HMIS: 230X

GHS Ratings:

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Respiratory sensitizer	1	Respiratory sensitizer
Skin sensitizer	1	Skin sensitizer

GHS Hazards:

H225	Highly flammable liquid and vapour
H303	May be harmful if swallowed
H313	May be harmful in contact with skin
H317	May cause an allergic skin reaction
H333	May be harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled

GHS Precautions:

P210	Keep away from heat/sparks/open flames/hot surfaces - No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/lighting equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P272	Contaminated work clothing should not be allowed out of the workplace
P280	Wear protective gloves/protective clothing/eye protection/face protection
P285	In case of inadequate ventilation wear respiratory protection
P321	Specific treatment (see ... on this label)
P363	Wash contaminated clothing before reuse
P302+P352	IF ON SKIN: Wash with soap and water
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

SDS for PT-383837875

Page 1 of 9
Printed: 4/25/2017 at 2:47:35PM

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: 8 C (46 F)

LEL:

UEL: 8.00

All flashpoints: TCC
EXTINGUISHING MEDIA: Alcohol foam, carbon dioxide (CO2), dry chemical, water spray/water fog extinguishing systems
UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors can travel to a source of ignition and flash back. Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flashpoint. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum re-conditioner, or properly disposed of.

SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways.

SECTION 7 - HANDLING & STORAGE

HANDLING: Wear all appropriate Personal Protective Equipment (PPE). Wear appropriate respiratory protection and ensure adequate ventilation at all times as vapors can accumulate over time in enclosed spaces and poorly ventilated areas. Use product in a way that minimizes splashes and/or creation of dust. Wash with soap and water thoroughly after each use.
STORAGE: Keep away from heat, sparks and flame. Keep container closed when not in use. Store in a cool dry area at a temperature between 50 and 95 degrees F. Do not store outside in direct sunlight.

SECTION 8 - EXPOSURE CONTROL AND PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
TITANIUM DIOXIDE 13463-67-7	15 mg/m3 TWA (total dust)	10 mg/m3 TWA	Not Established
ALKYD RESIN - NOT HAZARDOUS	Not Established	Not Established	Not Established
ALKYD RESIN - NOT HAZARDOUS	Not Established	Not Established	Not Established
ALKYD RESIN-CAS: PROPRIETARY	Not Established	Not Established	Not Established

SDS for PT-383837875

Page 3 of 9
Printed: 4/25/2017 at 2:47:35PM

P304+P341

P333+P313
P342+P311
P370+P378
P403+P235
P501

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
If skin irritation or a rash occurs: Get medical advice/attention.
Call a POISON CENTER or doctor/physician.
In case of fire: Use ... for extinction.
Store in a well ventilated place. Keep cool.
Dispose of contents/container to ...

Signal Word: Danger



SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
TITANIUM DIOXIDE	13463-67-7	26.53%
ALKYD RESIN - NOT HAZARDOUS	ALKYD RESIN	24.10%
ALKYD RESIN - NOT HAZARDOUS	YD RESIN-CAS: PROPRIETARY	15.88%
N-BUTYL ACETATE NORMAL	123-86-4	15.74%
SYNTHETIC AMORPHOUS SILICA	112926-00-8	8.65%
2-PENTANONE	107-87-9	4.76%
(ETHYL-3-OXOBUTANOATO-0*(1,0*3)(2-DIMETHYLAMINO)ETANOLATO(1-METHOXYPROPAN-OLATO)ALUMINUM(H1)) DIMERISED	149057-70-5	1.17%
METHYL ISOBUTYL KETONE SOLVENT	108-10-1	0.95%
XYLENE	1330-20-7	0.95%
MINERAL SPIRITS	8052-41-3	0.56%
WATER	7732-18-5	0.46%
COBALT ADDITIVE	61789-51-3	0.30%
ADDITIVE	96-29-7	0.35%
NON-HAZARDOUS INGREDIENTS	NH	0.15%
1-METHOXY-2-PROPANOL ACETATE	108-65-6	0.07%
ETHYLBENZENE	100-41-4	0.03%
1-METHOXY-2-PROPANOL	107-98-2	0.03%
PHOSPHORIC ACID	7664-38-2	0.00%

(1) NON-HAZARDOUS MATERIAL

SECTION 4 - FIRST AID MEASURES

INHALATION: If breathing problems occur during use, LEAVE AREA IMMEDIATELY and get fresh air. If breathing problems remain, SEEK IMMEDIATE MEDICAL ATTENTION.
EYE CONTACT: Flush eyes with large amounts of clean water for at least 20 minutes. Seek immediate medical attention.
SKIN CONTACT: Wash affected area thoroughly with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and launder before re-use.
INGESTION: Do not induce vomiting. Get immediate medical attention.

SDS for PT-383837875

Page 2 of 9
Printed: 4/25/2017 at 2:47:35PM

N-BUTYL ACETATE NORMAL 123-86-4	150 ppm TWA; 710 mg/m3 TWA	200 ppm STEL 150 ppm TWA	NIOSH: 150 ppm TWA; 710 mg/m3 TWA 200 ppm STEL; 950 mg/m3 STEL
SYNTHETIC AMORPHOUS SILICA 112926-00-8	Not Established	Not Established	Not Established
2-PENTANONE 107-87-9	200 ppm TWA; 700 mg/m3 TWA	150 ppm STEL	NIOSH: 150 ppm TWA; 530 mg/m3 TWA
(ETHYL-3- OXOBUTANOATO-0*(1,0*3)(2- DIMETHYLAMINO)ETANOL AT(0)(1-METHOXYPROPAN- OLATO)ALUMINUM(H1)) DIMERISED 149057-70-5	Not Established	Not Established	Not Established
METHYL ISOBUTYL KETONE SOLVENT 108-10-1	100 ppm TWA; 410 mg/m3 TWA	75 ppm STEL 50 ppm TWA	NIOSH: 50 ppm TWA; 205 mg/m3 TWA 75 ppm STEL; 300 mg/m3 STEL
XYLENE 1330-20-7	100 ppm TWA; 435 mg/m3 TWA	150 ppm STEL 100 ppm TWA	Not Established
MINERAL SPIRITS 8052-41-3	500 ppm TWA; 2500 mg/m3 TWA	100 ppm TWA	NIOSH: 350 mg/m3 TWA 1800 mg/m3 Ceiling (15 min)
WATER 7732-18-5	No TLV established	No PEL established	Not Established
COBALT ADDITIVE 61789-51-3	Not Established	Not Established	Not Established
ADDITIVE 96-29-7	Not Established	Not Established	Not Established
NON-HAZARDOUS INGREDIENTS NH	Not Established	Not Established	Not Established
1-METHOXY-2-PROPANOL ACETATE 108-65-6	TWA 50 PPM	Not Established	Not Established
ETHYLBENZENE 100-41-4	100 ppm TWA; 435 mg/m3 TWA	125 ppm STEL 100 ppm TWA	NIOSH: 100 ppm TWA; 435 mg/m3 TWA 125 ppm STEL; 545 mg/m3 STEL
1-METHOXY-2-PROPANOL 107-98-2	Not Established	150 ppm STEL 100 ppm TWA	NIOSH: 100 ppm TWA; 360 mg/m3 TWA 150 ppm STEL; 540 mg/m3 STEL
PHOSPHORIC ACID 7664-38-2	1 mg/m3 TWA	3 mg/m3 STEL 1 mg/m3 TWA	NIOSH: 1 mg/m3 TWA 3 mg/m3 STEL

ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels.

SDS for PT-383837875

Page 4 of 9
Printed: 4/25/2017 at 2:47:35PM

Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

VENTILATION & RESPIRATORY PROTECTION: Always follow all local, state, and federal laws and regulations regarding the use of respirators. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. Wear a MSHA/NIOSH approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.

ADMINISTRATIVE CONTROLS: All individual company safety policies should be reviewed to determine compliance with applicable Federal, State and local safety regulations. If a company determines that threshold limit values and air quality contaminant level have not been exceeded, then that company should set its own policies regarding the use of respirators and other Personal Protective Equipment.

SKIN PROTECTION: Where contact is likely, wear chemical resistant gloves, such as neoprene or solvent resistant nitrile. To prevent repeated or prolonged skin contact, wear impervious clothing such as a chemical suit, rubber boots, and/or chemical safety goggles plus a face shield if such should be necessary. If the equipment to be worn is not available or the type of equipment for a specific job is not known, consult a reputable safety equipment supply company. Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).

EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.

OTHER PROTECTIVE EQUIPMENT: Where splashing is possible, full chemically resistant protective clothing (e.g. acid suit) and boots are required.

HYGIENIC PRACTICES: Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all MSDS/label precautions even after container is emptied because they may retain product residues. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid prolonged or repeated contact with skin. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES

This product exhibits the following properties under normal conditions:

Appearance	Odor
Pigmented liquid	Solvent like
Physical State	Liquid
Vapor Pressure	9.0 mmHg
Wt% Solids	76.32
VOC (g/L) Less H ₂ O and Exempt Compounds	308.96
VOC (g/L) Material	308.96
% VOC (C.A.R.B.)	23.68

SECTION 10 - REACTIVITY & STABILITY

STABILITY:

SDS for PF-36363785

Page 5 of 9

Printed: 4/25/2017 at 2:47:39PM

Exposure to this material may affect the following organs:
Effects of Overexposure

CARCINOGENICITY:

CAS Number	Description	% Weight	Carcinogen Rating
61789-51-3	COBALT ADDITIVE	0.389	COBALT ADDITIVE: IARC Possible human carcinogen OSHA listed

ACUTE TOXICITY:

INHALATION: Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

CONDITIONS AGGRAVATED: Unknown.

CHRONIC EFFECTS: Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage.

SECTION 12 - ECOLOGICAL INFORMATION

No information available.

Component	Ecotoxicity
N-BUTYL ACETATE NORMAL	96 Hr LC50 Leuciscus idus: 62 mg/L [static] 48 Hr EC50 water flea: 44 mg/L 96 Hr EC50 Scenedesmus subspicatus: 320 mg/L; 72 Hr EC50 Scenedesmus subspicatus: 674.7 mg/L
2-PENTANONE	96 Hr LC50 Pimephales promelas: 1240 mg/L [flow-through]
METHYL ISOBUTYL KETONE SOLVENT	96 Hr LC50 Pimephales promelas: 505 mg/L [flow-through] 24 Hr EC50 water flea: 4280.0 mg/L; 48 Hr EC50 Daphnia magna: 170 mg/L 96 Hr EC50 Selenastrum capricornutum: 400 mg/L
XYLENE	96 Hr LC50 Pimephales promelas: 13.4 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 8.05 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 16.1 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: 26.7 mg/L [static] 48 Hr EC50 water flea: 3.82 mg/L; 48 Hr LC50 Gammarus lacustris: 0.6 mg/L
ADDITIVE	96 Hr LC50 Leuciscus idus: 320-1000 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 760 mg/L [static] 48 Hr EC50 Daphnia magna: 750 mg/L 72 Hr EC50 Scenedesmus subspicatus: 83 mg/L
1-METHOXY-2-PROPANOL ACETATE	96 Hr LC50 Pimephales promelas: 161 mg/L [static] 48 Hr EC50 Daphnia magna: >500 mg/L
ETHYLBENZENE	96 Hr LC50 Oncorhynchus mykiss: 14.0 mg/L [static]; 96 Hr LC50 Pimephales promelas: 9.09 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 150.0 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 4.2 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 32 mg/L [static]; 96 Hr LC50 Pimephales promelas: 48.5 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 9.6 mg/L [static] 48 Hr EC50 Daphnia magna: 1.8-2.4 mg/L 72 Hr EC50 Selenastrum capricornutum: 4.6 mg/L; 96 Hr EC50 Selenastrum capricornutum: >438 mg/L
1-METHOXY-2-PROPANOL	96 Hr LC50 Pimephales promelas: 20.8 g/L [static]; 96 Hr LC50 Leuciscus idus: 4600-10000 mg/L [static] 96 Hr EC50 water flea: 10457 mg/L

SDS for PF-36363785

Page 7 of 9

Printed: 4/25/2017 at 2:47:39PM

STABLE

INCOMPATIBILITY: (Materials to avoid): strong acids and bases, oxidizers, and selected amines

CONDITIONS TO AVOID: Avoid all possible sources of ignition.

Stability/Reactivity 1 - phrase code not on file

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide (CO) and carbon dioxide (CO₂)
Other unknown hazardous products are possible.

HazDecomp 2 - phrase code not on file

Hazardous polymerization will not occur

SECTION 11 - TOXICOLOGICAL INFORMATION

Mixture Toxicity	Inhalation Toxicity LC50: 26mg/L
Component Toxicity	
13463-67-7	TITANIUM DIOXIDE Inhalation LC50: 7 mg/L (Rat)
123-86-4	N-BUTYL ACETATE NORMAL Inhalation LC50: 300 ppm (Rat)
107-87-9	2-PENTANONE Oral LD50: 1,600 mg/kg (Rat)
149057-70-5	(ETHYL-3-OXOBUTANOATO-0*(1,0*3)(2-DIMETHYLAMINO)ETBANOLATO)(1-METHOXYPROPAN-OLATO)ALUMINUM(H1), DIMERISED Oral LD50: 5,000 mg/kg (Rat) Dermal LD50: 2,000 mg/kg (Rat)
108-10-1	METHYL ISOBUTYL KETONE SOLVENT Oral LD50: 2,080 mg/kg (Rat) Inhalation LC50: 8 mg/L (Rat)
7732-18-5	WATER Oral LD50: 90 mL/kg (Rat)
61789-51-3	COBALT ADDITIVE Oral LD50: 3,900 mg/kg (Rat)
96-29-7	ADDITIVE Oral LD50: 930 mg/kg (Rat) Inhalation LC50: 20 mg/L (Rat)
106-65-6	1-METHOXY-2-PROPANOL ACETATE Dermal LD50: 5,000 mg/kg (Rabbit) Inhalation LC50: 100 ppm (Rat)
100-41-4	ETHYLBENZENE Oral LD50: 3,500 mg/kg (Rat) Inhalation LC50: 17 mg/L (Rat)
107-98-2	1-METHOXY-2-PROPANOL Inhalation LC50: 24 mg/L (Rat)
7664-38-2	PHOSPHORIC ACID Oral LD50: 1,530 mg/kg (Rat) Dermal LD50: 2,730 mg/kg (Rabbit) Inhalation LC50: 850 mg/m3 (R)

INHALATION: Headaches, dizziness, nausea, decreased blood pressure, change in heart rate, and cyanosis may result from overexposure to vapor. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

INGESTION: This material may be harmful or fatal if swallowed.

SKIN CONTACT: May cause sensitization or allergic reaction.

EYE CONTACT: Direct contact with liquid, exposure to vapors or mist may cause stinging, tearing, redness, swelling and eye damage.

Routes of Entry:

Inhalation Skin Contact Eye Contact Ingestion

SDS for PF-36363785

Page 6 of 9

Printed: 4/25/2017 at 2:47:39PM

PHOSPHORIC ACID
96 Hr LC50 Gambusia affinis: 3.3.5 mg/L
12 Hr EC50 Daphnia magna: 4.6 mg/L

SECTION 13 - DISPOSAL CONSIDERATIONS

It is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition. Maximize material recovery for reuse or recycling.

It is the responsibility of the user to determine if the material is a RCRA "hazardous waste" at the time of disposal. Transportation, treatment, storage, and disposal of waste material must be conducted in accordance with RCRA regulations (see 40 CFR 260 through 40 CFR 271). State and/or local regulations may be more restrictive. Contact your regional US EPA office for guidance concerning case specific disposal issues.

Non-usable product is regulated by US EPA as hazardous material under the following codes:

SECTION 14 - TRANSPORTATION / SHIPPING INFORMATION

Hazardous Material! Ship according to all applicable local, state, and federal regulations regarding labeling and packaging requirements.

Agency DOT	Proper Shipping Name	UN Number	Packing Group	Hazard Class
	PAINT	UN1263	II	3

SECTION 15 - REGULATORY INFORMATION

Additional regulatory listings, where applicable.

The following chemicals are listed under California Proposition 65:
61789-51-3 COBALT ADDITIVE: 0.39 % Mutagen

The following chemicals appear on the New Jersey Right-To-Know Chemicals list:

123-86-4 N-BUTYL ACETATE NORMAL

The following chemicals appear on the Pennsylvania Right-To-Know list:

123-86-4 N-BUTYL ACETATE NORMAL 15.74 %

SARA HAZARD CATEGORY: The product has been reviewed according to the EPA Hazard Categories promulgated under sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

123-86-4 N-BUTYL ACETATE NORMAL Fire Hazard, Acute Health Hazard
149057-70-5 (ETHYL-3-OXOBUTANOATO-0*(1,0*3)(2-DIMETHYLAMINO)ETBANOLATO)(1-METHOXYPROPAN-OLATO)ALUMINUM(H1), DIMERISED Fire Hazard, Acute Health Hazard
61789-51-3 COBALT ADDITIVE Fire Hazard, Acute Health Hazard, Chronic Health Hazard

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

- None

Country	Regulation	All Components Listed
---------	------------	-----------------------

SDS for PF-36363785

Page 8 of 9

Printed: 4/25/2017 at 2:47:39PM

EU Risk Phrases

Safety Phrases

The chemical substances listed below are not on the TSCA Section 8 Inventory:
- None

SARA Section 313: The product contains the following substances subject to the reporting requirements of section 313 and Title II of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
61789-51-3 COBALT ADDITIVE 0.39%

SECTION 16 - OTHER INFORMATION

The information in this document is believed to be correct as of the date printed.

NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT OF THE HAZARDS RELATED TO ITS USE.

This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of his use thereof.


(C) Copyright, 2015 Products Techniques, Inc

Hazardous Material Information System (HMIS)

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0
HAZARDOUS REACTION	X

HMIS & NFPA Hazard Rating
Legend
* = Chronic Health Hazard
0 = INSIGNIFICANT
1 = SLIGHT
2 = MODERATE
3 = HIGH

National Fire Protection Association (NFPA)



Date Prepared: 4/25/2017

Reviewer Revision