

SAFETY DATA SHEET



Commercial Product Name: NEXTEL-Verdünner / Thinner 8061
Product No.: 9010300000000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2020
2.10	04/14/2020	F-90103000000	Date of first issue: 06/02/2015

SECTION 1. IDENTIFICATION

Product name : NEXTEL-Verdünner / Thinner 8061 farblos / transparent

Product number : 9010300000000

Manufacturer or supplier's details

Manufacturer, importer, supplier : Mankiewicz Coatings L.L.C

Address : 1200 Charleston Regional Parkway
Charleston, South Carolina 29492
USA

Telephone : +1 (843) 6547755
Telefax : +1 (843) 6547759
E-mail address : sdb_info@umco.de

Emergency telephone : CHEMTREC +1 (800) 4249300 or + (703) 5273887

Recommended use of the chemical and restrictions on use

Recommended use : Industrial serial painting

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 3

Carcinogenicity : Category 2

Specific target organ toxicity : Category 3 (Central nervous system)
- single exposure

Specific target organ toxicity : Category 2
- repeated exposure

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



SAFETY DATA SHEET



Commercial Product Name: NEXTEL-Verdünnern / Thinner 8061
Product No.: 9010300000000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2020
2.10	04/14/2020	F-90103000000	Date of first issue: 06/02/2015

Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.



SAFETY DATA SHEET



Commercial Product Name: NEXTEL-Verdünnern / Thinner 8061
Product No.: 9010300000000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2020
2.10	04/14/2020	F-90103000000	Date of first issue: 06/02/2015

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture of organic solvents, halogen-free

Components

Chemical name	CAS-No.	Concentration (% w/w)
n-butyl acetate	123-86-4	$\geq 40 - \leq 100$
xylenes	1330-20-7	$\geq 5 - < 12.5$
ethylbenzene	100-41-4	$\geq 1 - < 5$

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In all cases of doubt, or when sickness symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.
- If inhaled : Remove to fresh air, keep patient warm and at rest.
Irregular breathing/no breathing: artificial respiration.
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash skin thoroughly with soap and water or use recognised skin cleanser.
Do NOT use solvents or thinners !
- In case of eye contact : Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- If swallowed : Do NOT induce vomiting.
If accidentally swallowed obtain immediate medical attention.
Never give anything by mouth to an unconscious person.
Keep at rest.
- Most important symptoms and effects, both acute and delayed : For information on symptoms and effects refer to Section 2 Hazard statements and Section 11 Toxicological Information.
- Notes to physician : No information available.

SECTION 5. FIRE-FIGHTING MEASURES



SAFETY DATA SHEET



Commercial Product Name: NEXTEL-Verdünnern / Thinner 8061
Product No.: 9010300000000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2020
2.10	04/14/2020	F-90103000000	Date of first issue: 06/02/2015

- Suitable extinguishing media : Alcohol resistant foam, CO2, powders
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Further information : Cool endangered containers with water in case of fire.
DO NOT ALLOW RUN-OFF FROM FIRE FIGHTING TO ENTER DRAINS OR WATER COURSES!!
- Special protective equipment for fire-fighters : As in any fire, wear self-contained breathing apparatus pressure - demand, MSHA / NIOSH (approved or equivalent) and full protective gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Exclude sources of ignition and ventilate the area.
Do not inhale vapors.
Refer to protective measures listed in sections 7 and 8.
Evacuate personnel to safe areas.
- Environmental precautions : Do not let product enter drains.
If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.
- Methods and materials for containment and cleaning up : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).
Clean preferably with a detergent; avoid use of solvents.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.
Preparation may charge electrostatically: always use earthing leads when transferring from one container to another.
Operators should wear anti-static footwear and clothing. No sparking tools should be used.
Vapors are heavier than air and may spread along floors.
Vapors may form explosive mixtures with air.
- Advice on safe handling : Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentrations higher than the occupational exposure limits.
Comply with the health and safety at work laws.



SAFETY DATA SHEET



Commercial Product Name: NEXTEL-Verdünnert / Thinner 8061
Product No.: 9010300000000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2020
2.10	04/14/2020	F-90103000000	Date of first issue: 06/02/2015

Smoking, eating and drinking should be prohibited in the application area.
Observe specific national regulations for handling and use of paints.

Conditions for safe storage : Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type.
Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Further information on storage conditions : Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight.
Keep container dry in a cool, well-ventilated place.

Materials to avoid : Keep away from oxidizing agents and strongly acid or alkaline materials.

Recommended storage temperature : 41 - 95 °F / 5 - 35 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
n-butyl acetate	123-86-4	TWA	50 ppm	CR OEL
	Further information: Eye irritation, Upper Respiratory Tract irritation			
		STEL	150 ppm	CR OEL
	Further information: Eye irritation, Upper Respiratory Tract irritation			
		TWA	150 ppm 713 mg/m ³	CA AB OEL
		STEL	200 ppm 950 mg/m ³	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	150 ppm 713 mg/m ³	CA QC OEL
		STEV	200 ppm 950 mg/m ³	CA QC OEL
		VLE-PPT	150 ppm	NOM-010-STPS-2014
		VLE-CT	200 ppm	NOM-010-



SAFETY DATA SHEET



Commercial Product Name: NEXTEL-Verdünnern / Thinner 8061
Product No.: 9010300000000

Version 2.10 Revision Date: 04/14/2020 SDS Number: F-90103000000 Date of last issue: 03/27/2020
Date of first issue: 06/02/2015

				STPS-2014
		TWA	150 ppm 710 mg/m3	NIOSH REL
		ST	200 ppm 950 mg/m3	NIOSH REL
		TWA	150 ppm 710 mg/m3	OSHA Z-1
		TWA	150 ppm 710 mg/m3	OSHA P0
		STEL	200 ppm 950 mg/m3	OSHA P0
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
xylenes	1330-20-7	VLE-PPT	100 ppm	NOM-010- STPS-2014
		VLE-CT	150 ppm	NOM-010- STPS-2014
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 651 mg/m3	CA AB OEL
		TWA	100 ppm 434 mg/m3	CA AB OEL
		TWAEV	100 ppm 434 mg/m3	CA QC OEL
		STEV	150 ppm 651 mg/m3	CA QC OEL
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		STEL	150 ppm 655 mg/m3	OSHA P0
		TWA	100 ppm 435 mg/m3	OSHA P0
ethylbenzene	100-41-4	TWA	20 ppm	CR OEL
Further information: Confirmed animal carcinogen, Substances for which there is a Biological Exposure Index or Indices (see BEI section), Visual impairment, Upper Respiratory Tract irritation, Kidney damage (nephropathy)				
		TWA	100 ppm 434 mg/m3	CA AB OEL
		STEL	125 ppm 543 mg/m3	CA AB OEL
		TWA	20 ppm	CA BC OEL
		STEV	125 ppm 543 mg/m3	CA QC OEL
		TWAEV	100 ppm	CA QC OEL



SAFETY DATA SHEET



Commercial Product Name: NEXTEL-Verdünnern / Thinner 8061
Product No.: 9010300000000

Version 2.10 Revision Date: 04/14/2020 SDS Number: F-90103000000 Date of last issue: 03/27/2020
Date of first issue: 06/02/2015

			434 mg/m3	
		VLE-PPT	20 ppm	NOM-010-STPS-2014
		TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
xylenes	1330-20-7	Methyl-hippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g cre-atinine	ACGIH BEI
		Methyl-hippuric acid	Urine	End of shift	1.5 g/g cre-atinine	MX BEI
		Methyl-hippuric acids	Urine	End of shift	1.5 g/g cre-atinine	CR BEI
ethylbenzene	100-41-4	Sum of Mandelic acid plus phenylgly-oxalic acid	Urine	End of shift at end of work-week	0.7 g/g cre-atinine	MX BEI
		Sum of mandelic acid and phenyl gly-oxalic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI
		Sum of mandelic acid and phenyl gly-oxalic acid	Urine	End of shift	0.15 g/g creatinine	CR BEI



SAFETY DATA SHEET



Commercial Product Name: NEXTEL-Verdünnern / Thinner 8061
Product No.: 9010300000000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2020
2.10	04/14/2020	F-90103000000	Date of first issue: 06/02/2015

Engineering measures : Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain aerosol- and solvent vapors concentration below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection : If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators.

Use MSHA/NIOSH approved respirator if concentration exceeds recommended exposure levels.

Hand protection

Remarks : Glove permeation data does not exist for this material.
The following glove(s) should be used for splash protection only:
Appropriate material: nitrile

Eye protection : Use safety glasses or face shield (ANSI Z87.1 or approved equivalent).

Skin and body protection : Personal should wear protective clothing as necessary to prevent skin contact. All parts of the body should be washed after contact.

Protective measures : Do not eat or drink during work - no smoking.
Avoid product contact with skin, eyes and clothing.
Avoid the inhalation of dust from sanding, particulates and spray mist arising from the application of this preparation.
When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapor in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process until such time as the particulates and solvent vapor concentration has fallen below the exposure limits.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : according product name



SAFETY DATA SHEET



Commercial Product Name: NEXTEL-Verdünnern / Thinner 8061
Product No.: 9010300000000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2020
2.10	04/14/2020	F-90103000000	Date of first issue: 06/02/2015

Odor	: characteristic
pH	: Not applicable
Boiling point/boiling range	: ca. 248 °F / 120 °C
Flash point	: 79 °F / 26 °C
	Method: ISO 13736
Upper explosion limit / Upper flammability limit	: 10.0 %(V)
Lower explosion limit / Lower flammability limit	: 1.0 %(V)
Vapor pressure	: 100 hPa (122 °F / 50 °C)
Density	: 7.34 lb/gal (0.88 g/cm ³) (68 °F / 20 °C)
Solubility(ies)	
Water solubility	: insoluble
Autoignition temperature	: > 752 °F / > 400 °C
Viscosity	
Flow time	: < 12 s Cross section: 4 mm Method: DIN 53211
	< 10 s Cross section: 6 mm Method: ISO 2431

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reaction known under conditions of normal use. There are no data available on the preparation itself.
Conditions to avoid	: Stable under recommended storage and handling conditions (See section 7).



SAFETY DATA SHEET



Commercial Product Name: NEXTEL-Verdünnern / Thinner 8061
Product No.: 9010300000000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2020
2.10	04/14/2020	F-90103000000	Date of first issue: 06/02/2015

Incompatible materials : Keep away from oxidizing agents, strongly alkaline and strongly acidic materials in order to avoid exothermic reactions.

Hazardous decomposition products : When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 91.67 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:

xylenes:

Acute oral toxicity : LD50 Oral (Rat): 4,300 mg/kg

Carcinogenicity

IARC Group 2B: Possibly carcinogenic to humans
ethylbenzene 100-41-4

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Further information

Product:

Remarks : Exposure of vapor concentration in excess of the stated OEL's may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue muscular weakness,



SAFETY DATA SHEET



Commercial Product Name: NEXTEL-Verdünnern / Thinner 8061
Product No.: 9010300000000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2020
2.10	04/14/2020	F-90103000000	Date of first issue: 06/02/2015

drowsiness and in extrem cases, loss of consciousness.
Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : There are no data available on the preparation itself.

Persistence and degradability

Product:

Biodegradability : Remarks: There are no data available on the preparation itself.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: There are no data available on the preparation itself.

Mobility in soil

Product:

Mobility : Remarks: There are no data available on the preparation itself.

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : There are no data available on the preparation itself.

The product should not be allowed to enter drains or water



SAFETY DATA SHEET



Commercial Product Name: NEXTEL-Verdünnern / Thinner 8061
Product No.: 9010300000000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2020
2.10	04/14/2020	F-90103000000	Date of first issue: 06/02/2015

courses.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No.	: UN 1263
Proper shipping name	: PAINT RELATED MATERIAL
Class	: 3
Packing group	: III
Labels	: Class 3 - Flammable liquids
Packing instruction (cargo aircraft)	: 366
Packing instruction (passenger aircraft)	: 355

IMDG-Code

UN number	: UN 1263
Proper shipping name	: PAINT RELATED MATERIAL
Class	: 3
Packing group	: III
Labels	: 3
EmS Code	: <u>F-E</u> , <u>S-E</u>
Marine pollutant	: no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number	: UN 1263
Proper shipping name	: PAINT RELATED MATERIAL
Class	: 3
Packing group	: III
Labels	: Class 3 - Flammable liquids
Marine pollutant	: no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data



SAFETY DATA SHEET



Commercial Product Name: NEXTEL-Verdünnern / Thinner 8061
Product No.: 9010300000000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2020
2.10	04/14/2020	F-9010300000	Date of first issue: 06/02/2015

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Chronic Health Hazard
Flammable (gases, aerosols, liquids, or solids)
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

xylene	1330-20-7	>= 5 - < 10 %
ethylbenzene	100-41-4	>= 1 - < 5 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

xylene	1330-20-7	>= 5 - < 10 %
ethylbenzene	100-41-4	>= 1 - < 5 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

n-butyl acetate	123-86-4	>= 70 - < 90 %
xylene	1330-20-7	>= 5 - < 10 %
ethylbenzene	100-41-4	>= 1 - < 5 %

VOC content excluding water : 7 lb/gal (900 g/l)

For the calculation of VOC values in this section all substances have been considered which fall under the definition of VOC according to 40 CFR 51.100. Additionally, the calculation complies with the requirements of SCAQMD Rule 1106.1, amended February 12, 1999.

Clean Water Act

The following Hazardous Substances are listed under the U.S. Clean Water Act, Section 311, Table 116.4A:



SAFETY DATA SHEET



Commercial Product Name: NEXTEL-Verdünnern / Thinner 8061
Product No.: 9010300000000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2020
2.10	04/14/2020	F-90103000000	Date of first issue: 06/02/2015

n-butyl acetate	123-86-4	>= 70 - < 90 %
xlenes	1330-20-7	>= 5 - < 10 %
ethylbenzene	100-41-4	>= 1 - < 5 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

n-butyl acetate	123-86-4	>= 70 - < 90 %
xlenes	1330-20-7	>= 5 - < 10 %
ethylbenzene	100-41-4	>= 1 - < 5 %

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

ethylbenzene	100-41-4	>= 1 - < 5 %
--------------	----------	--------------

US State Regulations

Massachusetts Right To Know

n-butyl acetate	123-86-4
xlenes	1330-20-7
ethylbenzene	100-41-4

Pennsylvania Right To Know

n-butyl acetate	123-86-4
xlenes	1330-20-7
ethylbenzene	100-41-4

Maine Chemicals of High Concern

Product does not contain any listed chemicals

Vermont Chemicals of High Concern

ethylbenzene	100-41-4
--------------	----------

Washington Chemicals of High Concern

ethylbenzene	100-41-4
--------------	----------

California Prop. 65

WARNING: This product can expose you to chemicals including ethylbenzene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

n-butyl acetate	123-86-4
xlenes	1330-20-7
ethylbenzene	100-41-4

California Permissible Exposure Limits for Chemical Contaminants

n-butyl acetate	123-86-4
xlenes	1330-20-7
ethylbenzene	100-41-4

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory



SAFETY DATA SHEET


Commercial Product Name: NEXTEL-Verdünnern / Thinner 8061
Product No.: 9010300000000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2020
2.10	04/14/2020	F-90103000000	Date of first issue: 06/02/2015

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	*	3
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Health
0=Slightly Hazardous
1=Slightly Hazardous
2=Hazardous
3=Extreme danger
4=Deadly

Flammability
0=Will not burn
1=Flashpoint below 200 F
2=Flashpoint below 100 F
3=Flashpoint below 73 F

Instability
0=Stable
1=Unstable if heated
2=Violent chemical reaction; water reactive
3=Shock or heat may detonate
4=May detonate

Special hazard
SA Simple Asphyxiant
ACID Acid
OX Oxidizer
W Water Reactive
CORR Corrosive

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-

SAFETY DATA SHEET



Commercial Product Name: NEXTEL-Verdünnern / Thinner 8061
Product No.: 9010300000000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2020
2.10	04/14/2020	F-90103000000	Date of first issue: 06/02/2015

borne contaminants

CR BEI : Maximum allowable occupational exposure limits in the workplace - Table 3. Adopted Biological Exposure Indices

CR OEL : Costa Rica. Maximum allowable occupational exposure limits in the workplace.

MX BEI : Official Mexican Norm NOM-047-SSA1-2011, Environmental Health - Biological exposure indices for workers occupationally exposed to chemical agents

NIOSH REL : USA. NIOSH Recommended Exposure Limits

NOM-010-STPS-2014 : Mexico. Norm NOM-010-STPS-2014 on Chemicals Polluting the Work Environment - Identification, Assessment and Control - Appendix 1 Occupational Exposure Limits

OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average

ACGIH / STEL : Short-term exposure limit

CA AB OEL / TWA : 8-hour Occupational exposure limit

CA AB OEL / STEL : 15-minute occupational exposure limit

CA BC OEL / TWA : 8-hour time weighted average

CA BC OEL / STEL : short-term exposure limit

CA QC OEL / TWA EV : Time-weighted average exposure value

CA QC OEL / STEV : Short-term exposure value

CR OEL / TWA : Time weighted average 8-hr value

CR OEL / STEL : Short term exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday

NOM-010-STPS-2014 / VLE-PPT : Time weighted average limit value

NOM-010-STPS-2014 / VLE-CT : Short term exposure limit value

OSHA P0 / TWA : 8-hour time weighted average

OSHA P0 / STEL : Short-term exposure limit

OSHA Z-1 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization



SAFETY DATA SHEET



Commercial Product Name: NEXTEL-Verdünner / Thinner 8061
Product No.: 9010300000000

Version	Revision Date:	SDS Number:	Date of last issue: 03/27/2020
2.10	04/14/2020	F-90103000000	Date of first issue: 06/02/2015

tion; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 04/14/2020

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8

