

SAFETY DATA SHEET

Issuing Date: 28-Feb-2012 Revision Date: 09-Dec-2014

Revision Number: 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Code: 16708TEP Product Name: TAN EPOXY PRIMER MIL-PRF-23377K TYPE

I CLASS N, PART A

Hentzen Coatings, Inc.

Company Phone Number: 1-414-353-4200

6937 West Mill Road, Milwaukee, WI 53218-1225

Emergency telephone number ChemTrec 1-800-424-9300

Emergency telephone number offentirec 1-000-424-550

Recommended use of the chemical and restrictions on use

Industrial paint (Paint or Paint-Related), Restricted to professional users

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin Corrosion/Irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 2
Flammable Liquids	Category 2

Label Elements

Emergency Overview

DANGER

Hazard Statements

Harmful if swallowed harmful if inhaled Causes skin irritation Causes serious eye irritation May cause an allergic skin reaction Suspected of causing cancer Highly flammable liquid and vapor



Appearance Opaque

Physical state Liquid

Odor Solvent

16708TEP - TAN EPOXY PRIMER MIL-PRF-23377K TYPE I CLASS N, PART A

THE TOLDON, TANKA

Revision Date: 09-Dec-2014

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Contaminated work clothing should not be allowed out of the workplace

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/Bond container and receiving equipment

Use explosion-proof electrical/ ventilating/ lighting/ equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

If skin irritation or rash occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep cool Store in accordance with local regulations

Store in accordance with local regulations

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other information

3. COMPOSITION/INFORMATION ON INGREDIENTS

Contains a known or suspected carcinogen

This product contains substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990. See Section 15 for list of HAPS.

Chemical Name	CAS No	Weight-%	ACGIH	OSHA
BARIUM SULFATE	7727-43-7	10% - 20%	TWA: 5 mg/m³ inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica	dust TWA: 5 mg/m³ respirable
METHYL AMYL KETONE	110-43-0	10% - 20%	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m ³
BISPHENOL A/ EPICHLOROHYDRIN BASED EPOXY RESIN	25068-38-6	10% - 20%	N/A	N/A
TITANIUM DIOXIDE	13463-67-7	5% - 10%	TWA: 10 mg/m³	TWA: 15 mg/m³ total dust

16708TEP - TAN EPOXY PRIMER MIL-PRF-23377K TYPE I CLASS N, PART A

TYPE I CLASS N, PART A

METHYL ISOBUTYL KETONE	108-10-1	1% - 5%	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m ³
XYLENE(PURE)	1330-20-7	1% - 5%	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³

4. FIRST AID MEASURES

First Aid Measures

General advice Show this safety data sheet to the doctor in attendance. If symptoms persist, call a

physician.

Eye Contact Immediately flush eyes with water for at least 15 minutes. Get medical attention. If easy to

do, remove contact lenses. Keep eye wide open while rinsing. If symptoms persist, call a

Revision Date: 09-Dec-2014

physician.

Skin Contact Remove and wash contaminated clothing and gloves, including the inside, before re-use. If

skin irritation persists, call a physician. Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and

shoes.

Inhalation Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration.

Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Consult a physician if necessary. Immediate medical attention is not required. Move to fresh air in

case of accidental inhalation of vapors. If symptoms persist, call a physician.

Ingestion Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician. Rinse

mouth. Clean mouth with water and afterwards drink plenty of water. Never give anything by

mouth to an unconscious person. Consult a physician if necessary.

Self-protection of the first aider Remove all sources of ignition. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and

Effects

No information available.

Indication of any immediate medical attention and special treatment needed

Notes to physician May cause sensitization of susceptible persons. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media No information available.

Specific hazards arising from the chemical

Extremely flammable. Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by inhalation and skin contact.

Explosion Data

Sensitivity to Mechanical Impact no data available.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate

ventilation. Use personal protective equipment as required. Keep people away from and

Revision Date: 09-Dec-2014

upwind of spill/leak. Avoid breathing vapors or mists. Ventilate the area.

Environmental Precautions

Environmental Precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do

not flush into surface water or sanitary sewer system. Vapors are heavier than air, spread

along floors and form explosive mixtures with air.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up Pick up and transfer to properly labeled containers. Dam up. Soak up with inert absorbent

material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Soak up with inert

absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of

ignition. Take precautionary measures against static discharges. Use explosion-proof electrical (ventilation and lighting) equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use with local exhaust ventilation. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe vapor or mist. To dissipate static electricity during transfer, ground drum and

connect to receiving container with bonding strap. Use only non-sparking tools.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away

from heat, sparks and flame. Keep containers tightly closed in a cool, well-ventilated place.

Incompatible Products None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH	OSHA	NIOSH IDLH
BARIUM SULFATE 7727-43-7	TWA: 5 mg/m³ inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction	TWA: 10 mg/m³ total dust TWA: 5 mg/m³ respirable dust
METHYL AMYL KETONE 110-43-0	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m³	IDLH: 800 ppm TWA: 100 ppm TWA: 465 mg/m³

TALC (HYDROUS MAGNESIUM SILICATE) 14807-96-6	TWA: 2 mg/m³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	IDLH: 1000 mg/m³ TWA: 2 mg/m³ containing no Asbestos and <1% Quartz respirable dust
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m³	TWA: 15 mg/m³ total dust	IDLH: 5000 mg/m ³
METHYL ISOBUTYL KETONE 108-10-1	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m³	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m³ STEL: 75 ppm STEL: 300 mg/m³
TERTIARY BUTYL ACETATE 540-88-5	TWA: 200 ppm	TWA: 200 ppm TWA: 950 mg/m³	IDLH: 1500 ppm TWA: 200 ppm TWA: 950 mg/m³
XYLENE(PURE) 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³	

NIOSH IDLH: Immediately Dangerous to Life or Health

Exposure controls

Engineering Measures

Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Use personal protective equipment as required.

Skin and Body Protection Chemical resistant apron.

Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

Revision Date: 09-Dec-2014

provided in accordance with current local regulations.

Hygiene Measures Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work

area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state Liquid **Appearance** Opaque No data available Solvent. **Odor Threshold** Odor 16 °F / -9 °C рΗ No data available Flash Point 175 °F / 79 °C No data available **Boiling Point Decomposition temperature** Melting Point / Melting Range No data available Freezing Point No data available No data available Vapor Pressure @20°C (kPa) No data available Partition coefficient: No data available **Density Vapor Density** No data available

Bulk density No data available Specific Gravity 1.52

Evaporation Rate No data available Water solubility No data available

Dynamic viscosity No data available Weight per Gallon (lbs/gal): 12.68

Flammability Limits in Air

Upper 1.59 % Lower 0.23 %

10. STABILITY AND REACTIVITY

Reactivity
No data available

16708TEP - TAN EPOXY PRIMER MIL-PRF-23377K TYPE I CLASS N. PART A

TYPE I CLASS N, PART A

Revision Date: 09-Dec-2014

Chemical stability

Stable under recommended storage conditions.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

None known based on information supplied.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information The product has not been tested

Inhalation There is no data for this product.

Eye Contact There is no data for this product.

Skin Contact There is no data for this product.

Ingestion There is no data for this product.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
TITANIUM DIOXIDE 13463-67-7	10000 mg/kg (Rat)	N/A	N/A
METHYL ISOBUTYL KETONE 108-10-1	2080 mg/kg (Rat)	3000 mg/kg(Rabbit)	8.2 mg/L (Rat)4 h
TERTIARY BUTYL ACETATE 540-88-5	N/A	N/A	2230 mg/m³ (Rat) 4 h
XYLENE(PURE) 1330-20-7	3500 mg/kg (Rat)	4350 mg/kg(Rabbit)	29.08 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization
MUTAGENIC EFFECTS

No information available. No information available.

Carcinogenicity

This product contains one or more substances which are classified by IARC as

carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly

carcinogenic to humans (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
TALC (HYDROUS MAGNESIUM SILICATE) 14807-96-6	N/A	Group 3	N/A	N/A
TITANIUM DIOXIDE 13463-67-7	N/A	Group 2B	N/A	X
METHYL ISOBUTYL KETONE 108-10-1	А3	Group 2B	N/A	X
XYLENE(PURE) 1330-20-7	N/A	Group 3	N/A	N/A

Legend:

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity

Specific target organ systemic

toxicity (single exposure) Specific target organ systemic

toxicity (repeated exposure)

Chronic Toxicity

Target Organ Effects

No information available. No information available.

No information available.

May cause adverse liver effects. Repeated contact may cause allergic reactions in very

Revision Date: 09-Dec-2014

susceptible persons. Avoid repeated exposure.

Central nervous system (CNS), Central Vascular System (CVS), Eyes, Kidney, Liver,

Lungs, Peripheral Nervous System (PNS), Respiratory system, Skin.

Aspiration hazard

No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 1248 mg/kg
ATEmix (dermal) 15367 mg/kg
ATEmix (inhalation-dust/mist) 2.4 mg/l

Oral LD5050590 mg/kg (rat) EstimatedDermal LD50230177 mg/kg (rat) Estimated

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to daphnia and other aquatic invertebrates
METHYL AMYL KETONE 110-43-0	N/A	126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	N/A
TALC (HYDROUS MAGNESIUM SILICATE) 14807-96-6	N/A	100: 96 h Brachydanio rerio g/L LC50 semi-static	N/A
METHYL ISOBUTYL KETONE 108-10-1	400: 96 h Pseudokirchneriella subcapitata mg/L EC50	496 - 514: 96 h Pimephales promelas mg/L LC50 flow-through	170: 48 h Daphnia magna mg/L EC50
TERTIARY BUTYL ACETATE 540-88-5	N/A	296 - 362: 96 h Pimephales promelas mg/L LC50 flow-through	N/A
XYLENE(PURE) 1330-20-7	N/A	30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50	

Page 7/12

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
METHYL AMYL KETONE 110-43-0	1.98
METHYL ISOBUTYL KETONE 108-10-1	1.19
XYLENE(PURE) 1330-20-7	3.15

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste treatment methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

US EPA Waste Number D001

U159 U161 U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
METHYL ISOBUTYL KETONE 108-10-1	N/A	Included in waste stream: F039	N/A	U161
XYLENE(PURE) 1330-20-7	N/A	Included in waste stream: F039	N/A	U239

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status	
BARIUM SULFATE 7727-43-7	Toxic soluble	
XYLENE(PURE) 1330-20-7	Toxic Ignitable	

14. TRANSPORT INFORMATION

DOT

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II

Special Provisions 149, B52, IB2, T4, TP1, TP8, TP28

Description UN1263, Paint, 3, II, RQ

Emergency Response Guide

Number

128

TDG

UN-No UN1263
Proper shipping name Paint

Hazard class 3 **Packing Group** Ш

Description UN1263, Paint, 3, II

MEX

UN-No UN1263 Proper shipping name Paint **Hazard class** 3 **Packing Group**

Description UN1263, Paint, 3, II

ICAO

UN-No UN1263 Proper shipping name Paint 3 Hazard class н **Packing Group**

Special Provisions A3, A72

Description UN1263, Paint, 3, II

ICAO

UN1263 UN-No Paint Proper shipping name 3 **Hazard class Packing Group** 11

A3. A72 **Special Provisions**

UN1263, Paint, 3, II Description

IMDG/IMO

UN1263 UN-No Proper shipping name Paint 3 **Hazard class** 11 **Packing Group EmS-No** F-E, S-E **Special Provisions** 163

UN1263, Paint, 3, II Description

RID

UN-No UN1263 **Paint** Proper shipping name 3 Hazard class 11 **Packing Group Classification Code** F1

Description UN1263, Paint, 3, II

ADR/RID

UN1263 UN-No Proper shipping name Paint 3 **Hazard class Packing Group** 11 F1 **Classification Code Tunnel restriction code** (D/E)

163, 640C, 650 **Special Provisions**

Description UN1263, Paint, 3, II, (D/E)

ADR/RID-Labels

ADN

Proper shipping name Paint Hazard class 3 Packing Group п **Classification Code** F1

Special Provisions 163, 640C, 650 Description UN1263, Paint, 3, II

Limited Quantity (LQ) 5 L Ventilation VE01

15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL/NDSL Complies **EINECS/ELINCS** Complies **ENCS** Complies **IECSC** Complies Complies **KECL PICCS** Complies **AICS** Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	SARA 313 - Threshold Values %
METHYL ISOBUTYL KETONE	108-10-1	1.0
XYLENE(PURE)	1330-20-7	1.0

SARA 311/312 Hazard Categories

Yes Acute Health Hazard No **Chronic Health Hazard** Yes **Fire Hazard** Sudden Release of Pressure Hazard No **Reactive Hazard** No

CAA (Clean Air Act)

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants This product contains the following HAPs:

Chemical Name	CAS No	Hazardous air pollutants (HAPs) content
METHYL ISOBUTYL KETONE	108-10-1	Present
XYLENE(PURE)	1330-20-7	Present

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TERTIARY BUTYL ACETATE	N/A	N/A	N/A	X
XYLENE(PURE)	100 lb	N/A	N/A	X

CERCLA
This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ (reportable quantity)
METHYL ISOBUTYL KETONE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ
TERTIARY BUTYL ACETATE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ
XYLENE(PURE)	100 lb	N/A	RQ 100 lb final RQ RQ 45.4 kg final RQ

State Regulations

<u>California Proposition 65</u>
This product contains the following Proposition 65 chemicals

Chemical Name	CAS No	California Proposition 65
TITANIUM DIOXIDE	13463-67-7	Carcinogen
METHYL ISOBUTYL KETONE	108-10-1	Carcinogen
!		Developmental

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
BARIUM SULFATE	X	X	X	N/A	X
METHYL AMYL KETONE	X	X	X	N/A	X
TALC (HYDROUS MAGNESIUM SILICATE)	х	X	х	N/A	X
TITANIUM DIOXIDE	X	X	X	N/A	X
METHYL ISOBUTYL KETONE	х	х	х	Х	X
TERTIARY BUTYL ACETATE	×	Х	х	N/A	×
XYLENE(PURE)	Х	Х	X	X	X
METHYL ETHYL KETONE	X	Х	Х	X	X
BUTYL ACETATE	X	Х	X	N/A	X

International Regulations

Mexico - Grade

Serious risk, Grade 3

Chemical Name	Carcinogenic Status	Exposure Limits
METHYL AMYL KETONE	N/A	Mexico: TWA 50 ppm Mexico: TWA 235 mg/m³ Mexico: STEL 100 ppm Mexico: STEL 465 mg/m³
TALC (HYDROUS MAGNESIUM SILICATE)	N/A	Mexico: TWA 2 mg/m ³
TITANIUM DIOXIDE	N/A	Mexico: TWA 10 mg/m ³ Mexico: STEL 20 mg/m ³

METHYL ISOBUTYL KETONE	N/A	Mexico: TWA 50 ppm Mexico: TWA 205 mg/m³ Mexico: STEL 75 ppm Mexico: STEL 307 mg/m³
TERTIARY BUTYL ACETATE	N/A	Mexico: TWA 200 ppm Mexico: TWA 950 mg/m³ Mexico: STEL 250 ppm Mexico: STEL 1190 mg/m³
XYLENE(PURE)	N/A	Mexico: TWA 100 ppm Mexico: TWA 435 mg/m ³ Mexico: STEL 150 ppm Mexico: STEL 655 mg/m ³

16. OTHER INFORMATION

NFPA

Health Hazard 2

Flammability 3

Instability 0

Physical and Chemical

Revision Date: 09-Dec-2014

Hazards -

NFPA Rating



HMIS

Health Hazard 1 * Flammability 3

Physical Hazard 0 Personal protection X

Chronic Hazard Star Legend

* Chronic Health Hazard

Issuing Date:

28-Feb-2012

Revision Date:

09-Dec-2014

Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

end