



Revision Number: 006.0

Issue date: 07/06/2020

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Loctite® Naval Jelly® Rust Dissolver
Product type/use: Rust dissolver
Restriction of Use: None identified
Company address:
 Henkel Corporation
 One Henkel Way
 Rocky Hill, Connecticut 06067

IDH number: 553472
Item number: 38474
Region: United States
Contact information:
 Telephone: +1 (860) 571-5100
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: MAY BE CORROSIVE TO METALS.
 CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
 MAY CAUSE CANCER.

HAZARD CLASS	HAZARD CATEGORY
CORROSIVE TO METALS	1
SKIN CORROSION	1
SERIOUS EYE DAMAGE	1
CARCINOGENICITY	1A

PICTOGRAM(S)



Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep only in original packaging. Wash affected area thoroughly after handling. Wear protective gloves, clothing, eye and face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. Wash contaminated clothing before reuse. Absorb spillage to prevent material damage.

Storage: Store locked up. Store in corrosive resistant container with a resistant inner liner.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Phosphoric acid	7664-38-2	10 - 30
2-Propanol	67-63-0	1 - 5
Sulfuric acid	7664-93-9	0.1 - 1

IDH number: 553472

Product name: Loctite® Naval Jelly® Rust Dissolver

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. Get medical attention.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.
Unusual fire or explosion hazards:	Not flammable, however Hydrogen gas may be liberated if product contacts powdered metals or metals above 185°F.
Hazardous combustion products:	Hydrogen.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Flush with water. Neutralize acid using lime or a lime based agent compatible with the product. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling:	Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Refer to Section 8.
Storage:	Keep from freezing. Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Phosphoric acid	3 mg/m3 STEL 1 mg/m3 TWA	1 mg/m3 PEL	None	None
2-Propanol	200 ppm TWA 400 ppm STEL	400 ppm (980 mg/m3) PEL	None	None
Sulfuric acid	0.2 mg/m3 TWA Thoracic fraction.	1 mg/m3 PEL	None	None
Silica, amorphous, fumed, crystal-free	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 0.8 mg/m3 TWA	None	None

Engineering controls:	Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.
Respiratory protection:	Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.
Eye/face protection:	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.
Skin protection:	Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Gel
Color:	Pink
Odor:	Lime
Odor threshold:	Not available.
pH:	1.5 - 2.5
Vapor pressure:	Not available.
Boiling point/range:	212 °F (100°C)None Approximately
Melting point/ range:	Not applicable
Specific gravity:	1.191
Vapor density:	Not available.
Flash point:	243 °C (469.4 °F)
Flammable/Explosive limits - lower:	Not applicable
Flammable/Explosive limits - upper:	Not applicable
Autoignition temperature:	Not applicable
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Soluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	2.4 %; 28.6 g/l (calculated)
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Hydrogen, by reaction with metals.
Incompatible materials:	Caustics. Powdered metals. Reacts with alkalis or water: Heat generated, spatters !
Reactivity:	Not available.
Conditions to avoid:	Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: Causes respiratory tract irritation. Respiratory tract burns.
Skin contact: Causes skin irritation. Causes skin burns.
Eye contact: Causes serious eye damage. Causes eye irritation. May cause eye burns.
Ingestion: Harmful if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Phosphoric acid	Oral LD50 (Rat) = 1,530 mg/kg Dermal LD50 (Rabbit) = 2,740 mg/kg	Irritant, Corrosive
2-Propanol	Oral LD50 (Rat) = 5,045 mg/kg Oral LD50 (Mouse) = 3,600 mg/kg Oral LD50 (Rabbit) = 6,410 mg/kg Oral LD50 (Rat) = 4.7 g/kg Oral LD50 (Mouse) = 4.5 g/kg Oral LD50 (Rabbit) = 8.0 g/kg Oral LD50 (Rabbit) = 5.03 g/kg Dermal LD50 (Rabbit) = 12,800 mg/kg	Allergen, Central nervous system, Irritant
Sulfuric acid	None	Carcinogen, Corrosive, Irritant
Silica, amorphous, fumed, crystal-free	None	Nuisance dust

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Phosphoric acid	No	No	No
2-Propanol	No	No	No
Sulfuric acid	Known To Be Human Carcinogen.	Group 1	No
Silica, amorphous, fumed, crystal-free	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: D002: Corrosive.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Phosphoric acid solution
Hazard class or division: 8
Identification number: UN 1805
Packing group: III
DOT Hazardous Substance(s): Phosphoric acid

International Air Transportation (ICAO/IATA)

Proper shipping name: Phosphoric acid, solution
Hazard class or division: 8
Identification number: UN 1805
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name:	PHOSPHORIC ACID SOLUTION
Hazard class or division:	8
Identification number:	UN 1805
Packing group:	III

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS:	Sulfuric acid (CAS# 7664-93-9).
CERCLA/SARA Section 311/312:	Immediate Health, Delayed Health
CERCLA/SARA Section 313:	None above reporting de minimis.
CERCLA Reportable quantity:	Phosphoric acid (CAS# 7664-38-2) 5,000 lbs. (2,270 kg) 2-Propanol (CAS# 67-63-0) 100 lbs. (45.4 kg)
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
------------------------------	---

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 9

Prepared by: Product Safety and Regulatory Affairs

Issue date: 07/06/2020

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.