

PRODUCTS TECHNIQUES, INC.
Safety Data Sheet

SECTION 1 - PRODUCT & COMPANY INFORMATION

Product Name: TT-E-527D FLAT RED LOW VOC Product Code: PT-383#31136
MANUFACTURER PH: 909.877.3951
Products/Techniques, Inc. FX: 909.877.6078
3271 S. Riverside Ave. E-mail: pt@ptpaint.com
Bloomington, CA 92316 Web: www.ptpaint.com

OPERATING HOURS: 8:00 am - 4:30 pm PDT

In an emergency, call
CHEMTREC: 1.800.424.6300

SECTION 2 - HAZARDS IDENTIFICATION

HMS: 230X

GHS Ratings:

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Oral Toxicity	Acute Tox. 4	Oral LD50 < 2000 mg/kg
Dermal Toxicity	Acute Tox. 4	Dermal LD50 < 2000 mg/kg
Inhalation Toxicity	Acute Tox. 4	Gases > 2500 <= 5000 ppm Vapors > 10 <= 20 mg/l Dusts & mists > 1 <= 5 mg/l
Skin corrosive	3	Reversible adverse effects in dermal tissue Draize score >= 1.5 < 2.3
Eye corrosive	2B	Mild eye irritant Subcategory 2B Reversible in 7 days
Respiratory sensitizer	1	Respiratory sensitizer
Skin sensitizer	1	Skin sensitizer

GHS Hazards

H225	Highly flammable liquid and vapour
H302	Harmful if swallowed
H305	May be harmful if swallowed and enters airways
H313	May be harmful in contact with skin
H317	May cause an allergic skin reaction
H320	Causes eye irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled

GHS Precautions

P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/lighting equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P261	Avoid breathing dust/fume/gas/mist/vapours/spray

SDS for PT-383#31136

Page 1 of 10
Printed: 2/20/2018 at 1:54:18PM

SECTION 4 - FIRST AID MEASURES

INHALATION: If breathing problems occur during use, LEAVE AREA IMMEDIATELY and get fresh air. If breathing problems remain, SEEK IMMEDIATE MEDICAL ATTENTION.
EYE CONTACT: Flush eyes with large amounts of clean water for at least 20 minutes. Seek immediate medical attention.
SKIN CONTACT: Wash affected area thoroughly with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and launder before re-use.
INGESTION: Do not induce vomiting. Get immediate medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: 0°C (32°F)

LEL: 1.00 UEL: 8.00

All flashpoints: TCC LEL AND UEL expressed as percent (%)
EXTINGUISHING MEDIA: Alcohol foam, carbon dioxide (CO2), dry chemical, water spray/water fog extinguishing systems.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors can travel to a source of ignition and flash back. Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flashpoint. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly banded and promptly returned to a drum re-conditioner, or properly disposed of.

SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways.

SECTION 7 - HANDLING & STORAGE

HANDLING: Wear all appropriate Personal Protective Equipment (PPE). Wear appropriate respiratory protection and ensure adequate ventilation at all times as vapors can accumulate over time in enclosed spaces and poorly ventilated areas. Use product in a way that minimizes splashes and/or creation of dust. Wash with soap and water thoroughly after each use.
STORAGE: Keep away from heat, sparks and flame. Keep container closed when not in use. Store in a cool dry area at a temperature between 50 and 95 degrees F. Do not store outside in direct sunlight.

SDS for PT-383#31136

Page 3 of 10
Printed: 2/20/2018 at 1:54:18PM

P272 Contaminated work clothing should not be allowed out of the workplace
P260 Wear protective gloves/protective clothing/eye protection/face protection
P285 In case of inadequate ventilation wear respiratory protection
P321 Specific treatment (see ... on this label)
P363 Wash contaminated clothing before reuse
P302+P352 IF ON SKIN: Wash with soap and water
P303+P361+P533 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
P333+P313 If skin irritation or a rash occurs: Get medical advice/attention
P342+P311 Call a POISON CENTER or doctor/physician
P370+P378 In case of fire: Use ... for extinction
P403+P235 Store in a well ventilated place. Keep cool
P501 Dispose of contents/container to ...

Signal Word: Danger



SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
ALKYD RESIN - NOT HAZARDOUS	ALKYD RESIN	27.96%
ALKYD RESIN - NOT HAZARDOUS	LYD RESIN-CAS PROPRIETARY	18.42%
N-BUTYL ACETATE NORMAL	123-86-4	14.96%
MICRO TALC	14807-96-6	11.32%
2-PENTANONE	107-87-9	5.53%
C.I. PIGMENT RED 170	2786-76-7	4.95%
SYNTHETIC AMORPHOUS SILICA	112926-00-8	3.06%
TRADE SECRET RESIN	CAS: TRADE SECRET	2.39%
1-METHOXY-2-PROPANOL ACETATE	108-65-6	2.15%
YELLOW PIGMENT	51274-00-1	1.85%
(ETHYL-3-OXOBUTANOATO-O'-1,0'-3)-(2-DIMETHYLAMINO)ETBANOLATO)(1-METHOXY-2-PROPANOL)ALUMINUM(H1) DIMERISED	149057-70-5	1.31%
XYLENE	1330-20-7	1.13%
METHYL ISOBUTYL KETONE SOLVENT	108-10-1	1.11%
MINERAL SPIRITS	8052-41-3	1.09%
TRADE SECRET NON HAZARDOUS	PROPRIETARY SURFACTANT	0.74%
SOLVENT NAPHTHA	64742-95-6	0.58%
COBALT ADDITIVE	61789-51-3	0.49%
ADDITIVE	96-29-7	0.47%
TITANIUM DIOXIDE	13463-67-7	0.26%
VMB NAPHTHA	64742-89-8	0.15%
ETHYLBENZENE	100-41-4	0.04%
1-METHOXY-2-PROPANOL	107-58-2	0.03%

SDS for PT-383#31136

Page 2 of 10
Printed: 2/20/2018 at 1:54:18PM

SECTION 8 - EXPOSURE CONTROL AND PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
ALKYD RESIN - NOT HAZARDOUS ALKYD RESIN	Not Established	Not Established	Not Established
ALKYD RESIN - NOT HAZARDOUS ALKYD RESIN-CAS PROPRIETARY	Not Established	Not Established	Not Established
N-BUTYL ACETATE NORMAL 123-86-4	150 ppm TWA, 710 mg/m3 TWA	200 ppm STEL 150 ppm TWA	NIOSH: 150 ppm TWA 710 mg/m3 TWA 200 ppm STEL 950 mg/m3 STEL
MICRO TALC 14807-96-6	Not Established	2 mg/m3 TWA (respirable fraction, particulate matter containing no asbestos and <1% crystalline silica)	NIOSH: 2 mg/m3 TWA (respirable dust containing no asbestos and less than 1% quartz)
2-PENTANONE 107-87-9	200 ppm TWA, 700 mg/m3 TWA	150 ppm STEL	NIOSH: 150 ppm TWA 530 mg/m3 TWA
C.I. PIGMENT RED 170 2786-76-7	15 mg/m3 TWA (total dust) 5 mg/m3 TWA (respirable fraction)	10 mg/m3 TWA (inhalable fraction) 3 mg/m3 TWA (respirable fraction)	DFG MAKs: 4 mg/m3 TWA (inhalable fraction) 1.5 mg/m3 TWA (respirable fraction)
SYNTHETIC AMORPHOUS SILICA 112926-00-8	Not Established	Not Established	Not Established
TRADE SECRET RESIN CAS: TRADE SECRET	Not Established	Not Established	Not Established
1-METHOXY-2-PROPANOL ACETATE 108-65-6	TWA 50 PPM	Not Established	Not Established
YELLOW PIGMENT 51274-00-1	Not Established	Not Established	Not Established
(ETHYL-3-OXOBUTANOATO-O'-1,0'-3)-(2-DIMETHYLAMINO)ETBANOLATO)(1-METHOXY-2-PROPANOL)ALUMINUM(H1) DIMERISED 149057-70-5	Not Established	Not Established	Not Established
XYLENE 1330-20-7	100 ppm TWA, 435 mg/m3 TWA	150 ppm STEL 100 ppm TWA	Not Established
METHYL ISOBUTYL KETONE SOLVENT 108-10-1	100 ppm TWA, 410 mg/m3 TWA	75 ppm STEL 50 ppm TWA	NIOSH: 50 ppm TWA 205 mg/m3 TWA 75 ppm STEL 300 mg/m3 STEL
MINERAL SPIRITS 8052-41-3	500 ppm TWA, 2900 mg/m3 TWA	100 ppm TWA	NIOSH: 350 mg/m3 TWA 1800 mg/m3 Ceiling (15 min)

SDS for PT-383#31136

Page 4 of 10
Printed: 2/20/2018 at 1:54:18PM

TRADE SECRET NON HAZARDOUS PROPRIETARY SURFACTANT	Not Established	Not Established	Not Established
SOLVENT NAPHTHA 64742-95-6	Not Established	Not Established	Not Established
COBALT ADDITIVE 61789-51-3	Not Established	Not Established	Not Established
ADDITIVE 96-29-7	Not Established	Not Established	Not Established
TITANIUM DIOXIDE 13463-67-7	15 mg/m3 TWA (total dust)	10 mg/m3 TWA	Not Established
VM&P NAPHTHA 64742-89-6	VPEL 300ppm TWA VPEL 400ppm STEL	TLV 300ppm STEL	Not Established
ETHYLBENZENE 100-41-4	100 ppm TWA; 435 mg/m3 TWA	125 ppm STEL 100 ppm TWA	NIOSH 100 ppm TWA 435 mg/m3 TWA 125 ppm STEL 545 mg/m3 STEL
1-METHOXY-2-PROPANOL 107-98-2	Not Established	150 ppm STEL 100 ppm TWA	NIOSH 100 ppm TWA 360 mg/m3 TWA 150 ppm STEL 540 mg/m3 STEL

ENGINEERING CONTROLS Good general ventilation should be sufficient to control airborne levels. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

VENTILATION & RESPIRATORY PROTECTION Always follow all local, state, and federal laws and regulations regarding the use of respirators. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. Wear a MSHA/NIOSH approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.

ADMINISTRATIVE CONTROLS All individual company safety policies should be reviewed to determine compliance with applicable Federal, State and local safety regulations. If a company determines that threshold limit values and air quality contaminant level have not been exceeded, then that company should set its own policies regarding the use of respirators and other Personal Protective Equipment.

SKIN PROTECTION Where contact is likely wear chemical resistant gloves such as neoprene or solvent resistant nitrile. To prevent repeated or prolonged skin contact, wear impervious clothing such as a chemical suit, rubber boots, and/or chemical safety goggles plus a face shield if such should be necessary. If the equipment to be worn is not available or the type of equipment for a specific job is not known, consult a reputable safety equipment supply company. Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).

EYE PROTECTION Wear safety glasses with side shields (or goggles) and a face

	Oral LD50 5,000 mg/kg (Rat)	Dermal LD50 2,000 mg/kg (Rat)
106-10-1	METHYL ISOBUTYL KETONE SOLVENT	
	Oral LD50 2,080 mg/kg (Rat)	Inhalation LC50 8 mg/L (Rat)
61789-51-3	COBALT ADDITIVE	
	Oral LD50 3,900 mg/kg (Rat)	
96-29-7	ADDITIVE	
	Oral LD50 930 mg/kg (Rat)	Inhalation LC50 20 mg/L (Rat)
13463-67-7	TITANIUM DIOXIDE	
	Inhalation LC50 7 mg/L (Rat)	
64742-89-8	VM&P NAPHTHA	
	Oral LD50 5,000 mg/kg (Mouse)	Dermal LD50 3,000 mg/kg (Rabbit)
100-41-4	ETHYLBENZENE	
	Oral LD50 3,500 mg/kg (Rat)	Inhalation LC50 17 mg/L (Rat)
107-98-2	1-METHOXY-2-PROPANOL	
	Inhalation LC50 24 mg/L (Rat)	

INHALATION: Headaches, dizziness, nausea, decreased blood pressure, change in heart rate, and cyanosis may result from overexposure to vapor. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

INGESTION: This material may be harmful or fatal if swallowed.

SKIN CONTACT: May cause sensitization or allergic reaction.

EYE CONTACT: Direct contact with liquid exposure to vapors or mist may cause stinging, tearing, redness, swelling and eye damage.

Routes of Entry

Inhalation Skin Contact Eye Contact Ingestion

Exposure to this material may affect the following organs

Effects of Overexposure

CARCINOGENICITY

CAS Number	Description	% Weight	Carcinogen Rating
61789-51-3	COBALT ADDITIVE	0.488	Cobalt Additive, IARC Possible human carcinogen OSHA listed

ACUTE TOXICITY

INHALATION: Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

CONDITIONS AGGRAVATED: Unknown.

CHRONIC EFFECTS: Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage.

SECTION 12 - ECOLOGICAL INFORMATION			
No information available.			
Component Ecotoxicity			
N-BUTYL ACETATE NORMAL			
	96 Hr LC50 Leuciscus idus 62 mg/L [static]		
	48 Hr EC50 water flea 44 mg/L		
	96 Hr EC50 Scenedesmus subspicatus 320 mg/L, 72 Hr EC50 Scenedesmus subspicatus 674.7 mg/L		
MICRO TALC			
	96 Hr LC50 Brachydane reno >100 g/L [semi-static]		

shield

OTHER PROTECTIVE EQUIPMENT Where splashing is possible, full chemically resistant protective clothing (e.g., acid suit) and boots are required.

HYGIENIC PRACTICES Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all MSDS/label precautions even after container is empty because they may retain product residues. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid prolonged or repeated contact with skin. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES	
This product exhibits the following properties under normal conditions.	
Appearance Pigmented liquid	Odor Solvent like
Physical State Liquid	Vapor Density 4.08
Vapor Pressure 8.2 mmHg @25C	Boiling Range 0 to 212 °C, 32 to 414 °F
Wt% Solids 73.23	Weight/Gallon 9.48
VOC(g/l) Less H2O and 104.68	VOC(lbs/gal) Less H2O and 2.54
Exempt Compounds	Exempt Compounds
VOC (g/L) Material 304.68	Specific Gravity 1.14
% VOC (C.A.R.B.) 26.82	

SECTION 10 - REACTIVITY & STABILITY

STABILITY

STABLE

INCOMPATIBILITY (Materials to avoid): strong acids and bases, oxidizers, and selected amines.

CONDITIONS TO AVOID Avoid all possible sources of ignition.

Stability/Reactivity 1 - phrase code not on file

HAZARDOUS DECOMPOSITION PRODUCTS Carbon monoxide (CO) and carbon dioxide (CO2). Other unknown hazardous products are possible.

HazDecomp 2 - phrase code not on file

Hazardous polymerization will not occur

SECTION 11 - TOXICOLOGICAL INFORMATION

Mixture Toxicity:

Inhalation Toxicity LC50 504mg/L

Component Toxicity

123-86-4	N-BUTYL ACETATE NORMAL
	Inhalation LC50 390 ppm (Rat)
2786-76-7	C.I. PIGMENT RED 170
	Oral LD50 5,000 mg/kg (Rat)
106-65-6	1-METHOXY-2-PROPANOL ACETATE
	Dermal LD50 5,000 mg/kg (Rabbit)
	Inhalation LC50 100 ppm (Rat)
149057-70-5	(ETHYL-3-OXOBUTANOATO-O-1',O'3)-(2-DIMETHYLAMINOCETANGLATO)(1-METHOXYPROPAN-GLATO)ALUMINUM(H1); DIMERISED

2-PENTANONE	96 Hr LC50 Pimephales promelas 1240 mg/L [flow-through]
1-METHOXY-2-PROPANOL ACETATE	96 Hr LC50 Pimephales promelas 161 mg/L [static] 48 Hr EC50 Daphnia magna >500 mg/L
XYLENE	96 Hr LC50 Pimephales promelas 13.4 mg/L [flow-through], 96 Hr LC50 Oncorhynchus mykiss 8.05 mg/L [flow-through], 96 Hr LC50 Lepomis macrochirus 16.1 mg/L [flow-through], 96 Hr LC50 Pimephales promelas 26.7 mg/L [static] 48 Hr EC50 water flea 3.82 mg/L, 48 Hr LC50 Gammarus lacustris 0.6 mg/L
METHYL ISOBUTYL KETONE SOLVENT	96 Hr LC50 Pimephales promelas 505 mg/L [flow-through] 24 Hr EC50 water flea: 4280.0 mg/L, 48 Hr EC50 Daphnia magna 170 mg/L 96 Hr EC50 Selenastrum capricornutum 400 mg/L
ADDITIVE	96 Hr LC50 Leuciscus idus 320-1000 mg/L [static], 96 Hr LC50 Poecilia reticulata 760 mg/L [static] 48 Hr EC50 Daphnia magna 750 mg/L 72 Hr EC50 Scenedesmus subspicatus 83 mg/L
VM&P NAPHTHA	72 Hr EC50 Selenastrum capricornutum 4700 mg/L
ETHYLBENZENE	96 Hr LC50 Oncorhynchus mykiss 14.0 mg/L [static], 96 Hr LC50 Pimephales promelas 9.09 mg/L [flow-through], 96 Hr LC50 Lepomis macrochirus 150.0 mg/L [static], 96 Hr LC50 Oncorhynchus mykiss 4.2 mg/L [static], 96 Hr LC50 Lepomis macrochirus 32 mg/L [static], 96 Hr LC50 Pimephales promelas 48.5 mg/L [static], 96 Hr LC50 Poecilia reticulata: 9.6 mg/L [static] 48 Hr EC50 Daphnia magna 1.8-2.4 mg/L 72 Hr EC50 Selenastrum capricornutum 4.6 mg/L, 96 Hr EC50 Selenastrum capricornutum >438 mg/L
1-METHOXY-2-PROPANOL	96 Hr LC50 Pimephales promelas 20.8 g/L [static], 96 Hr LC50 Leuciscus idus 4600-10000 mg/L [static] 96 Hr EC50 water flea 10457 mg/L

SECTION 13 - DISPOSAL CONSIDERATIONS

It is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition. Maximize material recovery for reuse or recycling.

It is the responsibility of the user to determine if the material is a RCRA "hazardous waste" at the time of disposal. Transportation, treatment, storage, and disposal of waste material must be conducted in accordance with RCRA regulations (see 40 CFR 260 through 40 CFR 271). State and/or local regulations may be more restrictive. Contact your regional US EPA office for guidance concerning case specific disposal issues.

Non-usable product is regulated by US EPA as hazardous material under the following codes

SECTION 14 - TRANSPORTATION / SHIPPING INFORMATION

Hazardous Material Ship according to all applicable local, state, and federal regulations regarding labeling and packaging requirements.

Agency	Proper Shipping Name	UN Number	Packaging Group	Hazard Class
D.O.T.	PAINT	UN 1263	III	3

SECTION 15 - REGULATORY INFORMATION

Additional regulatory listings, where applicable.
The following chemicals are listed under California Proposition 65
61789-51-3 COBALT ADDITIVE 0.49 % Mutagen

The following chemicals appear on the New Jersey Right-To-Know Chemicals list
123-86-4 N-BUTYL ACETATE NORMAL
108-65-6 1-METHOXY-2-PROPANOL ACETATE
1330-20-7 XYLENE
108-10-1 METHYL ISOBUTYL KETONE SOLVENT
8052-41-3 MINERAL SPIRITS

The following chemicals appear on the Pennsylvania Right-To-Know list
123-86-4 N-BUTYL ACETATE NORMAL 14.96 %
108-65-6 1-METHOXY-2-PROPANOL ACETATE 2.15 %
108-10-1 METHYL ISOBUTYL KETONE SOLVENT 1.11 %
8052-41-3 MINERAL SPIRITS 1.09 %

SARA HAZARD CATEGORY The product has been reviewed according to the EPA Hazard Categories promulgated under sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

123-86-4 N-BUTYL ACETATE NORMAL Fire Hazard, Acute Health Hazard
108-65-6 1-METHOXY-2-PROPANOL ACETATE Fire Hazard, Acute Health Hazard
149057-70-5 (ETHYL-3-OXOBUTANOATE-1,3-DIMETHYLAMINO)ETBANOLATO(1-
METHOXY-PROPANOYL)ALUMINIUM(III) DIMERIZED Fire Hazard, Acute Health Hazard
1330-20-7 XYLENE Fire Hazard, Acute Health Hazard, Chronic Health Hazard
108-10-1 METHYL ISOBUTYL KETONE SOLVENT Fire Hazard, Acute Health Hazard
8052-41-3 MINERAL SPIRITS Fire Hazard
61789-51-3 COBALT ADDITIVE Fire Hazard, Acute Health Hazard, Chronic Health Hazard

TOXIC SUBSTANCES CONTROL ACT: TSCA 2018 RESET COMPLIANT

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

- None

Country	Regulation	All Components Listed
---------	------------	-----------------------

EU Risk Phrases

Safety Phrase

All ingredients are TSCA 2018 Reset Compliant. The chemical substances listed below are not on the TSCA Section 8 Inventory:

- None

SARA Section 313: The product contains the following substances subject to the reporting requirements of section 313 and Title II of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

61789-51-3 COBALT ADDITIVE 0.49%

SECTION 16 - OTHER INFORMATION

The information in this document is believed to be correct as of the date printed.

NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OR

COMPLETENESS OF THIS INFORMATION. THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT OF THE HAZARDS RELATED TO ITS USE.

This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of his use thereof.

(C) Copyright 2015 Products Techniques, Inc.

Hazardous Material Information System (HMIS)

HEALTH	2	HMIS & NFPA Hazard Rating
FLAMMABILITY	3	Legend
PHYSICAL HAZARD	0	1 = CHRONIC HEALTH HAZARD
PERSONAL PROTECTION	X	0 = INSIGNIFICANT
		1 = SLIGHT
		2 = MODERATE
		3 = HIGH

National Fire Protection Association (NFPA)



Date Prepared: 2/20/2019

Reviewer: Revision