

# Safety Data Sheet

Product Name: 440 Express

Product identifier: 100444

Revision Date: 12-14-2015

Replaces:



## 1. Identification

**Product Name:** 440 Express  
**Product identifier:** 100444  
**Relevant identified uses of the substance or mixture and uses advised against:** Elimination of pin holes

### Other means of identification

**Chemical Manufacturer / Importer / Distributor:** ITW Evercoat  
a division of Illinois Tool Works Inc.  
6600 Cornell Road  
Cincinnati, OH 45242  
513-489-7600  
**Emergency telephone number:** CHEMTREC: 1-800-424-9300  
CANUTEC: 1-613-996-6666

## 2. Hazard(s) identification

**Classification of the chemical in accordance with paragraph (d) of §1910.1200;**

**GHS Hazard**

**Symbols:**



**GHS Classification:**

Reproductive Toxicity Category 1B  
Skin Corrosion/Irritation Category 2  
Serious Eye Damage/Eye Irritation Category 2A  
Flammable Liquid Category 3  
Hazardous to the aquatic environment - Acute Category 3  
Hazardous to the aquatic environment - Chronic Category 3  
Acute Toxicity - Inhalation Dust / Mist Category 4

**GHS Signal Word:**

**GHS Hazard Statements:**

Danger  
Flammable liquid and vapour.  
Causes skin irritation.  
Causes serious eye irritation.  
Harmful if inhaled.  
May damage fertility or the unborn child.  
Harmful to aquatic life.  
Harmful to aquatic life with long lasting effects.

# Safety Data Sheet

Product Name: 440 Express

Product identifier: 100444

Revision Date: 12-14-2015

Replaces:

---

## GHS Precautionary Statements:

### Safety Precautions:

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust/fume/gas/mist/vapours/spray.  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Avoid release to the environment.  
Wear protective gloves/protective clothing/eye protection/face protection.  
Use personal protective equipment as required.

### First Aid Measures:

IF ON SKIN: Wash with plenty of soap and water.  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.  
Rinse skin with water/shower.  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF exposed or concerned: Get medical advice/attention.  
Call a POISON CENTER or doctor/physician if you feel unwell.  
Specific treatment (see on this label).  
If skin irritation occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
Take off contaminated clothing and wash before reuse.  
In case of fire: Use for extinction.

### Storage:

Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.

### Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

### Hazards not otherwise classified:

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

# Safety Data Sheet

Product Name: 440 Express

Product identifier: 100444

Revision Date: 12-14-2015

Replaces:

## 3. Composition/information on ingredients

Chemical Component:	CAS number and other unique identifiers	% (or range) of ingredient
Xylene	1330-20-7	7 - 15
Ethylene glycol monobutyl ether	111-76-2	7 - 15
Methoxy 2-propyl Acetate	108-65-6	5 - 10
Ethyl Benzene	100-41-4	1 - 5

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. First-aid measures

**Eye Contact:** Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician. Move individual away from exposure. Flush eyes gently with water for at least 15 minutes, lifting upper & lower eye lids. Seek immediate medical attention.

**Skin Contact:** Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists. Wash affected area thoroughly with soap and water. Remove contaminated clothing and continue flushing with water. Wash clothing before reuse. Seek medical advice if symptoms persist

**Inhalation:** Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately.

**Ingestion:** Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this MSDS. Remove person to fresh air. Keep warm and quiet. If breathing is difficult, give oxygen by trained personnel. Seek immediate medical attention. Do not induce vomiting unless directed to do so by medical personnel. ASPIRATION HAZARD. This material may enter the lungs during vomiting. Never give anything by mouth to an unconscious person

**Immediate medical attention and special treatment needed,:** No additional first aid information available

# Safety Data Sheet

Product Name: 440 Express

Product identifier: 100444

Revision Date: 12-14-2015

Replaces:

## 5. Fire-fighting measures

<b>Suitable extinguishing media:</b>	Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water may be ineffective but water spray can be used to extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire. Regular foam Carbon dioxide Dry chemical
<b>Unsuitable extinguishing media:</b>	No data available
<b>Fire and/or Explosion Hazards:</b>	Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back.
<b>Hazardous Combustion Products:</b>	Carbon dioxide, Carbon monoxide, Styrene oxide, Hydrocarbons
<b>Special protective equipment and precautions for fire-fighters:</b>	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Water may be used to cool closed containers to prevent pressure build-up and possible auto ignition or explosion when exposed to extreme heat. Wear a self contained breathing apparatus (NIOSH approved) with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures:</b>	Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.
<b>Methods and material for containment and cleaning up:</b>	Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. All personnel in the area should be protected as in Section 8. Ensure adequate ventilation. Keep unnecessary and unprotected

# Safety Data Sheet

Product Name: 440 Express

Product identifier: 100444

Revision Date: 12-14-2015

Replaces:

personnel from entering the area. Prevent further leakage or spillage if safe to do so. Dike area to contain the spill and prevent releases to sewers, drains or other waterways. Do not allow the spilled product to enter public drainage system or open waterways. Prevent spilled material from contaminating soil, entering sanitary sewers, storm sewers, and drainage systems, and entering bodies of water or ditches that lead to waterways. Environmental precautions Prevent spreading over a wide area Use an inert absorbent such as sand or vermiculite. Place in properly labeled closed container.

## 7. Handling and storage

**Precautions for safe handling:** Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Gas, vapor, mist, or dust may be harmful if inhaled. Do not get in eyes, on skin and clothing Remove contaminated clothing and continue flushing with water. Wash clothing before reuse. Wash thoroughly after handling Ensure adequate ventilation. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not smoke. Ground and bond containers when transferring material Use an appropriate properly fitted respirator if exposures exceed PEL/TLV values.

**Conditions for safe storage:** Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Keep away from sources of ignition Store in a tightly closed container Store in a cool dry place

**Materials to Avoid/Chemical Incompatibility::** Strong oxidizing agents Strong acids Strong alkalis Aldehydes Amines Halogenated compounds Isocyanates

## 8. Exposure controls/personal protection

### Limits:

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
Xylene	100 ppm	100 ppm	150 ppm
Ethylene glycol monobutyl ether	50 ppm	20 ppm	No data available
Ethyl Benzene	100 ppm	100 ppm	No data available

**Appropriate engineering controls.:** Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure. General or local ventilation or isolation may prove adequate to keep airborne exposures below exposure limits. Explosion proof exhaust ventilation should be used.

**Eye Protection:** Wear chemically resistant safety glasses with side shields when

# Safety Data Sheet

Product Name: 440 Express

Product identifier: 100444

Revision Date: 12-14-2015

Replaces:

handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available. Splash proof chemical goggles are recommended to protect against the splash of product. An eye wash station must be available where this product is used.

**Skin Protection:**

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. To prevent repeated or prolonged skin contact, wear impervious clothing and boots

**Respiratory Protection:**

Respiratory protection will be required when handling this product. Use respirators only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. Use a NIOSH approved respirator designed to remove particulate matter and organic solvent vapors.

**Other Protective Equipment:**

Splash proof chemical goggles are recommended to protect against the splash of product. An eye wash station must be available where this product is used. Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. To prevent repeated or prolonged skin contact, wear impervious clothing and boots

**General Hygiene Conditions:**

Gas, vapor, mist, or dust may be harmful if inhaled. Do not get in eyes, on skin and clothing. Remove contaminated clothing and continue flushing with water. Wash clothing before reuse. Wash thoroughly after handling. Ensure adequate ventilation. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not smoke. Ground and bond containers when transferring material. Use an appropriate properly fitted respirator if exposures exceed PEL/TLV values.

## 9. Physical and chemical properties

**Appearance (physical state):**

Paste

**Color:**

Grey

**Odor:**

No data available

**Odor threshold:**

No data available

**pH:**

No data available

**Melting Point/Freezing Point (°C):**

No data available

**Initial Boiling Point and Boiling Range (°C):**

139

**Flash Point (°C):**

27

# Safety Data Sheet

Product Name: 440 Express

Product identifier: 100444

Revision Date: 12-14-2015

Replaces:

Evaporation Rate:	No data available
Flammability (solid, gas):	No data available
Upper Flammable/Explosive Limit:	7
Lower Flammable/Explosive Limit:	1
Vapor Pressure:	6.72 MMHG@70F
Vapor Density:	No data available
Relative Density:	Not determined
Solubility(ies):	Insoluble
Partition coefficient: n-octanol/water:	1.36
Auto-ignition Temperature (°C):	464 °C
Decomposition Temperature::	No data available
Viscosity:	No data available
VOC (as packaged-less exempts and water)	2.9 or 347
VHAP Content by weight – as packaged	12

## 10. Stability and reactivity

Reactivity:	No data available
Chemical stability:	Stable under normal conditions.
Conditions to avoid:	None known. Open flames hot surfaces Sources of ignition.
Incompatible materials:	Strong oxidizing agents Strong acids Strong alkalis Aldehydes Amines Halogenated compounds Isocyanates
Hazardous decomposition products:	Carbon dioxide Carbon monoxide

## 11. Toxicological information

Likely routes of exposure (inhalation, ingestion, skin and eye contact):	Skin contact, Ingestion, Eye contact, Absorption
--	--

### Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation:	Can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness. At elevated temperatures may cause irritation of the eyes and respiratory tract Can cause severe central nervous system depression (including unconsciousness).
Inhalation Toxicity:	Harmful! Can cause systemic damage (see "Target Organs")
Skin Contact:	Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Skin Absorption:	Minimal hazard in normal industrial use. May cause gastrointestinal discomfort Causes skin irritation. Contact may cause irritation and possible dermatitis or sensitization. Substance can be absorbed through the skin in harmful amounts.
Eye Contact:	Can cause severe irritation. Eye contact may result in corneal injury. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Temporary vision impairment (cloudy or

# Safety Data Sheet

Product Name: 440 Express

Product identifier: 100444

Revision Date: 12-14-2015

Replaces:

<b>Ingestion Irritation:</b>	blurred vision) is possible. Can cause irritation. Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea. Irritating to mouth, throat, and stomach. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.
<b>Ingestion Toxicity:</b>	Ingestion is not an anticipated route of exposure for this material in industrial use. Harmful if swallowed. May cause systemic poisoning.
<b>Long-Term (Chronic) Health Effects:</b>	
<b>Carcinogenicity:</b>	None of the substances have been shown to cause cancer in long term animal studies. Not a carcinogen according to NTP, IARC, or OSHA. This material contains a chemical which is listed by the International Agency for Research on Cancer (IARC) as a group 2B cancer causing agent (possibly carcinogenic to humans).
<b>Reproductive and Developmental Toxicity:</b>	May damage fertility or the unborn child.
<b>Mutagenicity:</b>	No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.
<b>Inhalation:</b>	Upon prolonged and/or repeated exposure, can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness. Harmful! Can cause systemic damage upon prolonged and/or repeated exposure (see "Target Organs")
<b>Skin Contact:</b>	Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
<b>Skin Absorption:</b>	Upon prolonged or repeated exposure, minimal hazard in normal industrial use. May cause gastrointestinal discomfort.

## Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
No data available			

Has the chemical been classified as a Carcinogen by NTP, IARC or OSHA.

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
No data available			

## 12. Ecological information

<b>Ecotoxicity (aquatic and terrestrial, where available):</b>	Toxic to aquatic life with long lasting effects. Toxic to aquatic life. Harmful to aquatic life. This material is toxic to aquatic organisms and should not be released to sewage, draining systems or any body of water exceeding concentrations of approved limits under applicable regulations and permits.
<b>Persistence and degradability:</b>	No data available
<b>Mobility in soil:</b>	No data available



# Safety Data Sheet

Product Name: 440 Express

Product identifier: 100444

Revision Date: 12-14-2015

Replaces:

Other adverse effects (such as hazardous to the ozone layer): No data available

## Données sur l'écotoxicité

Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
No data available			

## 13. Disposal considerations

**Description of waste residues:** Spent or discarded material is a hazardous waste.  
**Safe Handling of Waste:** Disposal must be in accordance with applicable Federal, State/Provincial and Local regulations.  
**Waste treatment methods (including packaging):** Dispose of by incineration following Federal, State, Local, or Provincial regulations.  
**Waste Disposal Code(s):** D001

## 14. Transport information

**UN number:** UN1263  
**UN proper shipping name:** Paint  
**Transport hazard class(es):** 3  
**Packing group:** III

The shipper is responsible for following all applicable regulations. The transportation classification provided is based on ITW Evercoat original packaging, which is suitable for domestic ground transport only.

## 15. Regulatory information

**Statut TSCA:** The intentional ingredients of this product are listed.

### Regulated Components:

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
Xylene	1330-20-7	N	N	Y	N
Ethyl Benzene	100-41-4	N	N	N	Y

## 16. Other information, including date of preparation or last revision.

**Revision Date:** 12-14-2015  
**Revision Number:** 7

# Safety Data Sheet

Product Name: 440 Express

Product identifier: 100444

Revision Date: 12-14-2015

Replaces:

---

**Disclaimer:** NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances