

# PRODUCTS TECHNIQUES, INC.

## Safety Data Sheet

### SECTION 1 - PRODUCT & COMPANY INFORMATION

Product Name: WASH PRIMER YELLOW Product Code: PTI-YACID

Trade Name: NSN: 8030-01-015-6104

MANUFACTURER:  
Products/Techniques, Inc.  
3271 S. Riverside Ave.  
Bloomington, CA 92316

PH: 909.877.3951  
FX: 909.877.6078  
E-mail: [pti@ptipaint.com](mailto:pti@ptipaint.com)  
Web: [www.ptipaint.com](http://www.ptipaint.com)

OPERATING HOURS: 8:00 am - 4:30 pm PDT

In an emergency, call:  
CHEMTREC: 1.800.424.9300

### SECTION 2 - HAZARDS IDENTIFICATION

HMIS:230X

#### GHS Ratings:

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Dermal Toxicity	Acute Tox. 4	Dermal>1000+<=2000mg/kg
Inhalation Toxicity	Acute Tox. 4	Gases>2500+<=5000ppm, Vapors>10+<=20mg/l, Dusts&mists>1+<=5mg/l
Skin corrosive	3	Reversible adverse effects in dermal tissue, Draize score: >= 1.5 < 2.3
Eye corrosive	2B	Mild eye irritant: Subcategory 2B, Reversible in 7 days
Skin sensitizer	1	Skin sensitizer
Carcinogen	1A	Known Human Carcinogen Based on human evidence

#### GHS Hazards

H225	Highly flammable liquid and vapour
H302	Harmful if swallowed
H305	May be harmful if swallowed and enters airways
H313	May be harmful in contact with skin
H317	May cause an allergic skin reaction
H320	Causes eye irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H350	May cause cancer

#### GHS Precautions

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment

P241	Use explosion-proof electrical/ventilating/light/.../equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P272	Contaminated work clothing should not be allowed out of the workplace
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P321	Specific treatment (see ... on this label)
P363	Wash contaminated clothing before reuse
P302+P352	IF ON SKIN: Wash with soap and water
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P308+P313	IF exposed or concerned: Get medical advice/attention
P333+P313	If skin irritation or a rash occurs: Get medical advice/attention
P370+P378	In case of fire: Use ... for extinction
P405	Store locked up
P403+P235	Store in a well ventilated place. Keep cool
P501	Dispose of contents/container to ...

Signal Word: Danger



### SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
ETHANOL	64-17-5	52.47%
BUTANOL	71-36-3	19.87%
POLYVNYL RESIN	27360-07-2	8.53%
IPA	67-63-0	5.45%
POTASSIUM HYDROXYOCTAOXODIZINCATEDICHROMATE	11103-86-9	5.18%
ZINC HYDROXIDE	20427-58-1	3.45%
METHANOL	67-56-1	2.60%
MICRO TALC	14807-96-6	1.31%
TRADE SECRET NON HAZARDOUS	PROPRIETARY SURFACTANT	0.52%
WATER	7732-18-5	0.18%
XYLENE	1330-20-7	0.08%
1-METHOXY-2-PROPANOL ACETATE	108-65-6	0.08%
N-BUTYL ACETATE NORMAL	123-86-4	0.08%
ETHYLBENZENE	100-41-4	0.03%

(1) NON-HAZARDOUS MATERIAL

### SECTION 4 - FIRST AID MEASURES

INHALATION: If breathing problems occur during use, **LEAVE AREA IMMEDIATELY** and get fresh air. If breathing problems remain, **SEEK IMMEDIATE MEDICAL ATTENTION**.

EYE CONTACT: Flush eyes with large amounts of clean water for at least 20 minutes. Seek immediate

medical attention.

SKIN CONTACT: Wash affected area thoroughly with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and launder before re-use.

INGESTION: Do not induce vomiting. Get immediate medical attention.

## SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: 0 C (32 F)

LEL:

UEL:

All flashpoints: TCC

EXTINGUISHING MEDIA: Alcohol foam, carbon dioxide (CO<sub>2</sub>), dry chemical, water spray/water fog extinguishing systems

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors can travel to a source of ignition and flash back.

Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flashpoint. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum re-conditioner, or properly disposed of.

SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways.

## SECTION 7 - HANDLING & STORAGE

HANDLING: Wear all appropriate Personal Protective Equipment (PPE). Wear appropriate respiratory protection and ensure adequate ventilation at all times as vapors can accumulate over time in enclosed spaces and poorly ventilated areas. Use product in a way that minimizes splashes and/or creation of dust. Wash with soap and water thoroughly after each use.

STORAGE: Keep away from heat, sparks and flame. Keep container closed when not in use. Store in a cool dry area at a temperature between 50 and 95 degrees F. Do not store outside in direct sunlight.

## SECTION 8 - EXPOSURE CONTROL AND PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
ETHANOL 64-17-5	1000 ppm TWA; 1900 mg/m <sup>3</sup> TWA	1000 ppm TWA	NIOSH: 1000 ppm TWA; 1900 mg/m <sup>3</sup> TWA
BUTANOL 71-36-3	100 ppm TWA; 300 mg/m <sup>3</sup> TWA	20 ppm TWA	NIOSH: 50 ppm Ceiling; 150 mg/m <sup>3</sup> Ceiling

POLYVNYL RESIN 27360-07-2	Not Established	Not Established	Not Established
IPA 67-63-0	400 ppm TWA; 980 mg/m3 TWA	400 ppm STEL 200 ppm TWA	NIOSH: 400 ppm TWA; 980 mg/m3 TWA 500 ppm STEL; 1225 mg/m3 STEL
POTASSIUM HYDROXYOCTAOXODIZIN CATEDICHROMATE 11103-86-9	5 ug/m3 8 hr TWA 1 mg/10m3 CEIL 0.1 mg/m3 CEIL (as CrO3)	0.01 mg/m3 TWA (as Cr, listed under Zinc chromates)	NIOSH: 0.001 mg/m3 10 hr TWA (as CR)
ZINC HYDROXIDE 20427-58-1	5 mg/m3 TWA (respirable fraction) 15 mh/m3 TWA (total dust)	10 mg/m3 TWA (total dust)	Not Established
METHANOL 67-56-1	200 ppm TWA; 260 mg/m3 TWA	250 ppm STEL 200 ppm TWA	NIOSH: 200 ppm TWA; 260 mg/m3 TWA 250 ppm STEL; 325 mg/m3 STEL
MICRO TALC 14807-96-6	Not Established	2 mg/m3 TWA (respirable fraction, particulate matter containing no asbestos and <1% crystalline silica)	NIOSH: 2 mg/m3 TWA (respirable dust, containing no asbestos and less than 1% quartz)
TRADE SECRET NON HAZARDOUS PROPRIETARY SURFACTANT	Not Established	Not Established	Not Established
WATER 7732-18-5	No TLV established	No PEL established	Not Established
XYLENE 1330-20-7	100 ppm TWA; 435 mg/m3 TWA	150 ppm STEL 100 ppm TWA	Not Established
1-METHOXY-2-PROPANOL ACETATE 108-65-6	TWA 50 PPM	Not Established	Not Established
N-BUTYL ACETATE NORMAL 123-86-4	150 ppm TWA; 710 mg/m3 TWA	200 ppm STEL 150 ppm TWA	NIOSH: 150 ppm TWA; 710 mg/m3 TWA 200 ppm STEL; 950 mg/m3 STEL
ETHYLBENZENE 100-41-4	100 ppm TWA; 435 mg/m3 TWA	125 ppm STEL 100 ppm TWA	NIOSH: 100 ppm TWA; 435 mg/m3 TWA 125 ppm STEL; 545 mg/m3 STEL

**ENGINEERING CONTROLS:** Good general ventilation should be sufficient to control airborne levels. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

**VENTILATION & RESPIRATORY PROTECTION:** Always follow all local, state, and federal laws and regulations regarding the use of respirators. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is

limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. Wear a MSHA/NIOSH approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.

**ADMINISTRATIVE CONTROLS:** All individual company safety policies should be reviewed to determine compliance with applicable Federal, State and local safety regulations. If a company determines that threshold limit values and air quality contaminant level have not been exceeded, then that company should set it's own policies regarding the use of respirators and other Personal Protective Equipment.

**SKIN PROTECTION:** Where contact is likely, wear chemical resistant gloves, such as neoprene or solvent resistant nitrile. To prevent repeated or prolonged skin contact, wear impervious clothing such as a chemical suit, rubber boots, and/or chemical safety goggles plus a face shield if such should be necessary. If the equipment to be worn is not available or the type of equipment for a specific job is not known, consult a reputable safety equipment supply company. Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).

**EYE PROTECTION:** Wear safety glasses with side shields (or goggles) and a face shield.

**OTHER PROTECTIVE EQUIPMENT:** Where splashing is possible, full chemically resistant protective clothing (e.g. acid suit) and boots are required.

**HYGIENIC PRACTICES:** Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all MSDS/label precautions even after container is emptied because they may retain product residues. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid prolonged or repeated contact with skin. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

## SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES

This product exhibits the following properties under normal conditions:

<p style="text-align: center;"><b>Appearance</b> Pigmented liquid</p> <p style="text-align: center;"><b>Physical State</b> Liquid</p> <p style="text-align: center;"><b>Vapor Pressure</b> 33.6 mmHg</p> <p style="text-align: center;"><b>Wt% Solids</b> 19.47</p> <p style="text-align: center;"><b>VOC(g/l) Less H2O and Exempt Compounds</b> 710.26</p> <p style="text-align: center;"><b>VOC (g/L) Material</b> 710.26</p> <p style="text-align: center;"><b>% VOC (C.A.R.B)</b> 80.52</p>	<p style="text-align: center;"><b>Odor</b> Solvent like</p> <p style="text-align: center;"><b>Vapor Density</b> 1.86</p> <p style="text-align: center;"><b>Boiling Range</b> 64 to 118 °C, 148 to 244 °F</p> <p style="text-align: center;"><b>Weight/Gallon</b> 7.36</p> <p style="text-align: center;"><b>VOC(lbs/gal) Less H2O and Exempt Compounds</b> 5.92</p> <p style="text-align: center;"><b>Specific Gravity</b> 0.88</p>
--	---

## SECTION 10 - REACTIVITY & STABILITY

**STABILITY:**

STABLE

**INCOMPATIBILITY (Materials to avoid):** strong acids and bases, oxidizers, and selected amines.

**CONDITIONS TO AVOID:** Avoid all possible sources of ignition.

No Data

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide (CO) and carbon dioxide (CO2). Other unknown hazardous products are possible.

No Data

Hazardous polymerization will not occur.

## SECTION 11 - TOXICOLOGICAL INFORMATION

### Mixture Toxicity

Oral Toxicity LD50: 2,846mg/kg

Inhalation Toxicity LC50: 83mg/L

### Component Toxicity

64-17-5	ETHANOL Dermal LD50: 20 g/kg (Rat)
71-36-3	BUTANOL Oral LD50: 790 mg/kg (Rat) Dermal LD50: 3,400 mg/kg (Rabbit)
67-63-0	IPA Oral LD50: 4,396 mg/kg (Rat) Inhalation LC50: 73 mg/L (Rat)
7732-18-5	WATER Oral LD50: 90 mL/kg (Rat:)
100-41-4	ETHYLBENZENE Oral LD50: 3,500 mg/kg (Rat) Inhalation LC50: 17 mg/L (Rat)

**INHALATION:** Headaches, dizziness, nausea, decreased blood pressure, change in heart rate, and cyanosis may result from overexposure to vapor. **Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.**

**INGESTION:** This material may be harmful or fatal if swallowed.

**SKIN CONTACT:** May cause sensitization or allergic reaction.

**EYE CONTACT:** Direct contact with liquid, exposure to vapors or mist may cause stinging, tearing, redness, swelling and eye damage.

Routes of Entry:

Inhalation      Skin Contact      Eye Contact      Ingestion

Exposure to this material may affect the following organs:

### Effects of Overexposure

### CARCINOGENICITY:

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
11103-86-9	POTASSIUM HYDROXYOCTAOXODIZINCATE DICHROMATE	5.18	POTASSIUM HYDROXYOCTAOXODIZINCATEDI CHROMATE: IARC: Human carcinogen IARC: Human carcinogen OSHA: listed ECHA CANDIDATE LIST: Human carcinogen
64-17-5	ETHANOL	52.47	ETHANOL: OSHA: listed IARC: Group 1

### ACUTE TOXICITY:

**INHALATION: Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.**

CONDITIONS AGGRAVATED:Unknown.

CHRONIC EFFECTS: **Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage.**

## SECTION 12 - ECOLOGICAL INFORMATION

No information available.

### Component Ecotoxicity

ETHANOL	96 Hr LC50 Oncorhynchus mykiss: 12900 mg/L [flow-through] (30 days old); 96 Hr LC50 Pimephales promelas: 14.2 mg/L 48 Hr EC50 Daphnia magna: 9268 mg/L; 24 Hr EC50 Daphnia magna: 10800 mg/L
BUTANOL	96 Hr LC50 Pimephales promelas: 1730-1910 mg/L [static]; 96 Hr LC50 Pimephales promelas:1740 mg/L[ flow-through ] 48 Hr EC50 Daphnia magna: 1983 mg/L 96 Hr EC50 Scenedesmus subspicatus: >500 mg/L; 72 Hr EC50 Scenedesmus subspicatus: >500 mg/L
IPA	96 Hr LC50 Pimephales promelas: 9640 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas:11130 mg/L[ static ] 48 Hr EC50 Daphnia magna: 13299 mg/L 96 Hr EC50 Scenedesmus subspicatus: >1000 mg/L; 72 Hr EC50 Scenedesmus subspicatus: >1000 mg/L
METHANOL	96 Hr LC50 Pimephales promelas: 28100 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 13200 mg/L
MICRO TALC	96 Hr LC50 Brachydanio rerio: >100 g/L [semi-static]
XYLENE	96 Hr LC50 Pimephales promelas: 13.4 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 8.05 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 16.1 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: 26.7 mg/L [static] 48 Hr EC50 water flea: 3.82 mg/L; 48 Hr LC50 Gammarus lacustris: 0.6 mg/L
1-METHOXY-2-PROPANOL ACETATE	96 Hr LC50 Pimephales promelas: 161 mg/L [static] 48 Hr EC50 Daphnia magna: >500 mg/L
N-BUTYL ACETATE NORMAL	96 Hr LC50 Leuciscus idus: 62 mg/L [static] 48 Hr EC50 water flea: 44 mg/L 96 Hr EC50 Scenedesmus subspicatus: 320 mg/L; 72 Hr EC50 Scenedesmus subspicatus: 674.7 mg/L
ETHYLBENZENE	96 Hr LC50 Oncorhynchus mykiss: 14.0 mg/L [static]; 96 Hr LC50 Pimephales promelas: 9.09 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 150.0 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 4.2 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 32 mg/L [static]; 96 Hr LC50 Pimephales promelas: 48.5 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 9.6 mg/L [static] 48 Hr EC50 Daphnia magna: 1.8-2.4 mg/L 72 Hr EC50 Selenastrum capricornutum: 4.6 mg/L; 96 Hr EC50 Selenastrum capricornutum: >438 mg/L

## SECTION 13 - DISPOSAL CONSIDERATIONS

It is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition. Maximize material recovery for reuse or recycling.

It is the responsibility of the user to determine if the material is a RCRA "hazardous waste" at the time of disposal. Transportation, treatment, storage, and disposal of waste material must be conducted in accordance with RCRA regulations (see 40 CFR 260 through 40 CFR 271). State and/or local regulations may be more restrictive. Contact your regional US EPA office for guidance concerning case specific

disposal issues.

Non-usable product is regulated by US EPA as hazardous material under the following codes:

## SECTION 14 - TRANSPORTATION / SHIPPING INFORMATION

Hazardous Material! Ship according to all applicable local, state, and federal regulations regarding labeling and packaging requirements.

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
D.O.T.	PAINT	UN 1263	II	3
IATA	PAINT	UN 1263	II	3
IMO	PAINT	UN 1263	II	3

## SECTION 15 - REGULATORY INFORMATION

Additional regulatory listings, where applicable.

The following chemicals are listed under California Proposition 65:

64-17-5 ETHANOL 52.47 % Carcinogen  
11103-86-9 POTASSIUM HYDROXYOCTAOXODIZINCATEDICHROMATE 5.18 % Carcinogen  
67-56-1 METHANOL 2.60 % Mutagen

The following chemicals appear on the New Jersey Right-To-Know Chemicals list:

67-56-1 METHANOL

The following chemicals appear on the Pennsylvania Right-To-Know list:

67-56-1 METHANOL 2.60 %

SARA HAZARD CATEGORY: The product has been reviewed according to the EPA 'Hazard Categories' promulgated under sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

64-17-5 ETHANOL Fire Hazard, Chronic Health Hazard  
71-36-3 BUTANOL Fire Hazard, Acute Health Hazard  
67-63-0 IPA Fire Hazard, Acute Health Hazard  
11103-86-9 POTASSIUM HYDROXYOCTAOXODIZINCATEDICHROMATE Acute Health Hazard, Chronic Health Hazard  
20427-58-1 ZINC HYDROXIDE Chronic Health Hazard  
67-56-1 METHANOL Fire Hazard, Acute Health Hazard

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

- None

Country

Regulation

All Components Listed

EU Risk Phrases

Safety Phrase

The chemical substances listed below are not on the TSCA Section 8 Inventory:

- None

SARA Section 313: The product contains the following substances subject to the reporting requirements of section 313 and Title II of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

## SECTION 16 - OTHER INFORMATION

The information in this document is believed to be correct as of the date printed.

NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT OF THE HAZARDS RELATED TO ITS USE.

This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of his use thereof.


(C) Copyright, 2015 Products Techniques, Inc.

### Hazardous Material Information System (HMIS)

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X

**HMIS & NFPA Hazard Rating Legend**  
\* = Chronic Health Hazard  
0 = INSIGNIFICANT  
1 = SLIGHT  
2 = MODERATE  
3 = HIGH

### National Fire Protection Association (NFPA)



Reviewer Revision

Date Prepared: 8/14/2017