



SAFETY DATA SHEET

CONFORMS TO OSHA HAZARD COMMUNICATION
STANDARD (HCS) 29 CFR 1910.1200

Page 1 of 4
Revision Date 7/7/2016
Supersedes Date 6/30/2014

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: LUBE 45-0980 GREASE; Angle Gear Lube; DOT45-0980 Gear Lube

Part number: 45-0980; (Supersedes CPT45-0980)

1.2 Identified uses: Lubricant where there is no possibility of contact with food

Uses advised against: Not for use where there is the possibility of contact with food.

1.3 Supplier: **Apex Tool Group LLC.**

14600 York Road, Suite A

Sparks, MD 21152 USA

Email contact: www.apextoolgroup.com

Non-emergency contact: Phone: 800.688.8949 Fax: 800.234.0472

1.4 Emergency telephone: **CHEMTREC: North America & Canada:** 800.262.9300

SECTION 2. HAZARDS IDENTIFICATION

2.1 GHS Classification:

Hazard class(es): Eye Irritant Cat. 2A; Aquatic Chronic Cat. 3

2.2 Label elements

Pictograms:



Signal word: Warning

Hazard-determining components of labeling: Not applicable

Hazard statements: Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

Precautionary statements: Wash skin thoroughly after handling. Wear eye protection/face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Avoid release to the environment. Dispose of contents/ container in accordance with local/ regional/ national/ international regulations. Safety data sheet available upon request.

Additional information: Contains long-chain alkyl amine. May cause an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable

vPvB: Not applicable

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Composition	Components	%	CAS #	Impurities
	Residual oils (petroleum), solvent-dewaxed*	50-70	64742-62-7	None
	Long-chain alkylamine	<1	Proprietary	None

3.2 Additional information *Contains <3% DMSO extract as measured by IP 346.

SECTION 4. FIRST AID MEASURES

4.1 First aid measures

Eye contact: Remove contact lenses, if wearing, and flush eyes with water for at least 15 minutes or until irritation subsides. If irritation persists, consult a physician.

Skin contact: Remove clothing and shoes, if contaminated. Wash skin with soap and water. Wash or clean contaminated clothing before reuse and discard oil-soaked shoes. If irritation persists, consult a physician.

Ingestion: If swallowed, DO NOT induce vomiting. As a precaution, give the person a glass of water to drink and seek medical attention. Never give anything by mouth to an unconscious person. Consult a physician.

Inhalation: Remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention immediately.

4.2 Most important symptoms and effects, both acute and delayed.

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment available.

No further relevant information available.

SECTION 5. FIREFIGHTING MEASURES

5.1 Suitable extinguishing media: Extinguishing media include dry chemical, alcohol foam, and carbon dioxide. Do not use direct stream of water. Water may be used to keep fire-exposed containers cool.

Unsuitable extinguishing media: Do not use direct stream of water.

5.2 Special hazards: Pressure build-up due to heat exposure may cause containers to rupture. Use water spray to keep containers cool.

5.3 Advice for firefighters: Firefighters should wear full protective gear, including helmet. Use supplied-air breathing equipment for enclosed or confined space or as otherwise needed.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. Keep away from ignition sources. Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions: Prevent entry into sewers, waterways or confined areas by diking or impounding. Dike far ahead of spill for later recovery and disposal. Advise authorities if the product has entered or may enter sewers, watercourses, or extensive land areas.

6.3 Containment and clean-up: **Land spill:** Stop leak if you can do so without risk. Recover free product using non-sparking tools. Add sand, earth, or other suitable absorbent material to the spill area. Recover by pumping or with suitable absorbents. Dispose of in accordance with national and/or local regulations relating to waste disposal.
Water spill: Stop leak if you can do so without risk. Confine the spill immediately with booms. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

6.4 Reference to other sections: See Section 7 for information on safe handling. See Section 8 for information on personal protective equipment.

SECTION 7. HANDLING AND STORAGE

7.1 Handling: Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.

See Section 8.2 for information on occupational hygiene.

7.2 Storage: Store in a cool, dry place in tightly sealed containers. Store out of direct sunlight. Do not store near heat, sparks, open flame, pilot lights, static electricity, or other sources of ignition. Do not store where temperature may exceed 49°C (120°F). Store away from oxidizing agents. Rotate stock.

See Section 10 for information on conditions and materials to avoid.

7.3 End Uses: Refer to Section 1 for identified uses, and uses advised against.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Workplace exposure limits:	<u>Components</u>	<u>Exposure limit and source</u>
	Residual oils (petroleum), solvent-dewaxed*	5 mg/m ³ (oil mist), OSHA
	Long-chain alkylamine	Not available

8.2 Exposure controls

Engineering controls: Provide exhaust ventilation or other engineering controls to keep the airborne concentration of vapors below their respective occupational exposure limits.

Ventilation: Use in a well-ventilated area. See Engineering Controls.

Personal hygiene: Wash skin thoroughly after contact, before breaks and meals and at the end of the work period. Product is readily removed from skin by waterless hand cleaners followed by washing thoroughly with soap and water.

Eye protection: Chemical splash goggles or face shield in compliance with OSHA regulations are advised when eye contact may occur.

Hand protection: Any lined non-permeable rubber gloves.

Respiratory protection: Use with adequate ventilation. Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. In case of insufficient ventilation, wear suitable respiratory equipment. A NIOSH/MSHA-approved air-supplied respirator is advised in absence of proper environmental control.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 Physical and chemical properties**

Appearance / odor:	Dark gray colored lube oil with slight sulfur odor	Vapor pressure:	Not available
Physical state:	Liquid	Vapor density:	Not available
Odor threshold:	Not available	Relative density:	Not available
pH:	Not available	Solubility in water:	Insoluble
Melting / freezing point:	Not available	Partition coefficient (n-octanol/water):	Not available
Boiling point / range:	Not available	Autoignition temperature:	Not available
Flash point:	400°F (204°C), ASTM D 92	Decomposition temperature:	Not available
Evaporation rate:	Not available	Viscosity:	Not available
Upper flammability limit:	Not available	Explosive properties:	Not applicable
Lower flammability limit:	Not available	Oxidizing properties:	Not an oxidizer
Percent VOC: 0%			

9.2 Other information No further relevant information available.

SECTION 10. STABILITY AND REACTIVITY

- 10.1 Reactivity:** See sub-sections below.
- 10.2 Chemical stability:** This material is stable under normal conditions.
- 10.3 Possibility of hazardous reactions:** Hazardous reactions are not expected to occur.
- 10.4 Conditions and materials to avoid:** Avoid heat, sparks, open flames and oxidizing materials.
- 10.5 Hazardous decomposition products:** Carbon monoxide, carbon dioxide, oxides of nitrogen, oxides of sulfur, phosphates, and other products of incomplete combustion.

11.1 Information on toxicological effects

Acute toxicity / LD₅₀ and LC₅₀ of ingredients:	<u>Components</u>	<u>LD₅₀</u>	<u>LC₅₀</u>
	Residual oils (petroleum), solvent-dewaxed*	Not available	Not available
	Long-chain alkylamine	612 mg/kg (oral, rat)	Not available
Routes of exposure:	Eyes, skin, ingestion and inhalation		
Other information:	Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis, which can be fatal.		

SECTION 12. ECOLOGICAL INFORMATION

12.1 Toxicity:	<u>Components</u>	<u>L(E)C₅₀</u>
	Residual oils (petroleum), solvent-dewaxed*	Not available
	Long-chain alkylamine	Not available
Toxicity notes:	Not available	

12.2 Persistence and degradability: Not available

12.3 Bioaccumulative potential: Not available

12.4 Mobility in soil: Not available

12.5 Persistence, bioaccumulation and toxicity for substance(s): This product is not, or does not contain, a substance that is a PBT or aPvB.

12.6 Other adverse effects: No adverse effects are expected.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

methods:

Consult national or regional authorities for proper disposal and reporting procedures.

SECTION 14. TRANSPORTATION INFORMATION

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

	<u>Proper Shipping Name:</u>	<u>UN Number:</u>	<u>Hazard Class:</u>	<u>Packing Group:</u>	<u>Remarks:</u>
U.S. D.O.T.	Not regulated	None	None	None	None
ADR/RID	Not regulated	None	None	None	None
IMDG	Not regulated	None	None	None	None
IATA	Not regulated	None	None	None	None

SECTION 15. REGULATORY INFORMATION**15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture****U.S. Federal Regulations:**

SARA Section 302 Extremely Hazardous Substances This product contains greater than 1.0% of the following chemical(s) on the SARA Extremely Hazardous Substances List:
None

SARA Section 304 CERCLA Hazardous Substances Release of the following chemical(s) at quantities equal to or greater than the reportable quantities (RQ), is subject to reporting to the National Response Center under CERCLA:
None

SARA Section 313 Toxic Chemicals This product contains the following chemical(s) listed in Section 313 at or above the de minimis concentrations:
None

TSCA Inventory All components of this material are on the U.S. TSCA Inventory.

California Proposition 65 Status This product does not contain chemical(s) known to the State of California to cause birth defects or other reproductive harm.

California Proposition 65 Listed Components 2-Propenoic Acid, Ethyl Ester; Ethylene oxide; Propylene oxide; 1,4-Dioxane

International Regulations:

European Union: This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. A Chemical Safety Assessment has not been carried out.

Canada All components are in compliance with the Canadian Environmental Protection Act. This product has been classified in accordance with the hazard criteria of the CPR and this MSDS contains all the information required by CPR.

Japan MITI Not available

Australia Not available

Switzerland Not available

SECTION 16. OTHER INFORMATION

Latest Revision Date: 3/14/2016

Version 4.2

The information and recommendations contained herein are, to the best of Apex Tool Group, LLC's knowledge and belief, accurate and reliable as of the date issued. Apex Tool Group, LLC makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and Apex Tool Group, LLC shall not be liable for any loss or damage based upon the criteria supplied by the developers of these rating systems, together with Apex Tool Group LLC's interpretation of the available data.

*** END OF SDS ***